

# Exploring Data in R

Jason Thomas

November 15th, 2018

Bloomberg  
Philanthropies



DATA FOR  
HEALTH INITIATIVE



CDC Foundation

Together our impact is greater



Vital  
Strategies



THE OHIO STATE  
UNIVERSITY

INSTITUTE FOR  
POPULATION RESEARCH

In collaboration with the WHO VA Reference Group

# Quick Recap & Introduction

- ▶ Yesterday, we saw that...
  - ▶ Python is very powerful and flexible
  - ▶ there are packages, like `pandas`, that provide many useful tools
  - ▶ examples include system commands (e.g., creating directories and running other programs)
- ▶ Python's capabilities make it useful for processing verbal autopsy records.

# Motivation

- ▶ Processing Verbal Autopsy Records
  1. Download records from ODK Aggregate with Briefcase
  2. Use openVA to assign causes of death
  3. Store the CoD results – e.g., in a DHIS2 or a database
  - ▶ still need data checks! (ideally this occurs before starting the Pipeline)
  - ▶ still need to check that the results make sense!
- ▶ This process can be automated using the openVA Pipeline
  - ▶ Python3.5 package – `openva-pipeline` – with tools for performing each step for processing VA data
    - ▶ includes a tool for running all of the steps
  - ▶ There is an SQLite database that holds configuration information and CoD results
  - ▶ The pipeline can be automated to run on a set schedule (e.g., once a week)

- ▶ The openVA Pipeline package is available at the *Python Package Index*:  
<https://pypi.org/project/openva-pipeline/>
- ▶ The documentation is located at *Read the Docs*:  
<https://openva-pipeline.readthedocs.io/en/latest/>
- ▶ Source code lives on Git Hub:  
[https://github.com/verbal-autopsy-software/openva\\_pipeline](https://github.com/verbal-autopsy-software/openva_pipeline)

# openVA Pipeline: installation

- ▶ Python packages can be installed with a program called `pip3`
- ▶ If dependencies are specified, `pip3` will install these packages as well
- ▶ The `openva-pipeline` package depends on `pandas`, `pysqlcipher3`, and `requests` (these dependencies also have dependencies as well)
- ▶ In a terminal, use the following commands to list the installed packages and to install the `openva-pipeline` package (and its dependencies if necessary)

```
pip3 list  
pip3 install openVA-pipeline --user
```

- ▶ the `--user` option installs the package in the user's library (not accessible by all users on the computer)

# openVA Pipeline: functionality

- ▶ Transfer Database
  - ▶ Information needed for Pipeline, ODK, openVA, DHIS2 (e.g., ODK aggregate username and password)
  - ▶ CoD results combined with VA data
  - ▶ Event Log (includes error messages)
- ▶ The Transfer Database can be created with the following Python3 commands.

```
import openva_pipeline as ovaPL
ovaPL.createTransferDB("Pipeline.db",
                      "/home/Jason/Pipeline/",
                      "key1234")
```

- ▶ Pipeline.db is the name of the database
  - ▶ /home/tot/Pipeline is the directory where the database is created
  - ▶ key1234 is the encryption key
- ▶ DB Browser is a useful GUI for interacting with the Transfer Database

## openVA Pipeline: functionality (continued)

- ▶ The `\texttt{openva_pipeline}` can be run with the following command

```
import openva_pipeline as ovaPL
ovaPL.runPipeline("Pipeline.db",
                  "/home/Jason/Pipeline/",
                  "key1234")
```

- ▶ `Pipeline.db` is the name of the database
- ▶ `/home/tot/Pipeline` is the directory where the database is created
- ▶ `key1234` is the encryption key

- ▶ TransferDB –
  - ▶ fetch information needed by ODK, openVA, and DHIS2
  - ▶ store CoD assignments and VA records in local database
- ▶ ODK – run ODK Briefcase and merge with previous export if necessary
- ▶ openVA – create and run an R script to openVA
  - ▶ includes capabilities for running SmartVA
- ▶ DHIS – (optional) post records to the *DHIS* VA Program



## Pipeline: demonstration

For the demonstration will use the ODK Aggregate and DHIS2 servers from SwissTPH

- ▶ ODK Aggregate
- ▶ DHIS2