DYNAMIC AIR SOLUTIONS PVT. LTD.
COMPLETE AIR CONDITIONING SOLUTION

VRF & MULTI-SPLIT CENTRAL SYSTEMS

COMMERCIAL AC BROCHURE

100% Full DC Inverter Commercial HVAC Systems

From 4HP luxury villas, residences, and boutique offices to large commercial developments and multi-chassis combinations. Powered by 100% Full DC Inverter compressors and brushless fan motors for peak seasonal efficiency, expansive piping capabilities, and precise multi-zone thermal management.


4HP to Large Sizes	100% Full DC	Long Piping	50%–130%
Modular Capacity Range	Twin Rotary & Inverter Scroll	Flexible High-Rise Design	Indoor Diversity Ratio

Core Equipment Lineup & Hardware Series

HIGH PERFORMANCE




VRF Outdoor Units
4HP to Large Commercial



4-Way Round Cassette
360° Uniform Discharge



1-Way Slim Cassette
Corner & Perimeter Fit



Concealed Ductable
Mid & High ESP Solutions

Comprehensive Indoor Unit Portfolio

VERSATILE FORM FACTORS

1 Slim Duct (Concealed)
Ultra-thin height profile (200mm) designed to fit shallow false ceilings in luxury bedrooms and hotel rooms.

2 High ESP Ductable
Handles external static pressure up to 250 Pa. Ideal for extended duct runs in large offices, banks, and retail floors.

3 4-Way Round Cassette
360-degree round-flow air discharge eliminates dead corners with integrated high-lift condensate drain pump.

4 1-Way Slim Cassette
Ideal for narrow hallways, corner installations, perimeter glass glazing zones, and executive boardrooms.

5 Floor / Ceiling Convertible
Flexible horizontal under-ceiling or vertical wall/floor perimeter mounting when ceiling void space is unavailable.

6 Wall-Mounted Commercial
Architectural curved front panel for retail shops, server nodes, and cabins requiring zero ductwork fabrication.

OUTDOOR UNIT MATRIX

100% Full DC Inverter Specifications

Eco R410A / R32 High-Pressure Cycle

1. Home VRF & Light Commercial Series (Single-Chassis Compact)

4HP – 12HP

Specification	4 HP (12.1 kW)	6 HP (15.5 kW)	8 HP (22.4 kW)	12 HP (33.5 kW)
Nominal Cooling Capacity	41,200 BTU/h	52,800 BTU/h	76,400 BTU/h	114,300 BTU/h
Power Supply Spec	220-240V / 1Ph / 50Hz	380-415V / 3Ph / 50Hz	380-415V / 3Ph / 50Hz	380-415V / 3Ph / 50Hz
Max Connectable Indoors	Up to 7 Units	Up to 9 Units	Up to 13 Units	Up to 19 Units
Sound Pressure Level	53 dB(A)	55 dB(A)	57 dB(A)	60 dB(A)
Max Total Pipe Length	150 meters	250 meters	300 meters	500 meters

2. Large Commercial Modular VRF Series (Multi-Chassis Combination)

LARGE COMMERCIAL SIZES

Specification	16 HP (45.0 kW)	24 HP (67.0 kW)	32 HP (90.0 kW)	Large Commercial Modular
Nominal Cooling Capacity	153,500 BTU/h	228,600 BTU/h	307,000 BTU/h	Custom Scalable Capacity
Cabinet Configuration	Single Standalone	Single Large Chassis	Modular Combo	Multi-Module Interlink
Max Connectable Indoors	Up to 26 Units	Up to 39 Units	Up to 53 Units	Up to 64+ Units
Cooling Ambience Range	-5°C to +52°C	-5°C to +52°C	-5°C to +52°C	-5°C to +52°C
Total Piping Reach	Up to 1,000 meters	Up to 1,000 meters	Up to 1,000 meters	Up to 1,000 meters

Included Dynamic Air Solutions Turnkey Services

- ✓ Site Survey & Sizing
- ✓ Heat Load Calculation
- ✓ Professional Installation
- ✓ Testing & Commissioning
- ✓ 1-Year AMC Warranty

DYNAMIC AIR SOLUTIONS PVT. LTD.
COMPLETE AIR CONDITIONING SOLUTION

DYNAMIC AIR SOLUTIONS PVT. LTD.
Complete HVAC, Refrigeration & Cold Storage Solutions
Kathmandu, Nepal

Call: 9851123725
WhatsApp: 9715023725
Email: sdynamicair@gmail.com
Website: www.dynamicair.com.np