DYNAMIC AIR SOLUTIONS PVT. LTD.
COMPLETE AIR CONDITIONING SOLUTION

RESIDENTIAL & COMMERCIAL SYSTEMS

WALL SPLIT AC BROCHURE

Wall-Mounted Split Air Conditioner Series

Engineered for sustained thermal comfort, quiet acoustics, and rapid climate cooling. Available in both advanced **Variable-Speed Inverter** and robust **Fixed-Speed (Normal)** configurations for homes, offices, healthcare facilities, and retail spaces.

24 dB(A)	Up to 50%	100% Copper	R32 / R410A
Ultra-Quiet Sleep Mode	Inverter Energy Savings	Grooved Condenser Coils	Eco-Safe Refrigerants



Aerodynamic Indoor Profile & 4-Way Air Delivery

Curved low-profile chassis with concealed LED digital temperature read-out, motorized horizontal and vertical louvres, and multi-stage filtration to eliminate airborne dust, pollens, and lingering odors with high aerodynamic airflow efficiency.

Technology Comparison: Inverter vs. Normal Type

SELECTION MATRIX

KEY PARAMETER	INVERTER TECHNOLOGY	NORMAL (FIXED SPEED) TYPE
Compressor Action	**Variable Speed BLDC Twin Rotary**	Constant Single Speed (On/Off Cycle)
Energy Efficiency	**Consumes 40%–50% less power**	Standard rated power draw
Thermal Stability	**Continuous modulation (±0.5°C exact)**	Cyclic temperature fluctuations (±2.0°C)
Chilling Speed	**High-frequency initial turbo ramp-down**	Standard fixed-displacement run rate
Best Suited For	**Bedrooms, Living Rooms, High-run Offices**	Meeting rooms, guest cabins, server bays
Capital Investment	**Moderate upfront; low lifecycle bills**	Budget-friendly immediate purchase price

TECHNICAL SPECIFICATIONS

Engineering & Performance Data

220–240V / 1-Phase / 50Hz

1. Inverter Series (Variable Speed Cooling & Heat-Pump)

HIGH EFFICIENCY

Specification	1.0 Ton (12,000 BTU)	1.5 Ton (18,000 BTU)	2.0 Ton (24,000 BTU)
Cooling Capacity Range	3,400 – 13,000 BTU/h	5,100 – 19,500 BTU/h	6,800 – 26,000 BTU/h
Electrical Power Input	980 W (250 – 1,400 W)	1,450 W (380 – 2,100 W)	1,950 W (520 – 2,750 W)
Indoor Sound Level (H/M/L)	38 / 31 / 24 dB(A)	41 / 34 / 27 dB(A)	45 / 38 / 31 dB(A)
Airflow Volume (High)	550 m³/h (324 CFM)	820 m³/h (482 CFM)	1,100 m³/h (647 CFM)
Refrigerant / Charge	Eco-Friendly R32	Eco-Friendly R32	Eco-Friendly R32
Recommended Area	100 – 150 sq. ft.	150 – 230 sq. ft.	230 – 320 sq. ft.

2. Normal / Non-Inverter Series (Fixed Speed Heavy-Duty)

STANDARD UTILITY

Specification	1.0 Ton (12,000 BTU)	1.5 Ton (18,000 BTU)	2.0 Ton (24,000 BTU)
Rated Cooling Capacity	12,000 BTU/h (3.52 kW)	18,000 BTU/h (5.28 kW)	24,000 BTU/h (7.03 kW)
Electrical Power Input	1,180 W	1,750 W	2,300 W
Indoor Sound Level (H/M/L)	40 / 35 / 29 dB(A)	43 / 38 / 32 dB(A)	47 / 42 / 36 dB(A)
Airflow Volume (High)	520 m³/h (306 CFM)	780 m³/h (459 CFM)	1,020 m³/h (600 CFM)
Refrigerant Type	R410A / R32	R410A / R32	R410A / R32
Recommended Area	100 – 140 sq. ft.	140 – 210 sq. ft.	210 – 300 sq. ft.

Included Dynamic Air Solutions Turnkey Services

- ✓ Site Survey & Sizing
- ✓ Heat Load Calculation
- ✓ Professional Installation
- ✓ Testing & Commissioning
- ✓ 1-Year AMC Warranty

DYNAMIC AIR SOLUTIONS PVT. LTD.
Complete HVAC, Refrigeration & Cold Storage Solutions
Kathmandu, Nepal

Call: 9851123725
WhatsApp: 9715023725
Email: sdynamicair@gmail.com
Website: www.dynamicair.com.np