

NLP Assignment Solution

SECTION 1: Implementing Bag-of-Words

1. Vocabulary Construction:

Corpus:

- Post A: "cats are cute and funny"
- Post B: "dogs are funny animals"
- Post C: "cats and dogs rarely get along"

Unique Vocabulary (sorted alphabetically):

['along', 'and', 'animals', 'are', 'cats', 'cute', 'dogs', 'funny', 'get', 'rarely']

2. Dimension of the Vector:

The dimension is equal to the size of the vocabulary.

Dimension = 10

3. Matrix Construction:

Count Vectors (based on the sorted vocabulary):

- Post A: [0, 1, 0, 1, 1, 1, 0, 1, 0, 0]
- Post B: [0, 0, 1, 1, 0, 0, 1, 1, 0, 0]
- Post C: [1, 1, 0, 0, 1, 0, 1, 0, 1, 1]

Stacked Matrix Shape: (3, 10)

4. Matrix Interpretation:

- The Rows (3) represent the individual documents (Post A, Post B, Post C).
- The Columns (10) represent the unique words in the global vocabulary.
- Each cell (i, j) represents the frequency of word j in document i.

SECTION 2: Designing a simple model for classification

1. Probability Expressions:

Given $P(\text{cat}) = p$.

>Probability of a post of length 10 having NO cat =: $(1 - p)^{10}$

>Probability of a post of length 10 having AT LEAST one "cat" = $1 - (1 - p)^{10}$

>General expression for post of length L being cat-type

$$P(\text{cat-type}) = 1 - (1 - p)^L$$

2. Probability Vector Calculation:

Total words in corpus = 5 (A) + 4 (B) + 6 (C) = 15 words.

Frequency of "cats" in corpus = 2 (once in A, once in C).

$$\text{Probability } P = 2 / 15 \approx 0.133$$

Theoretical probability of Post A (Length L=5) being cat-type:

$$P(\text{Post A is cat-type}) = 1 - (1 - 2/15)^5$$

$$P(\text{Post A is cat-type}) \approx 1 - (0.487)$$

$$P(\text{Post A is cat-type}) \approx 0.513 \text{ (or 51.3\%)}$$

3. Conditional Probability (Bayes):

Let A = Post contains cute

Let B = Post is cat-type

From the corpus:

- Cat-type posts are Post A and Post C (Total = 2).

- Post A contains "cute". Post C does not.

$P(A|B)$ [Probability it contains "cute" given it is cat-type]:

$$= (\text{Number of cat-type posts with "cute"}) / (\text{Total cat-type posts})$$

$$= 1 / 2 = 0.5$$

In this corpus, there is a 50% chance that a discussion about cats involves them being cute.

Using Bayes Theorem, we find $P(B|A)$ [Probability it is cat-type given it contains "cute"]:

$$P(B|A) = (P(A|B) * P(B)) / P(A)$$

$$- P(A|B) = 0.5$$

$$- P(B) \text{ [Prior probability of being cat-type]} = 2 \text{ posts out of } 3 = 2/3$$

$$- P(A) \text{ [Prior probability of containing "cute"]} = 1 \text{ post out of } 3 = 1/3$$

$$P(B|A) = (0.5 * 0.666...) / 0.333...$$

$$P(B|A) = 1.0$$

If a post contains "cute", it is 100% certain to be a cat-type post in this specific corpus.

SECTION 3: Designing a simple model for Optimising Upvotes

1. Maximizing Upvotes $U(L)$:

$$\text{Function: } U(L) = (-1/20)L^2 + 3L$$

First Derivative $U'(L)$:

$$U'(L) = (-2/20)L + 3$$

$$U'(L) = -0.1L + 3$$

Set $U'(L) = 0$ to find critical point:

$$0 = -0.1L + 3$$

$$0.1L = 3$$

$$L = 30$$

Second Derivative Test $U''(L)$:

$$U''(L) = -0.1$$

Since $U''(L)$ is negative, the function is concave down, confirming $L = 30$ is a Maximum.

Optimum length = 30 words.

2. Optimizing $G(L, p)$:

$$G(L, p) = [1 - (1-p)^L] * [(-1/20)L^2 + 3L]$$

Suggestion for finding optimum without derivatives:

Since the function is complex and non-linear, and analytical derivatives might be difficult to solve for roots, we can use Numerical Optimization methods such as:

1. Gradient Descent: Iteratively moving in the direction of the steepest ascent.

2. Grid Search: Since L must be an integer, we can evaluate the function at discrete intervals of L to find the peak.

I also plotted a graph to portray the upvote function, the expected upvote function for the cat type post and cat +cut type post.

It is given in the folder