# Database – No SQL – Mongodb

## Session 3 –

1. **Create a MongoDB collection named 'restaurants' and use insertOne to add a new restaurant document with fields: name, cuisine, location, and rating.**

**Ans:**

```
db.createCollection("restaurants")

db.restaurants.insertOne({
    name: "Spice Garden",
    cuisine: "Indian",
    location: "Vadodara",
    rating: 4.5
})
```

2. **Use insertMany to add 3 new documents to the 'movies' collection, each representing a different movie with fields: title, genre, releaseYear, and imdbRating.<br><br>Hint: Think of movies currently trending on BookMyShow or Netflix.**

**Ans:**

```
db.movies.insertMany([
    {
        title: "Interstellar",
        genre: "Sci-Fi",
        releaseYear: 2014,
        imdbRating: 8.7
    },
    {
        title: "Inception",
        genre: "Sci-Fi",
        releaseYear: 2010,
        imdbRating: 8.8
    },
    {
        title: "3 Idiots",
        genre: "Comedy/Drama",
        releaseYear: 2009,
        imdbRating: 8.4
    }
])
```

3. **Write a query using find to display all products from a 'flipkart_products' collection where the price is less than 1000.**

**Ans:**

```
db.flipkart_products.find({
    price: { $lt: 1000 }
})
```

**For readable output:**

```
db.flipkart_products.find({
    price: { $lt: 1000 }
}).pretty()
```

4. **Update the rating of a restaurant named 'Burger Hub' in the 'restaurants' collection to 4.7 using updateOne.**

**Ans:**

```
db.restaurants.updateOne(
    { name: "Burger Hub" },
    { $set: { rating: 4.7 } }
)
```

**You can verify the update with:**

```
db.restaurants.find({ name: "Burger Hub" }).pretty()
```

5. **Delete all orders from an 'orders' collection where the status is 'cancelled' using deleteMany.<br><br>Constraint: Only delete documents with status exactly equal to 'cancelled'.**

**Ans:**

```
db.orders.deleteMany({
    status: "cancelled"
})
```