SE – Introduction to Web Technologies – HTML and CSS

Session – 11

1. **Create an HTML page that uses Bootstrap utility classes to add 3 different levels of spacing (margin and padding) around a card displaying a Flipkart-style product image and name.**

Ans : -

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Flipkart Product</title>

    <link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet">
</head>
<body>

<div class="container mt-5">

    <div class="card m-3 p-4">

        <img src="https://via.placeholder.com/200"
             class="card-img-top p-2"
             alt="Product">

        <div class="card-body">

            <h5 class="card-title mt-2">
                Samsung Galaxy S25
            </h5>

        </div>

    </div>

</div>

</body>
</html>
```

2. **Build a movie review card (like BookMyShow) using Bootstrap typography utilities to style the movie title, rating, and review text with different font weights and sizes.**

Ans : -

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Movie Review</title>

    <link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet">
</head>
<body>

<div class="container mt-5">

<div class="card p-4">

    <h2 class="fw-bold display-6">
        Avengers: Endgame
    </h2>

    <p class="fs-4 fw-semibold text-warning">
        ⭐ 4.8/5
    </p>

    <p class="fs-6 fw-light">
        A thrilling superhero movie with action,
        emotion, and spectacular visual effects.
    </p>

</div>

</div>

</body>
</html>
```

3. **Design a Zomato-style restaurant list where each restaurant card uses at least three different Bootstrap color utility classes to highlight ratings, offers, and open/closed status.**

Ans : -

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Restaurant List</title>

    <link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet">
</head>
<body>

<div class="container mt-5">

<div class="card p-3 mb-3">

    <h4>Spice Garden</h4>

    <span class="badge bg-success">
        Rating: 4.5
    </span>

    <span class="badge bg-warning text-dark">
        20% OFF
    </span>

    <span class="badge bg-success">
        Open
    </span>

</div>

<div class="card p-3">

    <h4>Pizza Hub</h4>

    <span class="badge bg-primary">
        Rating: 4.2
    </span>

    <span class="badge bg-danger">
        Flat ₹100 OFF
    </span>

    <span class="badge bg-secondary">
        Closed
    </span>
```

```
</div>

</div>

</body>
</html>
```

4. **Override the Bootstrap primary button color in your own CSS file to use a custom shade (not the default blue), and apply it to a 'Book Ticket' button on your page.

Hint: Use the CSS selector .btn-primary in your custom stylesheet and link it after the Bootstrap CSS.**

Ans : -

index.html :

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">

    <title>Book Ticket</title>

    <link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet">

    <link rel="stylesheet" href="style.css">
</head>
<body>

<div class="container mt-5">

<button class="btn btn-primary">
    Book Ticket
</button>

</div>

</body>
</html>
```

style.css :

```
.btn-primary{
    background-color:#8e44ad;
```

```
    border-color:#8e44ad;
}

.btn-primary:hover{
    background-color:#6c3483;
    border-color:#6c3483;
}
```

5. **Add a theme switcher button to your page that toggles between a light and dark background using Bootstrap classes, and updates the text color for readability.

Hint: Use JavaScript to toggle 'bg-light'/'bg-dark' and 'text-dark'/'text-light' classes on the main container.**

Ans : -

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Theme Switcher</title>

    <link
href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
rel="stylesheet">
</head>
<body>

<div id="mainContainer"
     class="container mt-5 p-4 bg-light text-dark rounded">

    <h2>BookMyShow</h2>

    <p>Movie Details Page</p>

    <button class="btn btn-primary"
            onclick="toggleTheme()">
        Switch Theme
    </button>

</div>

<script>

function toggleTheme(){

    const container = document.getElementById("mainContainer");
```

```
    container.classList.toggle("bg-light");
    container.classList.toggle("bg-dark");

    container.classList.toggle("text-dark");
    container.classList.toggle("text-light");
}

</script>

</body>
</html>
```