

Computational Genomics (0382.3102)

Lecture 5

Multiple Sequence Alignment: Hueristics; A 2-Approximation Algorithm

Prof. Benny Chor

School of Computer Science

Tel-Aviv University

Based in part on MSA sections in Gusfield's book,
and chapter 3 in Kanehisa's book

MSA is Hard

- Input: Sequences S_1, S_2, \dots, S_k , $k \geq 3$.

MSA is Hard

- Input: Sequences S_1, S_2, \dots, S_k , $k \geq 3$.
- Typical sequences' lengths $n_1, n_2, \dots, n_k \approx$ a few hundreds for AAs, 1000-2000 bp for DNA sequences.

MSA is Hard

- Input: Sequences S_1, S_2, \dots, S_k , $k \geq 3$.
- Typical sequences' lengths $n_1, n_2, \dots, n_k \approx$ a few hundreds for AAs, 1000-2000 bp for DNA sequences.
- DP on the full k -dim box of volume $n_1 \times n_2 \times \dots \times n_k$ takes $O(n_1 \cdot n_2 \cdot \dots \cdot n_k \cdot 2^k)$.

MSA is Hard

- Input: Sequences S_1, S_2, \dots, S_k , $k \geq 3$.
- Typical sequences' lengths $n_1, n_2, \dots, n_k \approx$ a few hundreds for AAs, 1000-2000 bp for DNA sequences.
- DP on the full k -dim box of volume $n_1 \times n_2 \times \dots \times n_k$ takes $O(n_1 \cdot n_2 \cdot \dots \cdot n_k \cdot 2^k)$.
- Such running time is very slow even for $k = 3$, and totally infeasible for $k \geq 6$.

MSA is Hard

- Input: Sequences S_1, S_2, \dots, S_k , $k \geq 3$.
- Typical sequences' lengths $n_1, n_2, \dots, n_k \approx$ a few hundreds for AAs, 1000-2000 bp for DNA sequences.
- DP on the full k -dim box of volume $n_1 \times n_2 \times \dots \times n_k$ takes $O(n_1 \cdot n_2 \cdot \dots \cdot n_k \cdot 2^k)$.
- Such running time is very slow even for $k = 3$, and totally infeasible for $k \geq 6$.
- Certain versions of MSA are known to be NPH, so an exact poly time (poly in what?) is unlikely.

Coping with NP hardness

- Several (of many) approaches:

Coping with NP hardness

- Several (of many) approaches:
- Hueristics.

Coping with NP hardness

- Several (of many) approaches:
- Hueristics.
- Fixed parameter complexity.

Coping with NP hardness

- Several (of many) approaches:
- Hueristics.
- Fixed parameter complexity.
- Poly time **approximation** algorithms.

MSA Hueristics

- Several (of many) approaches:

MSA Hueristics

- Several (of many) approaches:
- Searching only a **promising subset** of the k -dim box (used by Carillo-Lipman).

MSA Hueristics

- Several (of many) approaches:
- Searching only a **promising subset** of the k -dim box (used by Carillo-Lipman).
- Progressive pairwise alignment (used in CLUSTALW, a very popular package).

MSA Hueristics

- Several (of many) approaches:
- Searching only a **promising subset** of the k -dim box (used by Carillo-Lipman).
- Progressive pairwise alignment (used in CLUSTALW, a very popular package).

Fixed Parameter Complexity

- Is MSA in **FTP**?

Approximation Algorithms

- Gusfield 2-approximation algorithm.

Approximation Algorithms

- Gusfield 2-approximation algorithm.
- Setting: Sum of pairs. Distance Measure.

Dry Run of 2 Approx. MSA

- Four Sequences: S_1, S_2, S_3, S_4 .

Dry Run of 2 Approx. MSA

- Four Sequences: S_1, S_2, S_3, S_4 .
- $d(\text{mismatch}) = 3, d(\text{indel}) = 2$
(triangle inequality holds).

Dry Run of 2 Approx. MSA

- Four Sequences: S_1, S_2, S_3, S_4 .
- $d(\text{mismatch}) = 3, d(\text{indel}) = 2$
(triangle inequality holds).

Dry Run of 2 Approx. MSA

- Four Sequences: S_1, S_2, S_3, S_4 .
- $d(\text{mismatch}) = 3$, $d(\text{indel}) = 2$
(triangle inequality holds).
- $S_1 = \text{AAAAAAAAAAAAA}$
 $S_2 = \text{AAAAAAAAAAAAAC}$
 $S_3 = \text{AAAAAAGAAAAA}$
 $S_4 = \text{TAAAAAAAAAAAAAA}$

Dry Run of 2 Approx. MSA

- Four Sequences: S_1, S_2, S_3, S_4 .
- $d(\text{mismatch}) = 3, d(\text{indel}) = 2$
(triangle inequality holds).
- $S_1 = \text{AAAAAAAAAAAAA}$
 $S_2 = \text{AAAAAAAAAAAAAC}$
 $S_3 = \text{AAAAAAGAAAAA}$
 $S_4 = \text{TAAAAAAAAAAAAA}$
- $d(S_1, S_i) = 3, d(S_i, S_j) = 4$.

Dynamics of Progressive MSA

Dynamics of Progressive MSA

$$\begin{aligned} 1) \quad S_1 &= \text{AAAAAAAAAAAAA-} \\ S_2 &= \text{AAAAAAAAAAAAAC} \end{aligned}$$

Dynamics of Progressive MSA

$$\begin{aligned} 1) \quad S_1 &= \text{AAAAAAAAAAAAA-} \\ S_2 &= \text{AAAAAAAAAAAAAC} \end{aligned}$$

Dynamics of Progressive MSA

- 1) $S_1 = \text{AAAAAAAAAAAAA-}$
 $S_2 = \text{AAAAAAAAAAAAAC}$
- 2) $S_1 = \text{AAAAAA-AAAAA-}$
 $S_2 = \text{AAAAAA-AAAAAC}$
 $S_3 = \text{AAAAAAGAAAAA-}$

Dynamics of Progressive MSA

- 1) $S_1 = \text{AAAAAAAAAAAAA-}$
 $S_2 = \text{AAAAAAAAAAAAAC}$
- 2) $S_1 = \text{AAAAAA-AAAAA-}$
 $S_2 = \text{AAAAAA-AAAAAC}$
 $S_3 = \text{AAAAAAGAAAAA-}$

Dynamics of Progressive MSA

1) $S_1 = \text{AAAAAAAAAAAAA-}$
 $S_2 = \text{AAAAAAAAAAAAAC}$

2) $S_1 = \text{AAAAAA-AAAAA-}$
 $S_2 = \text{AAAAAA-AAAAAC}$
 $S_3 = \text{AAAAAAGAAAAA-}$

3) $S_1 = \text{-AAAAAA-AAAAA-}$
 $S_2 = \text{-AAAAAA-AAAAAC}$
 $S_3 = \text{-AAAAAAGAAAAA-}$
 $S_4 = \text{TAAAAAA-AAAAA-}$

Dynamics of Progressive MSA

1) $S_1 = \text{AAAAAAAAAAAAA-}$
 $S_2 = \text{AAAAAAAAAAAAAC}$

2) $S_1 = \text{AAAAAA-AAAAA-}$
 $S_2 = \text{AAAAAA-AAAAAC}$
 $S_3 = \text{AAAAAAGAAAAA-}$

3) $S_1 = \text{-AAAAAA-AAAAA-}$
 $S_2 = \text{-AAAAAA-AAAAAC}$
 $S_3 = \text{-AAAAAAGAAAAA-}$
 $S_4 = \text{TAAAAAA-AAAAA-}$

General Analysis of MSA Quality

- Denote $D(S_i, S_j) = \text{MSA-induced distance of } S_i, S_j$.

General Analysis of MSA Quality

- Denote $D(S_i, S_j)$ = MSA-induced distance of S_i, S_j .
- Denote $d(S_i, S_j)$ = optimal (pairwise-induced) distance of S_i, S_j .

General Analysis of MSA Quality

- Denote $D(S_i, S_j) = \text{MSA-induced distance of } S_i, S_j$.
- Denote $d(S_i, S_j) = \text{optimal (pairwise-induced) distance of } S_i, S_j$.
- By algorithm, $D(S_1, S_j) = d(S_1, S_j)$.

More Analysis of MSA Quality

- By triangle inequality,

$$\begin{aligned} D(S_i, S_j) &\leq D(S_i, S_1) + D(S_1, S_j) \\ &= d(S_i, S_1) + d(S_1, S_j) \end{aligned}$$

More Analysis of MSA Quality

- By triangle inequality,

$$\begin{aligned} D(S_i, S_j) &\leq D(S_i, S_1) + D(S_1, S_j) \\ &= d(S_i, S_1) + d(S_1, S_j) \end{aligned}$$

- Thus

$$\begin{aligned} \sum_{i=1}^k \sum_{j=i+1}^k D(S_i, S_j) &\leq \sum_{i=1}^k \sum_{j=i+1}^k d(S_i, S_1) \\ &\quad + \sum_{i=1}^k \sum_{j=i+1}^k d(S_1, S_j) \end{aligned}$$

More Analysis of MSA Quality

- By triangle inequality,

$$\begin{aligned} D(S_i, S_j) &\leq D(S_i, S_1) + D(S_1, S_j) \\ &= d(S_i, S_1) + d(S_1, S_j) \end{aligned}$$

- Thus

$$\begin{aligned} \sum_{i=1}^k \sum_{j=i+1}^k D(S_i, S_j) &\leq \sum_{i=1}^k \sum_{j=i+1}^k d(S_i, S_1) \\ &\quad + \sum_{i=1}^k \sum_{j=i+1}^k d(S_1, S_j) \end{aligned}$$

- Standard arithmetic now implies 2 approx. ratio (in fact $2 - 1/k$).

More Analysis of MSA Quality

- By triangle inequality,

$$\begin{aligned} D(S_i, S_j) &\leq D(S_i, S_1) + D(S_1, S_j) \\ &= d(S_i, S_1) + d(S_1, S_j) \end{aligned}$$

- Thus

$$\begin{aligned} \sum_{i=1}^k \sum_{j=i+1}^k D(S_i, S_j) &\leq \sum_{i=1}^k \sum_{j=i+1}^k d(S_i, S_1) \\ &\quad + \sum_{i=1}^k \sum_{j=i+1}^k d(S_1, S_j) \end{aligned}$$

- Standard arithmetic now implies 2 approx. ratio (in fact $2 - 1/k$).
- See Gusfield for full details.