

SOCIALSPHEAR

Public API Specification

Version 1.0 | Base URL: <https://api.socialsphear.com/v1>

1. API Overview

The SocialSphear Public REST API enables developers to integrate SocialSphear's scheduling and analytics capabilities into their own tools, automate workflows, and build on top of the platform. The API is available on all paid plans (Creator and above).

Property	Value
Base URL	https://api.socialsphear.com/v1
Protocol	HTTPS only — HTTP requests are rejected with 301
Format	JSON — all requests and responses use application/json
Authentication	Bearer token — API key in Authorization header
Rate limiting	100 requests/min (Creator), 500/min (Pro), 2,000/min (Agency)
Pagination	Cursor-based — use <code>next_cursor</code> and <code>limit</code> parameters
Versioning	URL versioning — <code>/v1/</code> prefix. Breaking changes release as <code>/v2/</code>
Documentation	https://docs.socialsphear.com/api
Status page	https://status.socialsphear.com
Support	api-support@socialsphear.com

1.1 Authentication

All API requests require an API key sent as a Bearer token in the Authorization header. Generate API keys from your workspace Settings, then Developer, then API Keys.

```
# Example request with API key authentication
curl -X GET https://api.socialsphear.com/v1/posts \
  -H "Authorization: Bearer sk_live_your_api_key_here" \
  -H "Content-Type: application/json"
```

1.2 Standard Response Format

```
// Success response
{
  "success": true,
  "data": { ... },
  "meta": {
    "request_id": "req_01HX8K9M2P",
    "timestamp": "2026-06-01T09:00:00Z"
  }
}

// Error response
{
```

```
"success": false,
"error": {
  "code": "RESOURCE_NOT_FOUND",
  "message": "Post with ID post_abc123 not found",
  "status": 404
},
"meta": {
  "request_id": "req_01HX8K9M2P",
  "timestamp": "2026-06-01T09:00:00Z"
}
}
```

1.3 Error Codes

HTTP Status	Error Code	Meaning
400	INVALID_REQUEST	Request body or parameters are malformed or missing required fields
401	UNAUTHORIZED	API key is missing, invalid, or revoked
403	FORBIDDEN	API key lacks permission for this workspace or resource
404	RESOURCE_NOT_FOUND	The requested resource does not exist
409	CONFLICT	Request conflicts with current state (e.g. duplicate schedule)
422	UNPROCESSABLE	Request is valid but cannot be processed (e.g. past scheduled time)
429	RATE_LIMITED	Too many requests — see Retry-After header for wait time
500	INTERNAL_ERROR	SocialSphear server error — contact api-support@socialsphear.com

2. Workspaces

A workspace represents one brand or client. All posts, social accounts, and team members belong to a workspace. Your API key is scoped to a specific workspace.

Method	Endpoint	Description	Auth
GET	/workspaces/me	Get the workspace associated with the current API key	Required
PATCH	/workspaces/me	Update workspace name or logo URL	Required
GET	/workspaces/me/members	List all team members and their roles	Required

GET /workspaces/me — Example Response

```
{
  "success": true,
  "data": {
    "id": "ws_01HX8K9M2P",
    "name": "BrightPost Agency",
    "slug": "brightpost-agency",
    "logo_url": "https://cdn.socialsphear.com/logos/brightpost.png",
    "plan": "agency",
    "social_accounts_count": 24,
    "members_count": 8,
    "created_at": "2026-01-15T10:30:00Z"
  }
}
```

3. Social Accounts

Social accounts are the connected social media profiles within a workspace. Connections are managed via OAuth in the dashboard. The API allows listing and status checking.

Method	Endpoint	Description	Auth
GET	/social-accounts	List all connected social accounts	Required
GET	/social-accounts/:id	Get a specific social account by ID	Required
GET	/social-accounts/:id/health	Check OAuth token health and expiry	Required
DELETE	/social-accounts/:id	Disconnect a social account	Required

GET /social-accounts — Example Response

```
{
  "success": true,
  "data": [
    {
      "id": "sa_01HX9K3N5Q",
      "platform": "instagram",
      "username": "brightpost_agency",
      "status": "active",
      "token_expires_at": "2026-09-01T00:00:00Z",
      "followers_count": 12400,
      "created_at": "2026-01-20T08:00:00Z"
    },
    {
      "id": "sa_01HX9K3N6R",
      "platform": "linkedin",
      "username": "BrightPost Agency",
      "status": "expiring",
      "token_expires_at": "2026-06-10T00:00:00Z"
    }
  ]
}
```

4. Posts

Posts are the core unit of content in SocialSphear. A single post can be published to multiple platforms simultaneously. Each platform delivery is tracked as a separate PostJob.

Method	Endpoint	Description	Auth
GET	/posts	List all posts (paginated) with optional filters	Required
POST	/posts	Create a new post (draft or scheduled)	Required
GET	/posts/:id	Get a specific post with all PostJobs	Required
PATCH	/posts/:id	Update post content, scheduled time, or platforms	Required
DELETE	/posts/:id	Delete a post (only if not yet published)	Required
POST	/posts/:id/schedule	Schedule a draft post at a specific datetime	Required
POST	/posts/:id/publish-now	Publish a post immediately to all selected platforms	Required
POST	/posts/:id/cancel	Cancel a scheduled post and move to draft	Required
POST	/posts/:id/duplicate	Create a copy of the post as a new draft	Required
GET	/posts/calendar	Get posts in a date range (for calendar views)	Required

POST /posts — Create a Scheduled Post

```
// Request body
{
  "content": "Exciting news – we just launched our new product!\n\n#launch #startup #SaaS",
  "platforms": ["instagram", "linkedin", "twitter"],
  "social_account_ids": ["sa_01HX9K3N5Q", "sa_02JK4L7P8R", "sa_03ML5N9Q1S"],
  "scheduled_at": "2026-07-01T09:00:00Z",
  "media_urls": ["https://cdn.socialsphear.com/media/ws_abc/launch-image.jpg"],
  "platform_overrides": {
    "twitter": { "content": "Big news! We just launched. Check the link in bio. #launch" }
  }
}

// Response
{
  "success": true,
  "data": {
    "id": "post_01JK7P9R2S",
    "status": "scheduled",
    "scheduled_at": "2026-07-01T09:00:00Z",
    "post_jobs": [
      { "id": "pj_01", "platform": "instagram", "status": "pending" },
      { "id": "pj_02", "platform": "linkedin", "status": "pending" },
      { "id": "pj_03", "platform": "twitter", "status": "pending" }
    ]
  }
}
```

```
    "created_at": "2026-06-28T14:22:00Z"
  }
}
```

GET /posts — Query Parameters

Parameter	Type	Default	Description
status	string	all	Filter by status: draft, scheduled, published, failed
platform	string	all	Filter by platform: instagram, linkedin, twitter, etc.
from	ISO 8601 datetime	30 days ago	Start of date range (scheduled_at)
to	ISO 8601 datetime	now	End of date range (scheduled_at)
limit	integer (1-100)	20	Number of results per page
cursor	string	null	Cursor for next page (from previous response's next_cursor)

5. Media

Upload images and videos to SocialSphear's media library before attaching them to posts. Upload flow: request a presigned URL, upload directly to Cloudflare R2, then confirm the upload.

Method	Endpoint	Description	Auth
POST	/media/upload-url	Request a presigned upload URL for a media file	Required
POST	/media/confirm	Confirm upload complete and trigger platform resizing	Required
GET	/media	List all media files in the workspace library	Required
DELETE	/media/:id	Delete a media file from the library	Required

Media Upload Flow

```
// Step 1 – Request presigned URL
POST /media/upload-url
{ "filename": "product-launch.jpg", "content_type": "image/jpeg", "size_bytes": 2048000
}

// Response
{
  "data": {
    "upload_id": "upl_01KL8Q3T5V",
    "upload_url": "https://upload.socialsphear.com/presigned/abc123",
    "expires_at": "2026-06-28T15:00:00Z"
  }
}

// Step 2 – PUT file directly to upload_url (client to R2, bypasses API)
PUT https://upload.socialsphear.com/presigned/abc123
Content-Type: image/jpeg
[binary image data]

// Step 3 – Confirm upload complete
POST /media/confirm
{ "upload_id": "upl_01KL8Q3T5V" }

// Response – media is now in library, resized variants being generated
{
  "data": {
    "id": "med_01KL9R4U6W",
    "url": "https://cdn.socialsphear.com/media/ws_abc/product-launch.jpg",
    "variants": {
      "instagram_square": "...1080x1080.jpg",
      "twitter_landscape": "...1200x675.jpg",
      "linkedin_landscape": "...1200x627.jpg",
      "tiktok_vertical": "...1080x1920.jpg"
    }
  }
}
```


6. Analytics

Query engagement metrics for your posts and social accounts. Analytics data is available from 1 hour after a post publishes and is retained for 36 months.

Method	Endpoint	Description	Auth
GET	/analytics/posts/:post_id	Get all metrics snapshots for a specific post	Required
GET	/analytics/accounts/:account_id	Get account-level metrics over time	Required
GET	/analytics/summary	Get workspace-level summary metrics for a date range	Required
GET	/analytics/top-posts	Get top-performing posts ranked by engagement rate	Required
GET	/analytics/export	Export all analytics data as CSV for a date range	Required

GET /analytics/summary — Response

```
// Example: GET /analytics/summary?from=2026-06-01&to=2026-06-30&platforms=instagram,linkedin
{
  "data": {
    "period": { "from": "2026-06-01", "to": "2026-06-30" },
    "totals": {
      "posts_published": 48,
      "total_reach": 284500,
      "total_impressions": 612000,
      "total_likes": 9840,
      "total_comments": 1230,
      "total_shares": 445,
      "avg_engagement_rate": 3.86
    },
    "by_platform": [
      { "platform": "instagram", "posts": 24, "reach": 184000, "avg_engagement_rate": 4.2 },
      { "platform": "linkedin", "posts": 24, "reach": 100500, "avg_engagement_rate": 3.1 }
    ]
  }
}
```

7. AI Endpoints

The AI endpoints expose SocialSphear's caption generation and hashtag suggestion capabilities. Usage deducts from your workspace's monthly AI credit allowance.

Method	Endpoint	Description	Auth
POST	/ai/caption	Generate a caption for one or more platforms	Required
POST	/ai/hashtags	Generate hashtag suggestions for a topic	Required
GET	/ai/best-time	Get the AI-suggested best time to post for a platform	Required
GET	/ai/credits	Get current AI credit usage and plan allowance	Required

POST /ai/caption — Request and Response

```
// Request
{
  "topic": "Launching our new AI-powered analytics feature",
  "platforms": ["instagram", "linkedin"],
  "tone": "professional",
  "language": "en",
  "include_hashtags": true,
  "brand_voice": true
}

// Response
{
  "data": {
    "captions": {
      "instagram": {
        "content": "Big news! Our AI analytics just got smarter.\n\n#analytics #aitools #contentcreator",
        "character_count": 72,
        "platform_limit": 2200,
        "hashtags_included": 3
      },
      "linkedin": {
        "content": "We are proud to announce a significant upgrade to SocialSphear's analytics engine. Our AI now surfaces actionable insights from your engagement data.",
        "character_count": 155,
        "platform_limit": 3000,
        "hashtags_included": 0
      }
    },
    "credits_used": 3,
    "credits_remaining": 847
  }
}
```

8. Webhooks

Configure webhooks to receive real-time notifications when events occur in your SocialSphear workspace. SocialSphear will POST to your endpoint with the event payload within 5 seconds of the event.

8.1 Configure Webhooks

Method	Endpoint	Description	Auth
GET	/webhooks	List all configured webhook endpoints	Required
POST	/webhooks	Create a new webhook endpoint	Required
DELETE	/webhooks/:id	Delete a webhook endpoint	Required
POST	/webhooks/:id/test	Send a test event to the webhook endpoint	Required

8.2 Available Events

Event	Trigger	Payload Contains
post.scheduled	A post is successfully scheduled	post_id, scheduled_at, platforms, workspace_id
post.published	A post publishes successfully on a platform	post_id, post_job_id, platform, platform_post_url, published_at
post.failed	A post fails to publish after all retries	post_id, post_job_id, platform, error_message, retry_count
post.cancelled	A scheduled post is cancelled	post_id, cancelled_by_user_id, cancelled_at
account.token_expiring	An OAuth token expires in less than 7 days	social_account_id, platform, token_expires_at
account.disconnected	A social account is disconnected	social_account_id, platform, disconnected_at
approval.requested	An editor submits a post for approval	post_id, submitted_by_user_id, workspace_id
approval.approved	An admin approves a post	post_id, approved_by_user_id, approved_at
approval.rejected	An admin rejects a post	post_id, rejected_by_user_id, reason

8.3 Webhook Signature Verification

All webhook deliveries include an X-SocialSphear-Signature header. Verify this signature in your endpoint to confirm the request came from SocialSphear.

```
// Verify webhook signature (Node.js example)
import crypto from 'crypto';

function verifyWebhookSignature(payload, signature, secret) {
  const expected = crypto
    .createHmac('sha256', secret)
    .update(payload, 'utf8')
    .digest('hex');
  return crypto.timingSafeEqual(
    Buffer.from(signature),
    Buffer.from('sha256=' + expected)
  );
}

app.post('/webhook', (req, res) => {
  const signature = req.headers['x-socialsphear-signature'];
  const isValid = verifyWebhookSignature(
    JSON.stringify(req.body), signature, process.env.WEBHOOK_SECRET
  );
  if (!isValid) return res.status(401).send('Invalid signature');

  const { event, data } = req.body;
  // Handle event...
  res.status(200).send('OK');
});
```

9. Rate Limits and Quotas

Plan	Requests/min	Posts/day (API)	AI Credits/mo	Webhook endpoints
Creator	100	50	200	2
Pro	500	500	1,000	10
Agency	2,000	5,000	5,000	50
Enterprise	Custom	Unlimited	Unlimited	Unlimited

When rate limited, the API returns HTTP 429 with a Retry-After header indicating how many seconds to wait before retrying. Implement exponential backoff in your client for resilient integrations.

10. SDK and Quick Start

10.1 Official TypeScript and JavaScript SDK

```
# Install the SDK
npm install @socialsphear/sdk

# Basic usage
import { SocialSphear } from '@socialsphear/sdk';

const client = new SocialSphear({ apiKey: process.env.SOCIALSPHEAR_API_KEY });

// Schedule a post
const post = await client.posts.create({
  content: "Hello from the SocialSphear API!",
  platforms: ['instagram', 'linkedin'],
  socialAccountIds: ['sa_01HX9K3N5Q', 'sa_02JK4L7P8R'],
  scheduledAt: new Date('2026-07-01T09:00:00Z'),
});
console.log('Post scheduled: ' + post.id);

// Get analytics
const summary = await client.analytics.summary({
  from: '2026-06-01',
  to: '2026-06-30',
  platforms: ['instagram'],
});
console.log('Total reach: ' + summary.totals.total_reach);
```

10.2 API Changelog

Version	Date	Changes
v1.0	Month 5 (Launch)	Initial public API release — posts, media, analytics, AI, webhooks
v1.1	Month 7	Add /ai/content-plan endpoint, bulk post scheduling via array
v1.2	Month 9	Social listening query endpoints, competitor data endpoints
v2.0	Month 12	Breaking: pagination moves to cursor-only, OAuth 2.0 for API keys