


Disjoint Set

郭至軒 (KuoE0)

KuoE0.tw@gmail.com

KuoE0.ch






Attribution-ShareAlike 3.0 Unported (CC BY-SA 3.0)

<http://creativecommons.org/licenses/by-sa/3.0/>

Latest update: Mar 13, 2013


Disjoint Set

中國譯：並查集




Disjoint Set

中國譯：並查集




Disjoint Set

中國譯：並查集




Disjoint Set




中國譯：並查集



Tree Structure



Tree Structure




Data Structure

index	0	1	2	3	4
content	parent node	parent node	parent node	parent node	parent node


The parent of root is itself!

Find Operation




node	parent
1	1
2	1
5	2
6	2



How to determine that node 2 and node 6 in the same set?





How to determine that node 2 and node 6 in the same set?



How to determine that node 2 and node 6 in the same set?



How to determine that node 2 and node 6 in the same set?




Source Code


```
// parent is an array stored the parent  
of nodes.
```

```
int findSet( int x ) {  
    if ( parent[ x ] == x )  
        return x;  
    return findSet( parent[ x ] );  
}
```


If the height of tree is very large...




Reduce Height



Reduce Height



Reduce Height



node

parent

1

1

2

1

5

1

6


1

Source Code


```
// parent is an array stored the parent of  
nodes.
```

```
int findSet( int x ) {  
    if ( parent[ x ] == x )  
        return x;  
    return parent[ x ] = findSet( parent[ x ] );  
}
```

Union Operation




Height = 3




Height = 2

Union Operation




Height = 3



Height = 2

Union Operation



Height = 3

Source Code

```
// parent is an array stored the parent of
nodes.
// height is an array stored the height of tree

void unionSet( int a, int b ) {
    if ( a == b )
        return;
    if ( height[ a ] > height[ b ] )
        parent[ b ] = a;
    else {
        parent[ a ] = b;
        if ( height[ a ] == height[ b ] )
            ++height[ b ];
    }
}
```


Time Complexity

Find Operation

$O(1)$

Union Operation

$O(1)$

Practice Now

[UVa] 10583 - Ubiquitous Religions

I 0583 - Ubiquitous Religions

佛教

佛教

基督教

佛教

基督教


佛教

基督教


佛教

回教


I 0583 - Ubiquitous Religions




I 0583 - Ubiquitous Religions




I 0583 - Ubiquitous Religions




I 0583 - Ubiquitous Religions




I 0583 - Ubiquitous Religions



I 0583 - Ubiquitous Religions



I 0583 - Ubiquitous Religions



Source Code

```
#include <iostream>
#include <cstdio>
using namespace std;
#define MAXN 50010
int parent[ MAXN ], height[ MAXN ];

int main() {
    int n, t = 0, e, a, b;
    while ( scanf( "%d %d", &n, &e ) && n && e ) {
        for ( int i = 1; i <= n; ++i )
            parent[ i ] = i;
        height[ i ] = 1;
        for ( int i = 0; i < e; ++i ) {
            scanf( "%d %d", &a, &b );
            unionSet( findSet( a ), findSet( b ) );
        }
        int ret = 0;
        for ( int i = 1; i <= n; ++i )
            if ( parent[ i ] == i )
                ++ret;
        printf( "Case %d: %d\n", ++t, ret );
    }
    return 0;
}
```

Practice Now

[UVa] 10608 - Friends

Thank You for Your Listening.

