



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Experiment No. 7
Apply Dimensionality Reduction on Adult Census Income Dataset and analyze the performance of the model
Date of Performance: 11-09-2023
Date of Submission: 09-10-2023



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Aim: Apply Dimensionality Reduction on Adult Census Income Dataset and analyze the performance of the model.

Objective: Able to perform various feature engineering tasks, perform dimensionality reduction on the given dataset and maximize the accuracy, Precision, Recall, F1 score.

Theory:

In machine learning classification problems, there are often too many factors on the basis of which the final classification is done. These factors are basically variables called features. The higher the number of features, the harder it gets to visualize the training set and then work on it. Sometimes, most of these features are correlated, and hence redundant. This is where dimensionality reduction algorithms come into play. Dimensionality reduction is the process of reducing the number of random variables under consideration, by obtaining a set of principal variables. It can be divided into feature selection and feature extraction.

Dataset:

Predict whether income exceeds \$50K/yr based on census data. Also known as "Adult" dataset.

Attribute Information:

Listing of attributes:

>50K, <=50K.

age: continuous.

workclass: Private, Self-emp-not-inc, Self-emp-inc, Federal-gov, Local-gov, State-gov, Without-pay, Never-worked.

fnlwgt: continuous.



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

education: Bachelors, Some-college, 11th, HS-grad, Prof-school, Assoc-acdm, Assoc-voc, 9th, 7th-8th, 12th, Masters, 1st-4th, 10th, Doctorate, 5th-6th, Preschool.

education-num: continuous.

marital-status: Married-civ-spouse, Divorced, Never-married, Separated, Widowed, Married-spouse-absent, Married-AF-spouse.

occupation: Tech-support, Craft-repair, Other-service, Sales, Exec-managerial, Prof-specialty, Handlers-cleaners, Machine-op-inspect, Adm-clerical, Farming-fishing, Transport-moving, Priv-house-serv, Protective-serv, Armed-Forces.

relationship: Wife, Own-child, Husband, Not-in-family, Other-relative, Unmarried.

race: White, Asian-Pac-Islander, Amer-Indian-Eskimo, Other, Black.

sex: Female, Male.

capital-gain: continuous.

capital-loss: continuous.


hours-per-week: continuous.

native-country: United-States, Cambodia, England, Puerto-Rico, Canada, Germany, Outlying-US(Guam-USVI-etc), India, Japan, Greece, South, China, Cuba, Iran, Honduras, Philippines, Italy, Poland, Jamaica, Vietnam, Mexico, Portugal, Ireland, France, Dominican-Republic, Laos, Ecuador, Taiwan, Haiti, Columbia, Hungary, Guatemala, Nicaragua, Scotland, Thailand, Yugoslavia, El-Salvador, Trinidad & Tobago, Peru, Hong, Holand-Netherlands.

```
import numpy as np # linear algebra
import pandas as pd # data processing, CSV file I/O (e.g. pd.read_csv)
import os
for dirname, _, filenames in os.walk('/kaggle/input'):
    for filename in filenames:
        print(os.path.join(dirname, filename))
```

```
df=pd.read_csv("/content/adult_dataset.csv")
```

```
df.head()
```



	age	workclass	fnlwgt	education	education.num	marital.status	occupation	relationship	race	sex
0	90	?	77053	HS-grad	9	Widowed	?	Not-in-family	White	Female
1	82	Private	132870	HS-grad	9	Widowed	Exec-managerial	Not-in-family	White	Female
2	66	?	186061	Some-college	10	Widowed	?	Unmarried	Black	Female
3	54	Private	140359	7th-8th	4	Divorced	Machine-op-inspct	Unmarried	White	Female

```
df.describe().T
```

	count	mean	std	min	25%	50%	75%
age	32561.0	38.581647	13.640433	17.0	28.0	37.0	48.0
fnlwgt	32561.0	189778.366512	105549.977697	12285.0	117827.0	178356.0	237051.0
education.num	32561.0	10.080679	2.572720	1.0	9.0	10.0	12.0
capital.gain	32561.0	1077.648844	7385.292085	0.0	0.0	0.0	0.0
capital.loss	32561.0	87.303830	402.960219	0.0	0.0	0.0	0.0
hours.per.week	32561.0	40.437456	12.347429	1.0	40.0	40.0	45.0

```
df.shape
```

(32561, 15)

```
df.columns
```

```
Index(['age', 'workclass', 'fnlwgt', 'education', 'education.num',
       'marital.status', 'occupation', 'relationship', 'race', 'sex',
       'capital.gain', 'capital.loss', 'hours.per.week', 'native.country',
       'income'],
      dtype='object')
```

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 32561 entries, 0 to 32560
Data columns (total 15 columns):
#   Column                Non-Null Count  Dtype
---  -
0   age                   32561 non-null  int64
1   workclass             32561 non-null  object
2   fnlwgt                32561 non-null  int64
3   education             32561 non-null  object
4   education.num         32561 non-null  int64
5   marital.status        32561 non-null  object
6   occupation            32561 non-null  object
7   relationship          32561 non-null  object
8   race                  32561 non-null  object
9   sex                   32561 non-null  object
10  capital.gain          32561 non-null  int64
11  capital.loss          32561 non-null  int64
12  hours.per.week        32561 non-null  int64
13  native.country        32561 non-null  object
14  income                32561 non-null  object
dtypes: int64(6), object(9)
memory usage: 3.7+ MB
```

```
df[df == '?'] = np.nan
```

```
df.isnull().sum()
```

```
age          0
workclass    1836
fnlwgt       0
education    0
education.num 0
marital.status 0
occupation   1843
relationship 0
race         0
sex          0
capital.gain 0
capital.loss 0
hours.per.week 0
native.country 583
income       0
dtype: int64
```

```
for col in ['workclass', 'occupation', 'native.country']:
    df[col].fillna(df[col].mode()[0], inplace=True)
```

```
df.isnull().sum()
```

```
age          0
workclass    0
fnlwgt       0
education    0
education.num 0
marital.status 0
occupation   0
relationship 0
race         0
sex          0
capital.gain 0
capital.loss 0
hours.per.week 0
native.country 0
income       0
dtype: int64
```

```
# converting categorical Columns
```

```
df.replace({'Sex':{'male':0,'female':1}, 'Embarked':{'S':0,'C':1,'Q':2}}, inplace=True)
```

```
X = df.drop(['income'], axis=1)
```

```
y = df['income']
```

```
from sklearn.model_selection import train_test_split
```

```
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.3, random_state = 0)
```

```
from sklearn import preprocessing
```

```
categorical = ['workclass', 'education', 'marital.status', 'occupation', 'relationship', 'race', 'sex', 'native.country']
```

```
for feature in categorical:
```

```
    label = preprocessing.LabelEncoder()
    X_train[feature] = label.fit_transform(X_train[feature])
    X_test[feature] = label.transform(X_test[feature])
```

```
from sklearn.preprocessing import StandardScaler
```

```
scaler = StandardScaler()
```

```
X_train = pd.DataFrame(scaler.fit_transform(X_train), columns = X.columns)
```

```
X_test = pd.DataFrame(scaler.transform(X_test), columns = X.columns)
```

```
X_train.head()
```

	age	workclass	fnlwgt	education	education.num	marital.status	occupation	relationship	
0	0.101484	2.600478	-1.494279	-0.332263	1.133894	-0.402341	-0.782234	2.214196	0
1	0.028248	-1.884720	0.438778	0.184396	-0.423425	-0.402341	-0.026696	-0.899410	0
2	0.247956	-0.090641	0.045292	1.217715	-0.034095	0.926666	-0.782234	-0.276689	0
3	-0.850587	-1.884720	0.793152	0.184396	-0.423425	0.926666	-0.530388	0.968753	0

```
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import accuracy_score
```

```
LR = LogisticRegression()
LR.fit(X_train, y_train)
```

```
LogisticRegression()
```

```
y_pred = LR.predict(X_test)
```

```
accuracy_score(y_test, y_pred)
```

```
0.8216808271061521
```

```
from sklearn.decomposition import PCA
pca = PCA()
```

```
X_train = pca.fit_transform(X_train)
pca.explained_variance_ratio_
```

```
array([0.14757168, 0.10182915, 0.08147199, 0.07880174, 0.07463545,
       0.07274281, 0.07009602, 0.06750902, 0.0647268 , 0.06131155,
       0.06084207, 0.04839584, 0.04265038, 0.02741548])
```

```
X = df.drop(['income'], axis=1)
y = df['income']
```

```
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.3, random_state = 0)
```

```
categorical = ['workclass', 'education', 'marital.status', 'occupation', 'relationship', 'race', 'sex', 'native.country']
for feature in categorical:
    label = preprocessing.LabelEncoder()
    X_train[feature] = label.fit_transform(X_train[feature])
    X_test[feature] = label.transform(X_test[feature])
```

```
X_train = pd.DataFrame(scaler.fit_transform(X_train), columns = X.columns)
```

```
pca= PCA()
pca.fit(X_train)
cumsum = np.cumsum(pca.explained_variance_ratio_)
dim = np.argmax(cumsum >= 0.90) + 1
print('The number of dimensions required to preserve 90% of variance is',dim)
```

```
The number of dimensions required to preserve 90% of variance is 12
```

```
X = df.drop(['income', 'native.country', 'hours.per.week'], axis=1)
y = df['income']
```

```
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.3, random_state = 0)
```

```
categorical = ['workclass', 'education', 'marital.status', 'occupation', 'relationship', 'race', 'sex']
for feature in categorical:
    label = preprocessing.LabelEncoder()
    X_train[feature] = label.fit_transform(X_train[feature])
    X_test[feature] = label.transform(X_test[feature])
```

```
X_train = pd.DataFrame(scaler.fit_transform(X_train), columns = X.columns)
```

```
X_test = pd.DataFrame(scaler.transform(X_test), columns = X.columns)
```

```
LR2 = LogisticRegression()
LR2.fit(X_train, y_train)
```

```
▼ LogisticRegression
LogisticRegression()
```

```
y_pred = LR2.predict(X_test)
```

```
accuracy_score(y_test, y_pred)
```

```
0.8227044733340158
```

```
from sklearn.metrics import confusion_matrix
import pandas as pd
```

```
confusion = confusion_matrix(y_test, y_pred)
```

```
df_confusion = pd.DataFrame(confusion, columns=['Predicted No', 'Predicted Yes'], index=['Actual No', 'Actual Yes'])
```

```
from sklearn.metrics import classification_report
print(classification_report(y_test, y_pred))
```

	precision	recall	f1-score	support
<=50K	0.84	0.95	0.89	7410
>50K	0.72	0.43	0.54	2359
accuracy			0.82	9769
macro avg	0.78	0.69	0.72	9769
weighted avg	0.81	0.82	0.81	9769



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Conclusion:

1. The accuracy of the logistic regression model after dimensionality reduction is approximately 0.8227.
2. The precision for the $>50K$ class is 0.72, recall is 0.43, and F1-score is 0.54.
3. The precision for the $\leq 50K$ class is 0.84, recall is 0.95, and F1-score is 0.89.
4. Dimensionality reduction has a positive impact by reducing the complexity of the model (fewer features to consider), making it computationally efficient, while still maintaining a reasonable level of predictive performance.