

Logarithm Cycle Antenna 698~2700MHz 8/9dBi PFZZ-1005

Electrical Spec Frequency range					
-1		MHz	698-806	806-960	1710-2700
VSWR			≤1.8 ≤1.5		
Input impendend	ce	Ω		50	
Gain		dBi	7.5	8	9
Polarization type	9			Vertical	
Horizontal Beam	nwidth	deg	85	85	60
Vertical Beamwi	dth	deg	60	60	50
Max power		W	50		
Lightning protec	tion			DC ground	
Mechanical S _l	pecifications				
Dimension		mm	282*210*50		
Weight		Kg	Kg 0.60		
Connector type			N-female RG-58 白色线长 220mm		
Diameter Of Installation		mm	Φ40-Φ50 双 U 码、双虎牙		
Radiating element materal			Al		
Radome material			ABS 防紫外线		
Antenna's color			White		
Operationnal Temperature		$^{\circ}$ C	-40 to +65		
Operationnal Humidity		%	5~95		
		MK Cabi	U Type Ch Flat Pad Spring Was Nut	MODEL NO. HOD Outdoor Wide Band (Directional Antenna
Outside Draw	ing		Flat Pad Spring Was	MODEL NO.HOD Outdoor Wide Band (Directional Antenna
Outside Draw Radiation Pat	_		Flat Pad Spring Was Nut	Outdoor Wide Band I	Directional Antenna
	_		Flat Pad Spring Was Nut	Outdoor Wide Band I	Directional Antenna
	tern		Flat Pad Spring Was Nut	Outdoor Wide Band I Item NO.E32	Directional Antenna