



# 2014

Hubbell Canada LP  
ExpressLine



**HUBBELL**  
Outdoor Lighting



**HUBBELL**  
Lighting

## ExpressLine LED

by Hubbell Canada LP

The name Hubbell has long been associated with quality products sold through the electrical distribution channel. Our Hubbell Lighting products are readily accepted by contractors and universally recognized as leading in quality and value by specifiers. Hubbell Lighting continues this tradition of quality, strengthening our support of this partnership today.

## New LED Solutions

The **ExpressLine** program expands our stock product range, and simplifies our business practices. With an expanding offering of LED wallpacks, floodlights and recessed downlight products, customers can maximize their energy savings and reduce maintenance costs. Look for the **NEW** logo highlighting Hubbell's latest LED products.



## Comprehensive Program

The **ExpressLine** program provides quick-turn solutions to the lighting challenges brought to you each day. The merchandising cartons are designed to help you quickly select the right fixture for each task. Display rack from Hubbell showcase Expressline lighting products for quick cash and carry sales.



## ExpressLine, ready to help you maximize sales

The ExpressLine program brings the very best of Hubbell Lighting and is much more than a collection of high quality, premium branded products. Hubbell Lighting's ExpressLine program offers high impact point-of-purchase merchandising displays, literature, header and application guide to maximize your sales!

## Selling & Merchandising Tools

To drive incremental sales, ExpressLine members have use of our displays, gondola headers, and promotional materials.



Easy to read packaging that includes valuable product features, dimensions and application information



**MERCHANDISING WIRE GONDOLA DISPLAY (EXPRESSLINE OR EXPRESSCAPE)**

6' tall x 3' wide x 16" deep  
(see merchandise order form)

## New Features, LED Products Equivalency

Each LED product in the ExpressLine catalog includes complete information in easy to read modules. Information specific to energy-efficiency, LED performance, traditional luminaire source equivalency, CCT and lumens per watt are available for each product.

**Full Cut-off LED Wallpack**

**NEW LNC2-12LU-5K** 29w LED, 120-277V, bronze 4 lbs

The compact Laredo LED LNC2 wallpack is larger more powerful version of the LNC wallpacks. Up to 4:1 spacing to mounting height ratio means fewer fixtures to install, single led driver. Rugged die-cast aluminum housing, optional acrylic diffuser included for reduced brightness applications. Ideal for schools, factories, hospitals, warehouses and retail applications. Listed to UL1598 for use in wet locations, IDA compliant, DLC and LightingFacts.

Series Number	Equivalency			Delivered Lumens	System Watts	Lumens Per Watt	Mounting Height	CCT	Voltage	Drive Current
	MH	HPS	CFL							
LNC2-12LU-5K	150w	150w	2x42w	2,419	29	83	Up to 15 ft.	5100K	120-277V	1@700mA

**Percentage of energy savings over traditional light sources**

**LED closest replacement for traditional light sources**

**Maximum lumen values produced by luminaire**

**Total watts consumed by luminaire**

**Luminous efficacy of luminaire**

**Suggested optimum application data**

**Correlated Color Temperature**

**Voltage**

**Number of drivers @ LED drive current**

**Luminaire information: application/uses, construction and dimensions**

**Industry listings, energy efficiency qualifications and environmental qualifications**

**SPC US**

**IDA**

**DLC**

**LED lighting facts**

**LED Product Partner**

## Certification

Hubbell Lighting products are designed and tested to meet the latest industry standards. Look for the industry standard logos for the products where applicable.



## LED Facade Flood

Catalog # Description

Wt.



ALF-6LU-5K-BZ

1' LED flood

4.0

Excellent for small floodlighting applications such as signs, façade, landscape accent, or small area illumination. The compact size allows the flood to be easily hidden or blend into the landscape environment.



IP64/IP65



Series Number	Equivalency			Delivered Lumens	System Watts	Lumens Per Watt	Max Candle Power	Beam Pattern	CCT	Voltage	Drive Current
	MH	HPS	CFL								
ALF-6LU	70w	70w	42w	848	10	85	621	6x5	5100K	120-277V	1@470mA



## LED Facade Flood

Catalog # Description

Wt.



ALF-12LU-5K-BZ

2' LED flood

8.0

Cast aluminum housing, 1/2" brass knuckle mount swivel, adjustable pivot from 0-75 degrees. Ideal for signs, facade, landscape accent or medium area illumination, easily hidden or blend into landscape environment.



IP64/IP65



Series Number	Equivalency			Delivered Lumens	System Watts	Lumens Per Watt	Max Candle Power	Beam Pattern	CCT	Voltage	Drive Current
	MH	HPS	CFL								
ALF-12LU	70w	100w	42w	1655	20	75	1208	6x5	5100K	120-277V	2@470mA



## LED Compact Flood

Catalog # Description

Wt.

NEW  
NEW

FSL-7

Compact architectural flood 120-277V

6.8

FSL-7-PC1

Compact architectural flood, PC, 120V

6.8

Compact, wide beam 7 LED floodlight, excellent for small floodlighting applications such as signs, façade, landscape accent, or small area illumination. The compact size allows the flood to be easily hidden or blend into the landscape environment. IP66, wet location listed.



Series Number	Equivalency			Delivered Lumens	System Watts	Lumens Per Watt	Max Candle Power	Beam Pattern	CCT	Voltage	Drive Current
	MH	HPS	CFL								
FSL-7/FSL-7-PC1	100w	100w	42w	2040	26.5	77	1450	Wide	5100K	120-277V*	1@1050mA



\*PC version 120V only

## LED Flood

Catalog # Description

Wt.

NEW  
NEW

FML-14

Architectural flood 120-277V

8.5

FML-14-PC1

Architectural flood, PC, 120V

8.5

Wide beam 14 LED floodlight. Rugged design with vented housing isolates LED module from driver maximizing product life and performance. 1/2" brass knuckle mount swivel, with adjustable pivot. Ideal for signs, facade, landscape accent or medium area illumination, easily hidden or blend into landscape environment. IP65, wet location listed.



Series Number	Equivalency			Delivered Lumens	System Watts	Lumens Per Watt	Max Candle Power	Beam Pattern	CCT	Voltage	Drive Current
	MH	HPS	CFL								
FML-14/FML-14-PC1	150w	150w	2x42w	4285	53	81	2805	Wide	5100K	120-277V*	1@1050mA



\*PC version 120V only

**NRG300 Wallpack Catalog #**
**Description**
**Wt.**

**NRG312LU**


<b>NRG-312LU-5K-BZ</b>	18w LED, 120-277V, bronze
<b>NRG-312LU-5K-BZ-PC</b>	18w LED, 120V, PC, bronze

5 lbs  
5 lbs

Polycarbonate front provides wide lateral spread and vandal resistance. Lateral coverage is five times the typical 6-10' mounting height. Now available in long life, energy-saving LED! Photocontrol units provide dusk-to-dawn energy management. Cast aluminum back housing provides solid mounting to wall or recessed wiring boxes. 1/2" bottom conduit knockout allows surface conduit wiring. For use in wet locations.



Series Number	Equivalency			Delivered Lumens	System Watts	Lumens Per Watt	Mounting Height	CCT	Voltage	Drive Current
	MH	HPS	CFL							
<b>NRG-312LU-5K-BZ</b>	<b>50w</b>	<b>70w</b>	<b>42w</b>	<b>1200</b>	<b>18</b>	<b>66</b>	<b>Up to 10 ft.</b>	5000K	120-277V	350mA


**LED Perimaliter Wallpacks**
**Catalog #**
**Description**
**Wt.**

**PGM3**

**PVL3**
**NEW**
**NEW**

<b>PGM3-30LU-5K-BZ</b>	69w LED, glass refractor, 120-277V, bronze	14 lbs
<b>PVL3-30LU-5K-BZ</b>	69w LED, acrylic refractor, 120-277V, bronze	12 lbs

\*347 available upon request

Rugged, durable LED wallpack ideal for perimeter/area lighting featuring wide lateral spacing, vandal resistant glass or polycarbonate lens, Dark Bronze finish. Ideal for factories, warehouses, distribution centers, parking structures and large retail applications. Listed to UL1598 for use in wet locations.



Series Number	Equivalency			Delivered Lumens	System Watts	Lumens Per Watt	Mounting Height	CCT	Voltage	Drive Current
	MH	HPS	CFL							
<b>PGM3-30LU</b>	<b>150w</b>	<b>250w</b>	<b>-</b>	<b>5,678</b>	<b>69</b>	<b>82</b>	<b>15-18 ft.</b>	5000K	120-277V	2@700mA
<b>PVL3-30LU</b>	<b>150w</b>	<b>250w</b>	<b>-</b>	<b>4,873</b>	<b>69</b>	<b>71</b>	<b>15-18 ft.</b>	5000K	120-277V	2@700mA


**LED Linear Wall**
**Catalog #**
**Description**
**Wt.**


<b>ALFW-6LU-5K-BZ</b>	1' linear wall mount	4.0
<b>ALFW-6LU-5K-BZ-PC</b>	1' linear wall mount, photocontrol	4.0




Excellent for small applications such as over door ways or small area illumination. The wall mount ALFW-6LU is a versatile solution for doorways entrances featuring an adjustable pivot from 0-75°. The compact size allows it to be easily hidden or blend into the environment. **IP64/IP65**

Series Number	Equivalency			Delivered Lumens	System Watts	Lumens Per Watt	Mounting Height	CCT	Voltage	Drive Current
	MH	HPS	CFL							
<b>ALFW-6LU</b>	<b>70w</b>	<b>70w</b>	<b>42w</b>	<b>848</b>	<b>10</b>	<b>85</b>	<b>Up to 10 ft.</b>	5100K	120-277V	470mA



## LNC LED Wallpack Family




### Zero Uplight



Catalog #	Description	Wt.
LNC-5LU-5K	13w LED, 120-277V, bronze	4 lbs
LNC-5LU-5K-PC	13w LED, 120V, PC, bronze	4 lbs
LNC-7LU-5K-3-1	16w LED, 120-277V, bronze	4 lbs
LNC-9LU-5K-3-1	20w LED, 120-277V, bronze	4 lbs

The compact LNC LED series is designed for perimeter illumination, available in three lumen packages for safety, security and identity. Typical mounting height is up to 12 feet with four times fixture spacing (without acrylic diffuser) and three times spacing with acrylic diffuser installed. Mounts over recessed junction boxes or wires to surface conduit through bottom 1/2" knockout for quick, versatile installation.



Series Number	Equivalency			Delivered Lumens	System Watts	Lumens Per Watt	Mounting Height	CCT	Voltage	Drive Current
	MH	HPS	CFL							
 LNC-5LU-5K	-	-	42w	967	12.6	76	up to 10 ft.	5100K	120-277V	700mA
 LNC-7LU-5K-3-1	70w	100w	-	1,389	16.4	85	up to 11 ft.	5100K	120-277V	700mA
 LNC-9LU-5K-3-1	100w	150w	-	1,745	20.6	85	10-12 ft.	5100K	120-277V	700mA

## LNC2 LED Wallpack

### Zero Uplight



Catalog #	Description	Wt.
LNC2-12LU-5K-3-1	29w LED, 120-277V, bronze	4 lbs
LNC2-12LU-5K-3-1-PC	29w LED, 120-277V photocontrol, bronze	4 lbs
LNC2-18LU-5K-3-1	45w LED, 120-277V, bronze	4 lbs
LNC2-18LU-5K-3-1-PC	45w LED, 120-277V photocontrol, bronze	4 lbs
LNC2-12LF-5K-3-1	T.B.A., 347V, bronze	4 lbs
LNC2-12LF-5K-3-1-PC	T.B.A., 347V photocontrol, bronze	4 lbs
LNC2-18LF-5K-3-1	T.B.A., 347V, bronze	4 lbs
LNC2-18LF-5K-3-1-PC	T.B.A., 347V photocontrol, bronze	4 lbs

The compact LED LNC2 wallpack is larger more powerful version of the LNC wallpacks. Up to 5:1 spacing to mounting height ratio means fewer fixtures to install. Rugged die-cast aluminum housing, optional acrylic diffuser included for reduced brightness applications. Ideal for schools, factories, hospitals, warehouses and retail applications. Listed to UL1598 for use in wet locations, IDA compliant, DLC and LightingFacts.



Series Number	Equivalency			Delivered Lumens	System Watts	Lumens Per Watt	Mounting Height	CCT	Voltage	Drive Current
	MH	HPS	CFL							
 LNC2-12L-5K	150w	150w	2x42w	2,419	29	83	Up to 15 ft.	5100K	120-277V	1@700mA
 LNC2-18L-5K	250w	250w	2x42w	3,311	45	74	Up to 15 ft.	5100K	120-277V	2@700mA
 LNC2-12LF-5K	150w	150w	2x42w				Up to 15 ft.	5100K	347V	1@700mA
LNC2-18LF-5K	250w	250w	2x42w				Up to 15 ft.	5100K	347V	2@700mA

**LED Dusk-to-Dawn**
**Catalog # Description**
**Wt.**

**NEW**
**DDL-9L1**

Multipurpose dusk-to-dawn, PC, 120V

6.8

Energy-efficient LED multipurpose dusk-to-dawn luminaire for security applications providing large area illumination. Symmetric lens and asymmetric lenses included as well as removable refractor to eliminate uplight for environmentally friendly installations. Versatile mounting options include: curved 24" aluminum arm, adjustable clamp for 2-3/8" & 1-5/8" OD poles, or direct wall mount.



SHOWN WITH REFRACTOR

Series Number	Equivalency			Delivered Lumens	System Watts	Lumens Per Watt	Mounting Height	CCT	Voltage	Drive Current
	MH	HPS	CFL							
<b>DDL-9L1</b>	175w	150w	85w	3246/3437*	40	up to 86	up to 20 ft.	5100K	120V	1@1280mA



\*Asymmetric/Symmetric lumen values

**Wet location**
**LED Vaportites**
**Catalog # Description**
**Wt.**

**NEW**
**VBGL-1**

Wet location LED ceiling/surface/pendant

3.4

**NEW**
**VWGL-1**

Wet location LED wall mount

3.6

Rugged die-cast aluminum construction, frosted globe with guard, wet location listed, energy-efficient LED vaportites for ceiling or pendant and wall mount. Use for entry, corridors, tunnels, service passages, stairwells. Gray powder paint finish.

VWGL



Series Number	Equivalency		Mount	Delivered Lumens	System Watts	Lumens Per Watt	CCT	Voltage	Drive Current
	INC	CFL							
<b>VBGL-1/VWGL-1</b>	150w	32w	Ceiling/Pendant	757	10	75.7	4000K	120-277V	1@250mA


**LED Recessed Downlight**
**Catalog # Description**
**Wt.**

**LB6LEDA8L30K WH** 6" LED downlight, 13.1w, 825 lumens

1.7 lbs

**NEW**
**LB6LEDA10L30K WH** 6" LED downlight, 14w, 1000 lumens

1.7 lbs

Dimmable 6" LiteBox LED trims, residential and light commercial applications for both new construction and retrofitting opportunities. The product offers excellent glare control and optical cutoff, 80+ CRI color quality and a warm white color temperature. Long life – 60,000 hours at 70% lumen maintenance. Energy Star qualified and meets California Title 24 (commercial).



Catalog Number	Equivalency		Delivered Lumens	System Watts	Lumens Per Watt	Mounting Height	CCT	Voltage	Drive Current
	INC.	CFL							
<b>LB6LEDA8L30K WH</b>	65w	18w	825	13	63	8-10 ft.	3000K	120V	700mA
<b>LB6LEDA10L30K WH</b>	75w	26w	1000	14	71	8-12 ft.	3000K	120V	700mA


**LED Recessed Downlight**

**LB4LEDA30K WH** 4" LED downlight, 8.8w, 556 lumens

1.8 lbs

Dimmable 4" LiteBox LED trims, residential and light commercial applications for both new construction and retrofitting opportunities. The product offers excellent glare control and optical cutoff, 80+ CRI color quality and a warm white color temperature. Long life – 50,000 hours at 70% lumen maintenance. Energy Star qualified and meets California Title 24 (commercial).



Catalog Number	Equivalency		Delivered Lumens	System Watts	Lumens Per Watt	Mounting Height	CCT	Voltage	Drive Current
	INC.	CFL							
<b>LB4LEDA30K WH</b>	50w	13w	556	8.8	63	8-10 ft.	3000K	120V	190mA





## Lightscaper LED

by Hubbell Lighting

Adding elegance, value and security to your home or business. Go Green with Hubbell Lightscaper® 12V LED products. Offering a long life, easy to install, no maintenance LED lighting system, Hubbell Lightscaper® LED fixtures feature popular styles to enhance any landscape while providing safety and security.



Each fixture is professional grade die-cast aluminum construction, built to perform. Path and flood fixtures come complete with stake, 4' of fixture cable and "Smart Connect" tool-free connector as well as a flat surface mount for decks or other applications. The 56 watt control center completes the system and features: CUL listed non-metallic housing, grounded cord set, photocontrol and easy cable connect. Complete fixture information on each carton includes: features, lighting layouts and dimensions.





## Tulip



Catalog #	Description	Wt.
TL-AB	Tulip 1.5w LED, antique bronze	2.3

The plant lover's favorite. Sweeping stem tulip, 20" tall with decorative leaves. Use along paths, walkways or to accent special planting. Creates a 6' pool of light with forward throw. Needs little or no watering!

## Mission



Catalog #	Description	Wt.
MS-AB	Mission 1.5w LED, antique bronze	3.3
MS-AG	Mission 1.5w LED, antique green	3.3

Traditional and classic. Complements a wide variety of architecture. Soft glow to side and ground. Stands 16" tall with 5" square head. Typical spacing 8'-10'.

## Seashell



Catalog #	Description	Wt.
SS-AB	Seashell 1.5w LED, antique bronze	2.0
SS-AG	Seashell 1.5w LED, antique green	2.0

Large seashell with adjustable knuckle. Use as full cut-off or tilt up (45° max.) for larger area coverage. A powerful and flexible luminaire for lighting large flower beds or plantings around building perimeters.

## Greenville



Catalog #	Description	Wt.
GN-AB	Greenville 1.5w LED, antique bronze	2.8
GN-PT	Greenville 1.5w LED, platinum silver	2.8

A stately appearance with classic shape. Stands 17" tall with 5" diameter head. Frosted glass lens provides soft lighting of taller surrounding plantings with 5' coverage. Use along walkways, steps. Typical spacing 8'-12'.

## Saturn



Catalog #	Description	Wt.
SA-AB	Saturn 1.5w LED, antique bronze	2.8
SA-PT	Saturn 1.5w LED, platinum silver	2.8

Modern and distinctive shepherd's crook with rotatable arm. Decorative copper-top head and cone shape frosted glass lens. Lighting covers 6' circle with ample vertical illumination for taller plantings. Make a statement with Saturn!

## Cone



Catalog #	Description	Wt.
CO-AB	Cone 1.5w LED, antique bronze	2.0
CO-AG	Cone 1.5w LED, antique green	2.0

Create a tropical image. The basic 7" diameter cone shape sits 16" high and creates a 5' lighted area with soft, indirect shielded light. Excellent for subtle illumination of plants or walkways.

## Reidville



Catalog #	Description	Wt.
RD-AB	Reidville 1.5w LED, antique bronze	3.3

Bell-shaped head supported by decorative arm and sturdy staff. Full cut-off pattern provides 5' pool of light on ground with no glare. Perfect for highlighting walkways, flowers and plants. Typical spacing 8'-10'.

## Flood



Catalog #	Description	Wt.
FL-AB	Flood 3w LED, antique bronze	2.0

Powerful 3w LED projection flood with adjustable knuckle for versatile aiming. Use for accent lighting of building facades, small signs or address numbers, columns, trees and residential flags to 20' height.

## Eyelid



Catalog #	Description	Wt.
EL-AB	Eyelid 1.5w LED, antique bronze	1.0
EL-PT	Eyelid 1.5w LED, platinum silver	1.0

Round 4" diameter eyelid for deck post or steplighting. Can be surface mounted or semi-recessed. Use for accent or small area illumination of perimeters or stairways. 2' mounting height provides soft coverage 5' wide, 2' forward.

## Recessed



Catalog #	Description	Wt.
RE-PT	Recessed 3w LED, pewter	1.5

Round recessed uplight for accent lighting of trees, columns and building facades. Powerful 3W LED projection beam. Provides hidden light source.

## Transformer &amp; Wiring



Catalog #	Description	Wt.
LVT56	56w low voltage transformer with PC	4.0
CB-75	75' 14 gauge low energy cable	6.0
CB-150	150' 14 gauge low energy cable	4.0

Non-metallic case protects timer controls and 120V-to-12V transformer. Surge protected with grounded cord/plug set and easy 12V cable attachment. Photocontrol triggers "time-on", eliminating seasonal adjustment. UL and c-UL certified (Controls 15 3w or 30 1.5w fixtures)

Low voltage #14 cable runs from LVT56 control center down path of lighting. UV protected, burial is not required, hide with mulch if desired. Perfect fit with fixture connectors for easy installation.

## Accessories included with fixtures



**STAKE**  
8" black die-cast aluminum stake with set screw and epoxy outer coating.



**FLAT SURFACE CONNECTOR**  
Each stake mounted fixture includes flat surface mount with two phillips head screws. Allows mounting to deck, steps or wood walkway.





Hubbell Lighting, headquartered in Greenville, SC, is a core business platform of Hubbell Incorporated. The platform supplies a comprehensive range of indoor and outdoor lighting products to industrial, commercial and institutional applications and is the largest manufacturer of residential lighting fixtures in North America.







**HUBBELL**  
Lighting

Canada  
Hubbell Canada LP  
870 Brock Road South  
Pickering, Ontario L1W 1Z8  
[www.hubbellonline.com](http://www.hubbellonline.com)

United States  
Hubbell Lighting, Inc.  
701 Millennium Boulevard  
Greenville, SC 29607  
[www.hubbelllighting.com](http://www.hubbelllighting.com)

Mexico  
Hubbell De Mexico, S.A. DE CV  
Av. Insurgentes Sur # 1228, 8th Floor  
Col. Tlacoquemecatl del Valle • 03200 Mexico, D.F.  
[www.hubbell.com.mx](http://www.hubbell.com.mx)

Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Copyright © 2013 HUBBELL LIGHTING All Rights Reserved HOL0059 EXPRESSLINE 12/13 Printed in Canada.