

1 kHz Reference Check

Measurement Report

DATE Thursday, 1 October 2026 at 22:17

INPUT —

MEASUREMENTS

Channel balance L-R -0.54 dB

Playback RPM 33.33 RPM • -0.01% vs 33 1/3 • Settled min 33.24 RPM • Settled max 33.42 RPM • Span 0.18 RPM

DIN-shaped wow & flutter RMS 0.032%

Raw speed variation Unweighted RMS $\pm 0.169\%$ • 2-sigma $\pm 0.338\%$

Raw wow/flutter components Unweighted wow RMS 0.163% • Unweighted flutter RMS 0.040%

1 kHz Electrical Crosstalk L→R -21.6 dB • R→L -18.6 dB • Balance 2.95 dB • Avg separation 20.1 dB

Distortion diagnostics L 1.72% THD • R 2.15% THD • THD L-R -0.43 pp • H2 R 2.0 dB higher • H3 L 4.4 dB higher

Harmonic reliability The right channel's third harmonic changed most during recording. Repeat before changing the cartridge setup.

Harmonic profile L 2nd -35.4 dB • 3rd -54.7 dB • 4th -71.6 dB • 5th -74.9 dB | R 2nd -33.4 dB • 3rd -59.1 dB • 4th -61.6 dB • 5th -69.4 dB