

Technics SL-1410MK2 - Empire 7000/III - ART USB phono plus

Measurement Report

DATE Thursday, 1 October 2026 at 12:18

INPUT USB Audio CODEC

MEASUREMENTS

Channel balance L-R -0.26 dB

Playback RPM 33.33 RPM • -0.01% vs 33 1/3 • Settled min 33.24 RPM • Settled max 33.41 RPM • Span 0.17 RPM

DIN-shaped wow & flutter RMS 0.040%

Raw speed variation Unweighted RMS $\pm 0.147\%$ • 2-sigma $\pm 0.294\%$

Raw wow/flutter components Unweighted wow RMS 0.139% • Unweighted flutter RMS 0.046%

1 kHz Electrical Crosstalk L→R -24.9 dB • R→L -22.8 dB • Balance 2.15 dB • Avg separation 23.8 dB

Distortion diagnostics L 2.26% THD • R 1.85% THD • THD L-R +0.41 pp • H2 L 1.7 dB higher • H3 L 5.3 dB higher

Harmonic reliability Steady during recording. Suitable for setup guidance.

Harmonic profile L 2nd -33.0 dB • 3rd -49.4 dB • 4th -63.0 dB • 5th -71.1 dB | R 2nd -34.7 dB • 3rd -54.6 dB • 4th -66.6 dB • 5th -74.7 dB