

Transfiguration Orpheus

Measurement Report

DATE Saturday, 26 September 2026 at 16:24

INPUT —

MEASUREMENTS

Channel balance L-R -0.35 dB

Playback RPM 33.51 RPM • +0.52% vs 33 1/3 • Settled min 33.42 RPM • Settled max 33.58 RPM • Span 0.16 RPM

DIN-shaped wow & flutter RMS 0.031%

Raw speed variation Unweighted RMS $\pm 0.136\%$ • 2-sigma $\pm 0.271\%$

Raw wow/flutter components Unweighted wow RMS 0.129% • Unweighted flutter RMS 0.039%

1 kHz Electrical Crosstalk L→R -19.1 dB • R→L -19.8 dB • Balance 0.64 dB • Avg separation 19.5 dB

Distortion diagnostics L 0.87% THD • R 1.18% THD • THD L-R -0.31 pp • H2 R 2.7 dB higher • H3 L 1.6 dB higher

Harmonic reliability Steady during recording. Suitable for setup guidance.

Harmonic profile L 2nd -41.3 dB • 3rd -60.1 dB • 4th -75.2 dB • 5th -73.3 dB | R 2nd -38.6 dB • 3rd -61.7 dB • 4th -77.1 dB • 5th -73.9 dB