

Micro Seiki QRP500 - Goldring 2100

Measurement Report

DATE Thursday, 1 October 2026 at 13:56

INPUT USB Audio CODEC

MEASUREMENTS

Channel balance L-R +0.32 dB

Playback RPM 33.36 RPM • +0.09% vs 33 1/3 • Settled min 33.27 RPM • Settled max 33.46 RPM • Span 0.19 RPM

DIN-shaped wow & flutter RMS 0.032%

Raw speed variation Unweighted RMS $\pm 0.163\%$ • 2-sigma $\pm 0.325\%$

Raw wow/flutter components Unweighted wow RMS 0.159% • Unweighted flutter RMS 0.033%

1 kHz Electrical Crosstalk L→R -22.4 dB • R→L -21.3 dB • Balance 1.13 dB • Avg separation 21.8 dB

Distortion diagnostics L 1.37% THD • R 1.97% THD • THD L-R -0.61 pp • H2 R 3.2 dB higher • H3 R 0.6 dB higher

Harmonic reliability Steady during recording. Suitable for setup guidance.

Harmonic profile L 2nd -37.5 dB • 3rd -51.1 dB • 4th -65.6 dB • 5th -75.2 dB | R 2nd -34.2 dB • 3rd -50.6 dB • 4th -57.5 dB • 5th -67.6 dB