

Ortofon 2M Bronze - Rega P3 - Audio Research SP20 - EVO4

Measurement Report

DATE Friday, 2 October 2026 at 9:44

INPUT EVO4

MEASUREMENTS

Channel balance L-R +0.53 dB

Playback RPM 33.34 RPM • +0.01% vs 33 1/3 • Settled min 33.26 RPM •
Settled max 33.41 RPM • Span 0.15 RPM

**DIN-shaped wow & flutter
RMS** 0.027%

Raw speed variation Unweighted RMS $\pm 0.125\%$ • 2-sigma $\pm 0.249\%$

**Raw wow/flutter
components** Unweighted wow RMS 0.120% • Unweighted flutter RMS
0.032%

1 kHz Electrical Crosstalk L→R -33.2 dB • R→L -32.4 dB • Balance 0.78 dB • Avg
separation 32.8 dB

Distortion diagnostics L 0.98% THD • R 1.13% THD • THD L-R -0.15 pp • H2 R 1.2
dB higher • H3 R 2.4 dB higher

Harmonic reliability The right channel's third harmonic changed most during
recording. Repeat before changing the cartridge setup.

Harmonic profile L 2nd -40.3 dB • 3rd -59.5 dB • 4th -63.2 dB • 5th -74.5 dB
| R 2nd -39.1 dB • 3rd -57.1 dB • 4th -58.9 dB • 5th -66.6 dB