JICO Shure V15 mr - Micro Seiki DQX500 - MA707 - Audio research SP20 - EVO4

Measurement Report

DATE Sunday, 18 October 2026 at 12:04

INPUT —

MEASUREMENTS

Channel balance	L-R -0.01 dB
Playback RPM	33.33 RPM • -0.02% vs 33 1/3 • Settled min 33.27 RPM • Settled max 33.39 RPM • Span 0.12 RPM
DIN-shaped wow & flutter RMS	0.025%
Raw speed variation	Unweighted RMS ±0.102% • 2-sigma ±0.204%
Raw wow/flutter components	Unweighted wow RMS 0.096% • Unweighted flutter RMS 0.032%
1 kHz Electrical Crosstalk	L→R -26.5 dB • R→L -28.2 dB • Balance 1.70 dB • Avg separation 27.3 dB
Distortion diagnostics	L 0.65% THD • R 0.49% THD • THD L-R +0.16 pp • H2 L 2.5 dB higher • H3 L 3.7 dB higher
Harmonic reliability	The right channel's third harmonic changed most during recording. Repeat before changing the cartridge setup.
Harmonic profile	L 2nd -43.8 dB • 3rd -70.1 dB • 4th -73.4 dB • 5th -82.2 dB | R 2nd -46.3 dB • 3rd -73.8 dB • 4th -74.8 dB • 5th -70.0 dB