



Tools – Logo Replacement Tool

Ver 0.2

SEG Group, Insyde Software

Jul. 06, 2016

History

Revision history for this material

Rev.	Data	Author	Approver	Summary
0.1	2013/08/02	Stone Cheng	Giant Liang	Initial version
0.2	2016/01/20	Tom Pan	Giant Liang	1. C code base on H2OEZE 2. Support image file format conversion

Agenda

- **Before Using H2OLRT**
- **Features**
- **UEFI Shell / DOS**
 - **Support mode**
 - **Arguments**
 - **Usage**

Features

- To provide replacing logo and BIOS version functions for BIOS image file
- Supported OS environment
 - DOS
 - UEFI SHELL

Before Using H2OLRT

Before Using H2OLRT

a. Logo format choices-

There are 4 logo format supported.

1. Jpeg
2. Pcx
3. Tga
4. Bmp
5. Gif

b. BIOS version name limitation –

- Max length 25

Before Using H2OLRT

c. Logo Index selection –

- BIOS code according to GUID to get logo. So user should also decide which picture to replace by GUID.

d. Logo file size limitation –

- There is no specific limitation. If the FV space is enough for new picture. It's OK to replace.

Support mode

Support mode

- Command (Console) mode only
 - Run H2OLRT with arguments, as 'help' command for example:
 - DOS
 - H2OLRT-D -h
 - UEFI Shell
 - 32bits : H2OLRT-S -h
 - 64bits : H2OLRT-Sx64 -h
- The following diagrams are executed on DOS platform

Support mode

- Illustrate executing `-h` command :

```
D:\>H20ELU-D.exe -h
Insyde H20LRT (Logo Replacement Tool) Version 100.00.02.10
Copyright (c) 2012 - 2016, Insyde Software Corp. All rights reserved.

-biosver          Specify the new BIOS version
-logoconvert      Specify whether to keep original image's format and
                  dimension or to use new image's format and dimension
-logoindex        Specify the index of to-be-replaced target logo
-logopath         Specify the logo file path
-out             Specify the BIOS image's output file path
-repbiosver       Specify the source BIOS image to replace BIOS version
-replogo          Specify the source BIOS image to replace replacement

Replace Logo
-replogo:[SrcBIOSImageName] -logopath:[LogoImagePathName] -logoindex:[Index] -logoconvert:[0/1] -out:[OutputPath]

Replace BIOS Version
-repbiosver:[SrcBIOSImageName] -biosver:[BIOSVersion] -out:[OutputPath]

Help
-h
```

Arguments

Arguments

- All arguments and parameters are specified with “-argument:parameter”, use double quotes to encapsulate the parameter text with spaces

Argument	Description
h	Display Help information
replogo	Specify the input bios image to do logo replacement
logopath	Specify the logo file path
logoindex	Specify the index of to-be-replaced target logo (zero-based)
logoconvert	Specify whether to keep original image's dimension or to use new image's dimension
repbiosver	Specify the input bios image to do bios version replacement
biosver	Specify the new bios version
out	Specify the bios image's output file path (Optional, if ignored, default to input bios image file)

Usage

Usage

Display available logo indices

- Type command "H2OLRT-D -replologo :[ImagePathName]"

```
D:\>H20ELU-D.exe -replologo:bios.fd
Insyde H2OLRT (Logo Replacement Tool) Version 100.00.02.10
Copyright (c) 2012 - 2016, Insyde Software Corp. All rights reserved.

Replace Logo:
  Bios path: bios.fd
  Logo path:

Available indices:
Index 0 -> FuNum: 0, Image format: PCX, Size: 27068 Bytes, W: 1024, H: 768
          Guid: 6F0CF054-AE6A-418C-A7CE-3C7A7CD74EC0
Index 1 -> FuNum: 1, Image format: JPG, Size: 12884 Bytes, W: 300, H: 300
          Guid: 931F77D1-10FE-48BF-AB72-773D389E3FAA
Index 2 -> FuNum: 1, Image format: JPG, Size: 17656 Bytes, W: 360, H: 360
          Guid: 771F77D1-13AF-48BF-2584-773D389E33CA
Index 3 -> FuNum: 1, Image format: JPG, Size: 3469 Bytes, W: 155, H: 68
          Guid: 96DCE314-3628-4256-A02E-3B10C61D85FD
Index 4 -> FuNum: 1, Image format: JPG, Size: 7831 Bytes, W: 208, H: 157
          Guid: 931F00D1-10FE-48BF-AB72-773D389E3FDA
```

Usage

Replace logo

- Type command "H2OLRT-D -relogo:[SrcBIOSImageName] – logopath:[LogoImagePathName] – logoindex:[IndexId] –logoconvert:[0|1] –out:[OutputPath]"
 - "-logoconvert" default is conversion(1) if ignored
 - "-out" is optional to save as the new image name

```
D:\>H2OLRT-D.exe -relogo:bios.fd -logopath:loading.gif -logoindex:2 -logoconvert:1 -out:logo.fd
Insyde H2OLRT (Logo Replacement Tool) Version 100.00.02.10
Copyright (c) 2012 - 2016, Insyde Software Corp. All rights reserved.

Replace Logo:
  Bios path: bios.fd
  Logo path: loading.gif
  Logo index: 2
  Logo convert: Yes
  Logo funum: 1
  Logo guid: 771F77D1-13AF-48BF-2584-773D389E33CA
  Logo out: logo.fd

Result:
Compress Firmware Volume....
Success!!
```

Usage

Replace bios version

- Type command "H2OLRT-D -repbiosver:[SrcBIOSImageName] -biosver:[NewBiosVersion] -out:[OutputPath]"
 - "-out" is optional to save as the new image name

```
D:\>H2OLRT-D.exe -repbiosver:bios.fd -biosver:Insyde U1.02 -out:ver.fd
Insyde H2OLRT (Logo Replacement Tool) Version 100.00.02.10
Copyright (c) 2012 - 2016, Insyde Software Corp. All rights reserved.

Replace Bios Version:
  Bios path: bios.fd
  Bios version: Denlow.05.04.21.0007
  New bios version: Insyde U1.02
  Bios out: ver.fd

Result:
Compress Firmware Volume....
Success!!

D:\>
```

Thanks!