

# Value Objects



Dirk Riehle, FAU Erlangen

**ADAP B06**

Licensed under [CC BY 4.0 International](https://creativecommons.org/licenses/by/4.0/)

# Agenda

---

1. Values vs. objects
2. Value equality
3. Immutable objects
4. Shared value objects
5. The QuantityUnit type
6. Value type constructors
7. Value types in practice

# 1. Values vs. Objects



# Values

Values are timeless abstractions; they have

- No life-cycle, no birth or death, and do not change
  - Unless you consider human invention of a value its birth
- No identity, cannot be counted, there is only “one copy”

Values are instances of value types (a.k.a. data types)

# Objects

Objects are virtual physical entities in the real / modeled world; they

- Exist in time and have a life-cycle, i.e. they
  - Can be created, changed, shared, deleted
- Have an identity independent of their attribute values

Objects are instances of object types (a.k.a. classes)

# Value vs. Object Semantics in Programming

Value semantics implies that

- Values are copied (unless made immutable)

Object semantics implies that

- Objects are moved around by reference (a value)

# Examples of Value Types

So-called primitive or built-in [1] or atomic value types include


- boolean and bits
- numbers (int, long, float)
- characters and strings
- object references

Domain-specific value types, include, but are not limited to

- Coordinates and homogeneous names
- SI units and their ranges and restrictions
- Monetary amount, interest rate, stock symbol
- URLs, http return codes

[1] Rule of thumb: If it fits into a (8, 16, 32, ...) register, it is a built-in value type

# Occurrences and Representations of Objects and Values



DR



# Values and Objects in Programming Languages

There typically is no first-class concept of “value type” [1]

Hence, values are often implemented as **immutable** objects

**Mutable objects** lead to side-effects, i.e. aliasing, a common source of bugs

[1] See <https://dirkriehle.com/publications/1998-selected/values-in-object-systems/> for various techniques and approaches, some of which are discussed in this lecture

# Advantages of Value Semantics

Using domain-specific value types

- Brings your programming closer to the problem domain
- Removes or restrain a major source of bugs (aliasing)
- May enhance system performance (shared, immutable)

Lack of identity allows for free copying

- No need for a separate database table to store values
- Value objects can be serialized in-line for network transfer
- No need for cross-process references in distributed systems

# Object References (Identifiers)

Object identifiers are always values

- In-memory object pointer
- Handle (special type of pointer)
- External object identifier
- Primary keys

Object identifiers are not locations

- But locations are often (wrongly) used to identify objects

## 2. Value Equality



# The Java equals() Contract for Any Object [1]


Applies to any runtime object (whether a regular object or a value object)

1. Reflexive: For any non-null reference `x`, `x.equals(x)` should return true.
2. Symmetric: For any non-null references `x` and `y`, `x.equals(y)` should return true if and only if `y.equals(x)` returns true.
3. Transitive: For any non-null references `x`, `y`, and `z`, if `x.equals(y)` returns true and `y.equals(z)` returns true, then `x.equals(z)` should return true.
4. Consistent: For any non-null references `x` and `y`, multiple invocations of `x.equals(y)` consistently return true or consistently return false, provided no information used in `equals()` comparisons on the objects is modified.
5. Null-Object: For any reference `x`, `x.equals(null)` should return false.

# The Equality Contract for Value Objects

Like the equality contract for any object plus

- An interface represents the value type
- The implementation classes represent an equivalency set



DR

# AbstractCoordinate.isEqual() Implementation

```
export abstract class AbstractCoordinate implements Coordinate {  
  
    public isEqual(other: Coordinate): boolean {  
        return (this.doGetX() == other.getX()) && (this.doGetY() == other.getY());  
    }  
  
    ...  
  
}
```

### **3. Immutable Objects**





# Immutable Objects



Immutable objects are objects that

- Have no mutation methods (never change their state)

# Immutable Value Objects

Value types are often implemented as immutable object classes

- (Former) mutation methods return another value object with the desired state

The result object may or may not be a new value object

```
export class CartesianCoordinate extends AbstractCoordinate {  
    ...  
  
    protected doSetX(x: number): Coordinate {  
        return new CartesianCoordinate(x, this.y);  
    }  
  
    protected doSetY(y: number): Coordinate {  
        return new CartesianCoordinate(this.x, y);  
    }  
  
    ...  
}
```

# Advantages and Disadvantages of Immutable Objects

## Advantages

- No side effects from aliasing!
- Safe and perform well in concurrent programming

## Disadvantages

- Increased object creation
- Your garbage collector may run hot quickly

# Design by Contract and Immutable Value Objects

## Preconditions

- Don't change

## Class invariants

- Are always the same: State did not change

## Postconditions

- Move to the result object

## 4. Shared Value Objects



# Shared Value Objects

---

One value → one object

# Advantages and Disadvantages of Sharing Value Objects

## Advantages

- Reduced (minimal!) memory consumption
- (Parts of) equality test can be reduced to identity test
- Hash code computation can be reduced to basic object hash code

## Disadvantages

- Added programming complexity
- Performance penalty for organizing shared objects
- Gets more difficult with more than one implementation class

# Handle / Body Idiom + Copy-on-Write [1]

The handle / body idiom

- Separates handle (reference) from body (payload)
- The handle is copied as the object is passed around

Copy-on-write

- Keeps the handle through which the write happens but
- Copies the body before mutation

This is a technique better suited than immutable objects for heavyweight objects



## 5. The QuantityUnit Type

---

# Design Exercise

---

Design a function that accepts a distance and a speed as the input

Compute and return the time it takes to go that distance at that speed

# A Short Interlude About Requirements

## Functional requirements missing

- Precision of calculation?
- What types of units?
- ...

## Non-functional requirements missing

- Speed of calculation?
- Concurrent computation?
- ...


# What's Wrong With This Solution?

```
export function calculateDuration1(distance: number, speed: number): number {  
    return distance / speed;  
}
```

# Base Units of the Metric System

Quantity	Base Unit	Symbol
Length	meter	m
Mass	kilogram	kg
Time	second	s
Electric current	Ampere	A
Thermodynamic temperature	Kelvin	K
Luminous intensity	Candela	cd
Amount of substance	mole	mol

# Introducing QuantityUnit



# Implementing (SI) Units

```
export class SIUnit {
  protected exponents: number[] = [0, 0, 0, 0, 0, 0, 0];

  constructor(exponents: number[]) {
    this.exponents = [...exponents];
  }

  public isEqual(other: SIUnit): boolean {
    return this.exponents.every((v, i) => v === other.exponents[i]);
  }

  public add(other: SIUnit): SIUnit {
    IllegalArgumentException.assert(!other.isEqual(this));
    return new SIUnit(this.exponents);
  }
  ...

  public multiply(other: SIUnit): SIUnit {
    let result: number[] = [0, 0, 0, 0, 0, 0, 0];
    for (let i = 0; i < this.exponents.length; i++) {
      result[i] = this.exponents[i] + other.exponents[i];
    };
    return new SIUnit(result);
  }
  ...
}
```

# A Better calculateDuration() Function

```
export function calculateDuration2(distance: number, speed: number): QuantityUnit {  
    IllegalArgumentException.assertCondition(speed != 0);  
    return new QuantityUnit(distance / speed, new SIUnit([0, 0, 1, 0, 0, 0, 0]));  
}
```

## Possible improvements

- Turn distance and speed into QuantityUnits
- Have base units ready as Unit instances e.g. for seconds



## 5. Value Type Constructors



# Value Type Constructors

Arrays, i.e. [ ]

Enumerations, i.e. enum

Parameterized types a.k.a. generics i.e. <...>

# Enumerations as Value Type Constructors

Enums provide shared values out of the box

- Immutability needs to be ensured by programming

Enums are great for documenting and type-checking codes!

# Parameterized Types as Value Type Constructors

Common parameterized types are ranges and range restrictions [1]

# Parameterized Types as Value Type Constructors [1]

```
export class RangeBound<T> {  
  
    protected value: T;  
    protected inclusive: boolean;  
  
    constructor(value: T, inclusive: boolean) {  
        this.value = value;  
        this.inclusive = inclusive;  
    }  
  
    public getValue(): T {  
        return this.value;  
    }  
  
    public isInclusive(): boolean {  
        return this.inclusive;  
    }  
}
```

```
export class Range<T> {  
  
    protected lowerBound: RangeBound<T>;  
    protected upperBound: RangeBound<T>;  
  
    constructor(lb: RangeBound<T>, ub: RangeBound<T>) {  
        this.lowerBound = lb;  
        this.upperBound = ub;  
    }  
  
    public includes(value: T): boolean {  
        let lowerValue = this.lowerBound.getValue();  
        let upperValue = this.upperBound.getValue();  
        ...  
    }  
  
    public getLowerBound(): RangeBound<T> {  
        return this.lowerBound;  
    }  
  
    ...  
}
```

# Example Data From the GeBOS System [1]

The GeBOS was a large C++ software to operate cooperative banks

It had about 50 unique base domain-specific value object classes

It had about 20 unique constructors, generating hundreds of value types

It had more than 200 enums representing various domain-specific codes

[1] Bäumer, D., Gryzcan, G., Knoll, R., Lilienthal, C., Riehle, D. & Züllighoven, H. (1997). [Framework Development for Large Systems](https://oss.cs.fau.de). Communications of the ACM, vol. 40, no. 10, pp. 52-59.

# Summary

---

1. Values vs. objects
2. Value equality
3. Immutable objects
4. Shared value objects
5. The QuantityUnit type
6. Value type constructors

# Thank you! Any questions?



[dirk.riehle@fau.de](mailto:dirk.riehle@fau.de) – <https://oss.cs.fau.de>

[dirk@riehle.org](mailto:dirk@riehle.org) – <https://dirkriehle.com> – [@dirkriehle](#)



# Legal Notices

## License

- Licensed under the [CC BY 4.0 International](https://creativecommons.org/licenses/by/4.0/) license

## Copyright

- © 2012, 2018, 2024 Dirk Riehle, some rights reserved