



TECHNICAL DATASHEET

Rev. 2026-09

LOGX CAT 6A S/FTP SHIELDED LAN CABLE

CAT6A S/FTP LAN Cable, 305 m Box

LOGX CAT6A S/FTP LAN CABLE (305M) COPPER 0.54MM, 4 PAIR S/FTP, 23 AWG

PART NUMBER

LXC6ASFPVG305

DESCRIPTION

LOGX CAT 6A S/FTP Solid LAN Cable is engineered for maximum electromagnetic interference (EMI) protection in enterprise 10-Gigabit Ethernet deployments. Features 23AWG (0.54mm) solid bare copper conductors, individual foil shielding around each pair (AL-Foil), and an overall tinned copper braid shield.

FEATURES & BENEFITS

- Double Shielding (S/FTP):** Individual Foil per pair + Overall Tinned Braid
- Solid 23AWG Bare Copper** (0.54mm) for superior 10GBASE-T performance
- Extended 500MHz Bandwidth** with high signal-to-noise ratio
- Ultimate Alien Crosstalk (ANEXT) & EMI Immunity**
- 100% Pass Fluke Channel / Permanent Link certified
- 305 Meter (1000 ft) Wooden Drum / Dispenser packaging

TYPICAL APPLICATIONS

- 10GBASE-T 10-Gigabit Ethernet Data Center Infrastructure
- High EMI Industrial & Mission-Critical Server Racks
- High-Power PoE / PoE+ / PoE++ (IEEE 802.3bt up to 90W)



COMPLIANCE & STANDARDS

- ✓ ANSI/TIA-568.2-D Category 6A
- ✓ ISO/IEC 11801 Class EA | IEC 61156-5
- ✓ EN 50173-1 & EN 50288-10-1
- ✓ 100% Pass Fluke Test Certified
- ✓ RoHS & REACH Compliant

COLOR CODING

|        |                       |
|--------|-----------------------|
| Pair 1 | White-Blue / Blue     |
| Pair 2 | White-Orange / Orange |
| Pair 3 | White-Green / Green   |
| Pair 4 | White-Brown / Brown   |

SPECIFICATIONS & TECHNICAL PARAMETERS

|                   |                                                        |                    |                                    |
|-------------------|--------------------------------------------------------|--------------------|------------------------------------|
| Product Standard  | LOGX CAT6A S/FTP Shielded LAN Cable                    | Conductor Material | Solid Bare Copper 0.54mm (23 AWG)  |
| Individual Shield | Each Pair Aluminum / Mylar Foil Shield (100% Coverage) | Overall Shield     | Tinned Copper Wire Braiding Shield |
| Outer Sheath      | Flame-Retardant PVC / LSZH (Grey Color)                | Overall Diameter   | 7.6 ± 0.4 mm                       |
| Packaging         | 305M (1000ft) Wooden Drum / Dispenser Reel             | Test Performance   | 100% Pass Fluke Test (500 MHz)     |

MECHANICAL CHARACTERISTICS

|                 |                                |
|-----------------|--------------------------------|
| Bending Radius  | 8 × Cable Diameter (Installed) |
| Pulling Tension | 120 N   Elongation ≥ 100%      |
| Operating Temp. | -20°C to +60°C                 |

ELECTRICAL CHARACTERISTICS

|                     |                                               |
|---------------------|-----------------------------------------------|
| Frequency Bandwidth | Up to 500 MHz (10GBASE-T High Speed)          |
| Shielding Immunity  | Screening Attenuation ≥ 75 dB (EMI/RFI Proof) |
| Quality Test        | 100% Pass Fluke Channel / Permanent Link      |

ORDERING INFORMATION

| PART NUMBER   | DESCRIPTION                      | PACKAGING |
|---------------|----------------------------------|-----------|
| LXC6ASFPVG305 | CAT6A S/FTP LAN Cable, 305 m Box | 305M Drum |