

LGX-MC10GSFP+ | LOGX 1G & 10G SFP PORT FIBER TO ETHERNET MEDIA CONVERTER

10G SFP+

DESCRIPTION

LOGX SFP Media Converters transparently convert copper Ethernet signals (RJ45) to fiber optic signals via standard SFP/SFP+ slots. Designed in a rugged metal enclosure with low power consumption, auto-negotiation, and Link Fault Pass-Through (LFP) for reliable enterprise network extension.

FEATURES & BENEFITS

- Converts 10/100/1000M or 10G Copper to High-Speed Optical Fiber
- Open Standard SFP / SFP+ Slot compatible with all MSA-compliant transceivers
- Auto-Negotiation & Auto-MDI/MDIX on RJ45 port eliminates crossover cables
- Link Fault Pass-Through (LFP) enables instant fault alerting on remote connections
- Rugged, compact metal chassis engineered for optimal heat dissipation and long MTBF
- Comprehensive LED status indicators for power, fiber link, copper activity, and speed

TYPICAL APPLICATIONS

- Extending Local Area Networks (LAN) over Long-Distance Fiber Optic Backbones
- Connecting Remote IP CCTV Cameras and Wi-Fi Access Points to Central Core Switches
- Data Center Server Interconnections (10GBASE-T to 10G SFP+)

SPECIFICATIONS & TECHNICAL PARAMETERS

Product Standard	LOGX Industrial/Enterprise Media Converter	Models Available	1G SFP (10/100/1000M) / 10G SFP+ (10GBASE-T to 10G SFP+)
Copper Interface	1 × RJ45 Port (Auto-MDI/MDI-X, Auto-Negotiation)	Fiber Interface	1 × Open SFP / SFP+ Slot (Universal Compatibility)
Chassis Material	Durable Metal Casing for Heat Dissipation	LED Indicators	PWR, 1000M/10G, Link/Act, FX Link/Act, TP Link/Act
Power Input	DC 5V / 1A (1G) DC 12V / 1A (10G), Adapter Included	Dimensions (W×D×H)	70 × 94 × 26 mm (1G) 94 × 70 × 26 mm (10G)



COMPLIANCE & STANDARDS

- IEEE 802.3ab (1000BASE-T), IEEE 802.3z (1000BASE-X)
- IEEE 802.3an (10GBASE-T), IEEE 802.3ae (10GBASE-SR/LR)
- CE, FCC Class A, RoHS Compliant

TECHNICAL SPECIFICATIONS

Forwarding Mode	Store-and-Forward Switching Architecture
Transmission Dist.	1G: 550m MMF / 120km SMF 10G: 300m MMF / 80km SMF
Power Consumption	< 3 Watts (1G) < 6 Watts (10G)

ENVIRONMENTAL SPECIFICATIONS

Operating Temp.	0°C to +50°C Storage: -20°C to +70°C
Operating Humidity	5% to 90% Non-condensing
Certifications	CE, FCC Class A, RoHS

ORDERING INFORMATION

PART NUMBER	DESCRIPTION	SPEED
LGX-MC1000GSFP	Logx SFP port 1G Media converter (10/100/1000M RJ45 to 1G SFP Slot, Metal Case)	1 Gigabit (1G)
LGX-MC10GSFP+	Logx SFP port 10G Media converter (10GBASE-T RJ45 to 10G SFP+ Slot, Metal Case)	10 Gigabit (10G)