

LXC6UUPVG305 | LOGX CAT6 UTP LAN CABLE (305M) 24AWG, BARE COPPER 0.52MM, PASS FLUKE TEST, GREY

305M BOX

DESCRIPTION

LOGX CAT 6 U/UTP Solid LAN Cable is engineered for high-performance Gigabit network cabling. Built with 24AWG solid bare copper conductors (0.52mm), HDPE insulation, internal PE cross separator, and flame-retardant PVC sheath. Exceeds Category 6 transmission standards and guaranteed 100% Pass Fluke Test.

FEATURES & BENEFITS

- **Solid 24AWG Bare Copper (0.52mm)** for maximum signal conductivity
- **Integrated PE Central Cross Separator** to minimize internal crosstalk (NEXT)
- **250MHz Performance Bandwidth** tested and certified
- **100% Pass Fluke Test** guaranteed quality standard
- Durable, easy-strip PVC outer sheath (Grey)
- 305 Meter (1000 ft) Easy-Pull Reel in Box packaging

TYPICAL APPLICATIONS

- 1000BASE-T Gigabit Ethernet & 100BASE-TX Fast Ethernet
- Horizontal Cabling in Structured Telecommunications Networks
- High-Speed VoIP, IP CCTV Surveillance, and Smart Building Systems
- Power over Ethernet (PoE / PoE+ IEEE 802.3af/at)



CAT 6 U/UTP - 4 PAIR - 24 AWG SOLID

COMPLIANCE & STANDARDS

- ANSI/TIA-568.2-D Category 6
- ISO/IEC 11801 Class E | IEC 61156-5
- EN 50173-1 & EN 50288-6-1
- 100% Pass Fluke Test Certified
- RoHS & REACH Compliant

COLOR CODING

Pair 1	White-Blue / Blue
Pair 2	White-Orange / Orange
Pair 3	White-Green / Green
Pair 4	White-Brown / Brown

SPECIFICATIONS & TECHNICAL PARAMETERS

Product Standard	LOGX CAT6 U/UTP Solid Cable	Conductor Material	Solid Bare Copper 0.52mm (24 AWG)
Insulation	High-Density Polyethylene (HDPE)	Central Cross Member	PE Cross Separator (Internal Spline)
Outer Jacket	Durable PVC (Grey Color)	Overall Diameter	5.8 ± 0.3 mm
Packaging	305M (1000ft) Easy-Pull Box	Test Performance	100% Pass Fluke Test (250 MHz)

MECHANICAL CHARACTERISTICS

Bending Radius	4 × Cable Diameter (Installed)
Max. Pulling Force	100 N Elongation ≥ 100%
Temperature Range	-20°C to +60°C (Operating)

ELECTRICAL CHARACTERISTICS

Frequency Bandwidth	Up to 250 MHz (Exceeds ANSI/TIA-568.2-D)
DC Resistance Unbal.	≤ 2.5% Velocity of Prop. 68%
Quality Test	100% Pass Fluke Channel / Link Test

ORDERING INFORMATION

PART NUMBER	DESCRIPTION	PACKAGING
LXC6UUPVG305	Logx CAT6 UTP LAN CABLE (305M) 24 AWG, BARE COPPER 0.52 MM, PASS FLUKE TEST, UTP, SOLID CABLE GREY	305M / Box