

LXCJ6UFT | LOGX K1014 UTP CAT6 & CAT6A KEYSTONE JACK 180 DEGREE TOOLLESS

CAT 6

DESCRIPTION

LOGX K1014 Toolless Keystone Jacks deliver fast, punch-free, and high-performance termination for Category 6 (250MHz) and Category 6A (500MHz) unshielded structured cabling. Engineered with a 180-degree toolless butterfly closing mechanism, phosphor bronze contacts plated with 50-microinch gold, and full compliance with PoE++ IEEE 802.3bt (up to 90W).

FEATURES & BENEFITS

- **180-Degree Toolless Termination** without requiring a 110 punchdown tool
- **50µ" Gold-Plated Contacts** for maximum signal integrity & anti-corrosion
- **Dual T568A & T568B Color Coding** with clear wire guide cap
- **Compact Slim Profile** fits high-density 24-port / 48-port panels & faceplates
- Supports Power over Ethernet (PoE / PoE+ / PoE++ IEEE 802.3bt up to 90W)
- High-impact flame-retardant UL 94V-0 white polycarbonate housing

TYPICAL APPLICATIONS

- Horizontal Cabling Termination in 19" Patch Panels and 86-Type Faceplates
- CAT6 (Gigabit) and CAT6A (10-Gigabit) Enterprise Data Center Networks
- High-Density Server Racks and Workstation Outlets

SPECIFICATIONS & TECHNICAL PARAMETERS

Product Standard	LOGX K1014 180° Toolless Keystone Jack	Shielding Type	UTP (Unshielded)
Housing Material	Flame-Retardant Polycarbonate (UL 94V-0)	RJ45 Contacts	Phosphor Bronze with 50µ" Gold Plating
Termination Type	180-Degree Toolless Butterfly Latch & Wire Cap	Wiring Standard	Dual T568A & T568B Color Coded
Supported Conductors	Solid & Stranded 22-26 AWG Copper	Durability	≥ 750 Insertions (RJ45) ≥ 250 Re-terminations

MECHANICAL CHARACTERISTICS

Plug Insertion Life	750 Mating Cycles
IDC Re-terminations	250 Cycles (22-26 AWG)
Holding Force	30 lbs (133 N) between plug and jack

ELECTRICAL CHARACTERISTICS

Contact Resistance	≤ 20 mΩ Insulation Res. ≥ 500 MΩ
Dielectric Strength	1000V AC RMS 60Hz 1 Min
Current Rating	1.5 Amps PoE/PoE++ Compatible (up to 90W)



COMPLIANCE & STANDARDS

- ANSI/TIA-568.2-D Category 6 & Category 6A
- ISO/IEC 11801 Class E & Class E_A
- IEC 60603-7-4 & IEC 60603-7-41
- IEEE 802.3bt (Type 4 PoE 90W)
- UL 94V-0 Fire Safety Standard
- RoHS & REACH Compliant

ORDERING INFORMATION

PART NUMBER	DESCRIPTION	CATEGORY
LXCJ6UFT	Logx K1014 UTP Cat6 Keystone Jack 180 Degree Toolless, 50u Gold Plated, White	CAT 6
LXCJ6AUFT	Logx K1014 UTP Cat6A Keystone Jack 180 Degree Toolless, 50u Gold Plated, White	CAT 6A