

LXFCLCLCDUS315 | LOGX LC-LC UPC SM & OM3 DUPLEX 2.0MM FIBER PATCH CORD

15M · MULTIMODE OM3 (AQUA)

DESCRIPTION

LOGX LC-LC Duplex Fiber Optic Patch Cords are factory-terminated with ultra-precision zirconia ceramic ferrules for low insertion loss and high return loss. Available in Single Mode (OS2 Yellow) and 10G Multimode (OM3 Aqua) across all standard lengths from 1M to 100M for data center and optical network connections.

FEATURES & BENEFITS

- **100% Factory Interferometer & Insertion Loss Tested** for guaranteed performance
- **Ultra-Precision Zirconia Ceramic Ferrules** (Insertion Loss ≤ 0.2 dB)
- **Available in Single Mode OS2 (Yellow) and 10G Multimode OM3 (Aqua)**
- **2.0mm Duplex Zipcord Construction** with flexible PVC outer jacket
- Complete range of pre-terminated lengths: 1M, 3M, 5M, 10M, 15M, 20M, 25M, 30M, 40M, 50M, 70M, 100M
- Includes protective dust caps and individual test report bag

TYPICAL APPLICATIONS

- Data Center Fiber SAN, Switches, SFP/SFP+ Transceivers, and Patch Panels
- High-Speed 10G/40G/100G Telecom Backbone & FTTx Infrastructure
- Broadband Optical Transmission and Industrial Automation

SPECIFICATIONS & TECHNICAL PARAMETERS

Connector Type	LC/UPC to LC/UPC Duplex	Fiber Types	Single Mode 9/125 μ m (OS2) / Multimode 50/125 μ m (OM3)
Outer Diameter	Duplex 2.0 mm (Zipcord Cable)	Jacket Material	Durable PVC / Flame-Retardant Sheath
Jacket Color	Yellow (Single Mode OS2) / Aqua (Multimode OM3)	Ferrule Material	High-Precision Zirconia Ceramic Ferrule
Insertion Loss	≤ 0.20 dB (Typical ≤ 0.15 dB)	Return Loss	≥ 50 dB (UPC SM) ≥ 35 dB (OM3)

OPTICAL & MECHANICAL SPECS

Insertion Loss	≤ 0.2 dB (1310/1550nm SM 850/1300nm OM3)
Durability	1000 Mating Cycles (Δ IL ≤ 0.2 dB)
Repeatability	≤ 0.1 dB Tensile Strength ≥ 100 N

ENVIRONMENTAL SPECIFICATIONS

Operating Temp.	-40°C to +75°C
Storage Temp.	-45°C to +85°C
Standard Compliance	Telcordia GR-326-CORE, IEC 61754-20



COMPLIANCE & STANDARDS

- TIA/EIA-568.3-D & ISO/IEC 11801
- Telcordia GR-326-CORE / IEC 61754-20
- UL 94V-0 & RoHS Compliant

ORDERING INFORMATION

SM PART NO. (OS2 YELLOW)	OM3 PART NO. (AQUA)	DESCRIPTION	LENGTH
LXFCLCLCDUS201	LXFCLCLCDUS301	Logx LC-LC-UPC Duplex 2.0 Fiber Optic Patch Cord, PVC	1 Meter
LXFCLCLCDUS203	LXFCLCLCDUS303	Logx LC-LC-UPC Duplex 2.0 Fiber Optic Patch Cord, PVC	3 Meters
LXFCLCLCDUS205	LXFCLCLCDUS305	Logx LC-LC-UPC Duplex 2.0 Fiber Optic Patch Cord, PVC	5 Meters
LXFCLCLCDUS210	LXFCLCLCDUS310	Logx LC-LC-UPC Duplex 2.0 Fiber Optic Patch Cord, PVC	10 Meters
LXFCLCLCDUS215	LXFCLCLCDUS315	Logx LC-LC-UPC Duplex 2.0 Fiber Optic Patch Cord, PVC	15 Meters
LXFCLCLCDUS220	LXFCLCLCDUS320	Logx LC-LC-UPC Duplex 2.0 Fiber Optic Patch Cord, PVC	20 Meters
LXFCLCLCDUS225	LXFCLCLCDUS325	Logx LC-LC-UPC Duplex 2.0 Fiber Optic Patch Cord, PVC	25 Meters
LXFCLCLCDUS230	LXFCLCLCDUS330	Logx LC-LC-UPC Duplex 2.0 Fiber Optic Patch Cord, PVC	30 Meters
LXFCLCLCDUS240	LXFCLCLCDUS340	Logx LC-LC-UPC Duplex 2.0 Fiber Optic Patch Cord, PVC	40 Meters
LXFCLCLCDUS250	LXFCLCLCDUS350	Logx LC-LC-UPC Duplex 2.0 Fiber Optic Patch Cord, PVC	50 Meters
LXFCLCLCDUS270	LXFCLCLCDUS370	Logx LC-LC-UPC Duplex 2.0 Fiber Optic Patch Cord, PVC	70 Meters
LXFCLCLCDUS2100	LXFCLCLCDUS3100	Logx LC-LC-UPC Duplex 2.0 Fiber Optic Patch Cord, PVC	100 Meters