

LXFPRLC12 | LOGX 6, 12, 24 & 48 PORT LC DUPLEX LOADED FIBER PATCH PANEL

12 PORT (1U)

DESCRIPTION

LOGX Sliding Rail Fiber Optic Patch Panels provide high-density fiber patching and splicing in standard 19-inch equipment racks. Pre-loaded with high-precision LC/UPC duplex adapters, smooth telescopic ball-bearing sliding rails for easy front maintenance, and complete internal splice management trays.

FEATURES & BENEFITS

- **Pre-Loaded with LC/UPC Duplex Singlemode Adapters** with zirconia sleeves
- **Smooth Telescopic Ball-Bearing Sliding Drawer** for easy front access without removing unit
- **Complete Splice Kit Included** (Splice trays, heatshrink holders, and protective sleeves)
- **4 Rear Cable Entry Ports** equipped with cable clamps and rubber protection glands
- Constructed from 1.2mm electro-galvanized cold-rolled steel with black powder finish
- Available in 1U (6, 12, 24 Port) and 2U (48 Port) configurations

TYPICAL APPLICATIONS

- Data Center Fiber Density Patching & Main Cross-Connect (MC)
- Telecom Central Offices, FTTx Core Nodes, and Enterprise Racks
- High-Speed 10G/40G/100G Optical Backbone Distribution

SPECIFICATIONS & TECHNICAL PARAMETERS

Product Standard	LOGX 19" Sliding Rail Fiber Patch Panel	Adapter Type	Loaded with LC/UPC Duplex Singlemode Adapters (Blue)
Capacities Available	6 Port (1U) / 12 Port (1U) / 24 Port (1U) / 48 Port (2U)	Chassis Material	1.2mm High-Strength Cold-Rolled Steel (SPCC)
Sliding Mechanism	Smooth Telescopic Ball-Bearing Drawer Rails	Splice Management	Includes Splice Trays, Heatshrink Sleeves & Cable Glands
Cable Entry Ports	4 Rear Cable Entry Ports with Rubber Grommets	Surface Finish	Electrostatic Matte Black Powder Coating

MECHANICAL CHARACTERISTICS

Drawer Extension	Full 100% Extension Sliding Drawer
Adapter Ceramic Sleeve	Zirconia Ceramic Alignment Sleeve ($\leq 0.2\text{dB}$ Loss)
Mounting Dimensions	Standard 19-Inch EIA Rack Width

SPLICE CAPACITY & ACCESSORIES

Splice Trays	Stackable ABS Trays (24 Fibers per tray)
Accessories Included	Splice Sleeves, PG Glands, Cable Ties, M6 Screws
Operating Temp.	-40°C to +80°C

**COMPLIANCE & STANDARDS**

- EIA/ECA-310-E Standard 19" Specifications
- TIA/EIA-568.3-D & ISO/IEC 11801
- Telcordia GR-326-CORE Compliant Adapters
- RoHS & REACH Compliant

ORDERING INFORMATION

PART NUMBER	DESCRIPTION	RACK SIZE
LXFPRLC06	Logx 6 Port Optic Fiber Patch Panel, LC Duplex SM Loaded, with Rail & Splice Tray, 1U	1U / 6 Port (12F)
LXFPRLC12	Logx 12 Port Optic Fiber Patch Panel, LC Duplex SM Loaded, with Rail & Splice Tray, 1U	1U / 12 Port (24F)
LXFPRLC24	Logx 24 Port Optic Fiber Patch Panel, LC Duplex SM Loaded, with Rail & Splice Tray, 1U	1U / 24 Port (48F)
LXFPRLC48	Logx 48 Port Optic Fiber Patch Panel, LC Duplex SM Loaded, with Rail & Splice Tray, 2U	2U / 48 Port (96F)