

**LXPC6UUPVG0.5 | LOGX CAT6 UTP, 4PX28AWG+CROSS+PVC+RJ45, GOLD PLATED PINS, PASS FLUKE TEST**

0.5 METER

**DESCRIPTION**

LOGX CAT 6 UTP patch cords are specifically manufactured with 4-pair 28AWG stranded copper conductors, an integrated central cross divider (+cross) for optimum pair separation and crosstalk suppression, high-durability PVC jacket, and RJ45 plugs with gold-plated pins. Factory certified to 100% Pass Fluke Test, ensuring superior network transmission performance and signal integrity.

**FEATURES & BENEFITS**

- **100% Pass Fluke Test** guaranteed electrical performance
- **4PX28AWG Stranded Conductors** for high flexibility and slim profile
- **Central Cross Separator (+cross)** to optimize pair isolation & NEXT
- **RJ45 Connectors with Gold Plated Pins** for superior contact
- **Durable PVC Outer Jacket** (Grey)
- Slim, compact design ideal for high-density data centers and server racks
- Molded snagless strain-relief boot for latch and cable protection
- $\geq 1000$  Mating / Insertion Cycles Durability

**TYPICAL APPLICATIONS**

- 1000BASE-T Gigabit Ethernet / 100BASE-TX Fast Ethernet
- High-Density Server Racks & Switch Patching
- Power over Ethernet (PoE / PoE+ / PoE++ IEEE 802.3af/at/bt)
- VoIP Telephony, CCTV IP Cameras, and Digital High-Speed Data

**COMPLIANCE & STANDARDS**

- ANSI/TIA 568.2-D Category 6
- ISO/IEC 11801 Class E
- IEC 61156-6 | EN 50173-1 & EN 50399
- 100% Pass Fluke Test Certified
- RoHS & REACH Compliant

**COLOR CODING**

|        |                       |
|--------|-----------------------|
| Pair 1 | White-Blue / Blue     |
| Pair 2 | White-Orange / Orange |
| Pair 3 | White-Green / Green   |
| Pair 4 | White-Brown / Brown   |

**SPECIFICATIONS & CONSTRUCTION**

|                     |                          |                   |                                 |
|---------------------|--------------------------|-------------------|---------------------------------|
| Product Model       | LOGX Category 6 (CAT6)   | Central Separator | PE Cross Separator (+cross)     |
| Shielding Type      | UTP (Unshielded)         | Connector Type    | RJ45 (8P8C)                     |
| Conductor Structure | 4PX28AWG Stranded Copper | Contacts Plating  | Gold Plated Pins                |
| Jacket Sheath       | PVC (Polyvinyl Chloride) | Quality Standard  | Pass Fluke Test (100%)          |
| Jacket Color        | Grey (G)                 | Assembly Type     | Injection Molding Snagless Boot |
| Outer Diameter      | 4.8 $\pm$ 0.2 mm         | Durability        | $\geq 1000$ Insertion Cycles    |
| Installation Temp.  | 0°C ~ +50°C              | Operating Temp.   | -20°C ~ +60°C                   |

**MECHANICAL CHARACTERISTICS**

|                         |                             |
|-------------------------|-----------------------------|
| Min. Tension            | $\geq 100$ N                |
| Conductor Elongation    | $\geq 15\%$                 |
| Jacket Tensile Strength | $\geq 10$ MPa               |
| Jacket Elongation       | $\geq 125\%$                |
| Min. Bend Radius        | 4 $\times$ Overall Diameter |

**ELECTRICAL CHARACTERISTICS**

|                       |                                        |
|-----------------------|----------------------------------------|
| Quality Test          | 100% Pass Fluke Test                   |
| DC Resistance Unbal.  | $\leq 2.0\%$                           |
| Dielectric Strength   | 1.0 kV, 1 Min (No breakdown)           |
| Delay Skew / Delay    | $\leq 45$ ns/100m   $\leq 555$ ns/100m |
| Insulation Resistance | $\geq 5000$ M $\Omega$ -km             |

**ORDERING INFORMATION**

| PART NUMBER    | DESCRIPTION                                                                      | LENGTH |
|----------------|----------------------------------------------------------------------------------|--------|
| LXPC6UUPVG0.25 | Logx 0.25M cat6, UTP, 4PX28AWG+cross+PVC+RJ45, gold plated pins, pass fluke test | 0.25M  |
| LXPC6UUPVG0.5  | Logx 0.5M cat6, UTP, 4PX28AWG+cross+PVC+RJ45, gold plated pins, pass fluke test  | 0.5M   |
| LXPC6UUPVG1    | Logx 1M cat6, UTP, 4PX28AWG+cross+PVC+RJ45, gold plated pins, pass fluke test    | 1M     |
| LXPC6UUPVG3    | Logx 3M cat6, UTP, 4PX28AWG+cross+PVC+RJ45, gold plated pins, pass fluke test    | 3M     |
| LXPC6UUPVG5    | Logx 5M cat6, UTP, 4PX28AWG+cross+PVC+RJ45, gold plated pins, pass fluke test    | 5M     |
| LXPC6UUPVG10   | Logx 10M cat6, UTP, 4PX28AWG+cross+PVC+RJ45, gold plated pins, pass fluke test   | 10M    |