

LXPC6UUPVG5 | LOGX CAT6 UTP, 4PX28AWG+CROSS+PVC+RJ45, GOLD PLATED PINS, PASS FLUKE TEST

5 METERS

DESCRIPTION

LOGX CAT 6 UTP patch cords are specifically manufactured with 4-pair 28AWG stranded copper conductors, an integrated central cross divider (+cross) for optimum pair separation and crosstalk suppression, high-durability PVC jacket, and RJ45 plugs with gold-plated pins. Factory certified to 100% Pass Fluke Test, ensuring superior network transmission performance and signal integrity.

FEATURES & BENEFITS

- **100% Pass Fluke Test** guaranteed electrical performance
- **4PX28AWG Stranded Conductors** for high flexibility and slim profile
- **Central Cross Separator (+cross)** to optimize pair isolation & NEXT
- **RJ45 Connectors with Gold Plated Pins** for superior contact
- **Durable PVC Outer Jacket** (Grey)
- Slim, compact design ideal for high-density data centers and server racks
- Molded snagless strain-relief boot for latch and cable protection
- ≥ 1000 Mating / Insertion Cycles Durability

TYPICAL APPLICATIONS

- 1000BASE-T Gigabit Ethernet / 100BASE-TX Fast Ethernet
- High-Density Server Racks & Switch Patching
- Power over Ethernet (PoE / PoE+ / PoE++ IEEE 802.3af/at/bt)
- VoIP Telephony, CCTV IP Cameras, and Digital High-Speed Data



COMPLIANCE & STANDARDS

- ANSI/TIA 568.2-D Category 6
- ISO/IEC 11801 Class E
- IEC 61156-6 | EN 50173-1 & EN 50399
- 100% Pass Fluke Test Certified
- RoHS & REACH Compliant

COLOR CODING

Pair 1	White-Blue / Blue
Pair 2	White-Orange / Orange
Pair 3	White-Green / Green
Pair 4	White-Brown / Brown

SPECIFICATIONS & CONSTRUCTION

Product Model	LOGX Category 6 (CAT6)	Central Separator	PE Cross Separator (+cross)
Shielding Type	UTP (Unshielded)	Connector Type	RJ45 (8P8C)
Conductor Structure	4PX28AWG Stranded Copper	Contacts Plating	Gold Plated Pins
Jacket Sheath	PVC (Polyvinyl Chloride)	Quality Standard	Pass Fluke Test (100%)
Jacket Color	Grey (G)	Assembly Type	Injection Molding Snagless Boot
Outer Diameter	4.8 $\pm$ 0.2 mm	Durability	≥ 1000 Insertion Cycles
Installation Temp.	0°C ~ +50°C	Operating Temp.	-20°C ~ +60°C

MECHANICAL CHARACTERISTICS

Min. Tension	≥ 100 N
Conductor Elongation	$\geq 15\%$
Jacket Tensile Strength	≥ 10 MPa
Jacket Elongation	$\geq 125\%$
Min. Bend Radius	4 $\times$ Overall Diameter

ELECTRICAL CHARACTERISTICS

Quality Test	100% Pass Fluke Test
DC Resistance Unbal.	$\leq 2.0\%$
Dielectric Strength	1.0 kV, 1 Min (No breakdown)
Delay Skew / Delay	≤ 45 ns/100m ≤ 555 ns/100m
Insulation Resistance	≥ 5000 M Ω -km

ORDERING INFORMATION

PART NUMBER	DESCRIPTION	LENGTH
LXPC6UUPVG0.25	Logx 0.25M cat6, UTP, 4PX28AWG+cross+PVC+RJ45, gold plated pins, pass fluke test	0.25M
LXPC6UUPVG0.5	Logx 0.5M cat6, UTP, 4PX28AWG+cross+PVC+RJ45, gold plated pins, pass fluke test	0.5M
LXPC6UUPVG1	Logx 1M cat6, UTP, 4PX28AWG+cross+PVC+RJ45, gold plated pins, pass fluke test	1M
LXPC6UUPVG3	Logx 3M cat6, UTP, 4PX28AWG+cross+PVC+RJ45, gold plated pins, pass fluke test	3M
LXPC6UUPVG5	Logx 5M cat6, UTP, 4PX28AWG+cross+PVC+RJ45, gold plated pins, pass fluke test	5M
LXPC6UUPVG10	Logx 10M cat6, UTP, 4PX28AWG+cross+PVC+RJ45, gold plated pins, pass fluke test	10M