

LOGX FIBER OPTIC PATCH CORD LC-LC DUPLEX

LC-LC UPC OM3 Duplex Patch Cord, 3 m

LOGX LC-LC UPC SM & OM3 DUPLEX 2.0MM FIBER PATCH CORD

PART NUMBER

LXFCLCLCDUS303

DESCRIPTION

LOGX LC-LC Duplex Fiber Optic Patch Cords are factory-terminated with ultra-precision zirconia ceramic ferrules for low insertion loss and high return loss. Available in Single Mode (OS2 Yellow) and 10G Multimode (OM3 Aqua) across all standard lengths from 1M to 100M for data center and optical network connections.

FEATURES & BENEFITS

- 100% Factory Interferometer & Insertion Loss Tested for guaranteed performance
- Ultra-Precision Zirconia Ceramic Ferrules (Insertion Loss  $\leq 0.2$ dB)
- Available in Single Mode OS2 (Yellow) and 10G Multimode OM3 (Aqua)
- 2.0mm Duplex Zipcord Construction with flexible PVC outer jacket
- Complete range of pre-terminated lengths: 1M, 3M, 5M, 10M, 15M, 20M, 25M, 30M, 40M, 50M, 70M, 100M
- Includes protective dust caps and individual test report bag

TYPICAL APPLICATIONS

- Data Center Fiber SAN, Switches, SFP/SFP+ Transceivers, and Patch Panels
- High-Speed 10G/40G/100G Telecom Backbone & FTTx Infrastructure
- Broadband Optical Transmission and Industrial Automation



COMPLIANCE & STANDARDS

- ✓ TIA/EIA-568.3-D & ISO/IEC 11801
- ✓ Telcordia GR-326-CORE / IEC 61754-20
- ✓ UL 94V-0 & RoHS Compliant

SPECIFICATIONS & TECHNICAL PARAMETERS

|                |                                                 |                  |                                                                  |
|----------------|-------------------------------------------------|------------------|------------------------------------------------------------------|
| Connector Type | LC/UPC to LC/UPC Duplex                         | Fiber Types      | Single Mode 9/125 $\mu$ m (OS2) / Multimode 50/125 $\mu$ m (OM3) |
| Outer Diameter | Duplex 2.0 mm (Zipcord Cable)                   | Jacket Material  | Durable PVC / Flame-Retardant Sheath                             |
| Jacket Color   | Yellow (Single Mode OS2) / Aqua (Multimode OM3) | Ferrule Material | High-Precision Zirconia Ceramic Ferrule                          |
| Insertion Loss | $\leq 0.20$ dB (Typical $\leq 0.15$ dB)         | Return Loss      | $\geq 50$ dB (UPC SM)   $\geq 35$ dB (OM3)                       |

OPTICAL & MECHANICAL SPECS

|                |                                                 |
|----------------|-------------------------------------------------|
| Insertion Loss | $\leq 0.2$ dB (1310/1550nm SM   850/1300nm OM3) |
| Durability     | 1000 Mating Cycles ( $\Delta$ IL $\leq 0.2$ dB) |
| Repeatability  | $\leq 0.1$ dB   Tensile Strength $\geq 100$ N   |

ENVIRONMENTAL SPECIFICATIONS

|                     |                                     |
|---------------------|-------------------------------------|
| Operating Temp.     | -40°C to +75°C                      |
| Storage Temp.       | -45°C to +85°C                      |
| Standard Compliance | Telcordia GR-326-CORE, IEC 61754-20 |

ORDERING INFORMATION

| PART NUMBER     | LENGTH                          |
|-----------------|---------------------------------|
| LXFCLCLCDUS201  | 1M · Single Mode OS2 (Yellow)   |
| LXFCLCLCDUS203  | 3M · Single Mode OS2 (Yellow)   |
| LXFCLCLCDUS205  | 5M · Single Mode OS2 (Yellow)   |
| LXFCLCLCDUS210  | 10M · Single Mode OS2 (Yellow)  |
| LXFCLCLCDUS215  | 15M · Single Mode OS2 (Yellow)  |
| LXFCLCLCDUS220  | 20M · Single Mode OS2 (Yellow)  |
| LXFCLCLCDUS225  | 25M · Single Mode OS2 (Yellow)  |
| LXFCLCLCDUS230  | 30M · Single Mode OS2 (Yellow)  |
| LXFCLCLCDUS240  | 40M · Single Mode OS2 (Yellow)  |
| LXFCLCLCDUS250  | 50M · Single Mode OS2 (Yellow)  |
| LXFCLCLCDUS270  | 70M · Single Mode OS2 (Yellow)  |
| LXFCLCLCDUS2100 | 100M · Single Mode OS2 (Yellow) |

| PART NUMBER     | LENGTH                      |
|-----------------|-----------------------------|
| LXFCLCLCDUS301  | 1M · Multimode OM3 (Aqua)   |
| LXFCLCLCDUS303  | 3M · Multimode OM3 (Aqua)   |
| LXFCLCLCDUS305  | 5M · Multimode OM3 (Aqua)   |
| LXFCLCLCDUS310  | 10M · Multimode OM3 (Aqua)  |
| LXFCLCLCDUS315  | 15M · Multimode OM3 (Aqua)  |
| LXFCLCLCDUS320  | 20M · Multimode OM3 (Aqua)  |
| LXFCLCLCDUS325  | 25M · Multimode OM3 (Aqua)  |
| LXFCLCLCDUS330  | 30M · Multimode OM3 (Aqua)  |
| LXFCLCLCDUS340  | 40M · Multimode OM3 (Aqua)  |
| LXFCLCLCDUS350  | 50M · Multimode OM3 (Aqua)  |
| LXFCLCLCDUS370  | 70M · Multimode OM3 (Aqua)  |
| LXFCLCLCDUS3100 | 100M · Multimode OM3 (Aqua) |