

LOGX FIBER OPTIC PATCH CORD LC-LC DUPLEX

LC-LC UPC OM3 Duplex Patch Cord, 5 m

LOGX LC-LC UPC SM & OM3 DUPLEX 2.0MM FIBER PATCH CORD

PART NUMBER

LXFCLCLCDUS305

DESCRIPTION

LOGX LC-LC Duplex Fiber Optic Patch Cords are factory-terminated with ultra-precision zirconia ceramic ferrules for low insertion loss and high return loss. Available in Single Mode (OS2 Yellow) and 10G Multimode (OM3 Aqua) across all standard lengths from 1M to 100M for data center and optical network connections.

FEATURES & BENEFITS

- 100% Factory Interferometer & Insertion Loss Tested for guaranteed performance
- Ultra-Precision Zirconia Ceramic Ferrules (Insertion Loss ≤ 0.2dB)
- Available in Single Mode OS2 (Yellow) and 10G Multimode OM3 (Aqua)
- 2.0mm Duplex Zipcord Construction with flexible PVC outer jacket
- Complete range of pre-terminated lengths: 1M, 3M, 5M, 10M, 15M, 20M, 25M, 30M, 40M, 50M, 70M, 100M
- Includes protective dust caps and individual test report bag

TYPICAL APPLICATIONS

- Data Center Fiber SAN, Switches, SFP/SFP+ Transceivers, and Patch Panels
- High-Speed 10G/40G/100G Telecom Backbone & FTTx Infrastructure
- Broadband Optical Transmission and Industrial Automation



COMPLIANCE & STANDARDS

- ✓ TIA/EIA-568.3-D & ISO/IEC 11801
- ✓ Telcordia GR-326-CORE / IEC 61754-20
- ✓ UL 94V-0 & RoHS Compliant

SPECIFICATIONS & TECHNICAL PARAMETERS

Connector Type	LC/UPC to LC/UPC Duplex	Fiber Types	Single Mode 9/125µm (OS2) / Multimode 50/125µm (OM3)
Outer Diameter	Duplex 2.0 mm (Zipcord Cable)	Jacket Material	Durable PVC / Flame-Retardant Sheath
Jacket Color	Yellow (Single Mode OS2) / Aqua (Multimode OM3)	Ferrule Material	High-Precision Zirconia Ceramic Ferrule
Insertion Loss	≤ 0.20 dB (Typical ≤ 0.15 dB)	Return Loss	≥ 50 dB (UPC SM) ≥ 35 dB (OM3)

OPTICAL & MECHANICAL SPECS

Insertion Loss	≤ 0.2 dB (1310/1550nm SM 850/1300nm OM3)
Durability	1000 Mating Cycles (ΔIL ≤ 0.2 dB)
Repeatability	≤ 0.1 dB Tensile Strength ≥ 100 N

ENVIRONMENTAL SPECIFICATIONS

Operating Temp.	-40°C to +75°C
Storage Temp.	-45°C to +85°C
Standard Compliance	Telcordia GR-326-CORE, IEC 61754-20

ORDERING INFORMATION

PART NUMBER	LENGTH
LXFCLCLCDUS201	1M · Single Mode OS2 (Yellow)
LXFCLCLCDUS203	3M · Single Mode OS2 (Yellow)
LXFCLCLCDUS205	5M · Single Mode OS2 (Yellow)
LXFCLCLCDUS210	10M · Single Mode OS2 (Yellow)
LXFCLCLCDUS215	15M · Single Mode OS2 (Yellow)
LXFCLCLCDUS220	20M · Single Mode OS2 (Yellow)
LXFCLCLCDUS225	25M · Single Mode OS2 (Yellow)
LXFCLCLCDUS230	30M · Single Mode OS2 (Yellow)
LXFCLCLCDUS240	40M · Single Mode OS2 (Yellow)
LXFCLCLCDUS250	50M · Single Mode OS2 (Yellow)
LXFCLCLCDUS270	70M · Single Mode OS2 (Yellow)
LXFCLCLCDUS2100	100M · Single Mode OS2 (Yellow)

PART NUMBER	LENGTH
LXFCLCLCDUS301	1M · Multimode OM3 (Aqua)
LXFCLCLCDUS303	3M · Multimode OM3 (Aqua)
LXFCLCLCDUS305	5M · Multimode OM3 (Aqua)
LXFCLCLCDUS310	10M · Multimode OM3 (Aqua)
LXFCLCLCDUS315	15M · Multimode OM3 (Aqua)
LXFCLCLCDUS320	20M · Multimode OM3 (Aqua)
LXFCLCLCDUS325	25M · Multimode OM3 (Aqua)
LXFCLCLCDUS330	30M · Multimode OM3 (Aqua)
LXFCLCLCDUS340	40M · Multimode OM3 (Aqua)
LXFCLCLCDUS350	50M · Multimode OM3 (Aqua)
LXFCLCLCDUS370	70M · Multimode OM3 (Aqua)
LXFCLCLCDUS3100	100M · Multimode OM3 (Aqua)