

LOGX 19 INCH SLIDING FIBER PATCH PANEL

24 Port LC Duplex Fiber Patch Panel, 1U

LOGX 6, 12, 24 & 48 PORT LC DUPLEX LOADED FIBER PATCH PANEL

PART NUMBER
LXFPRDLC24

DESCRIPTION

LOGX Sliding Rail Fiber Optic Patch Panels provide high-density fiber patching and splicing in standard 19-inch equipment racks. Pre-loaded with high-precision LC/UPC duplex adapters, smooth telescopic ball-bearing sliding rails for easy front maintenance, and complete internal splice management trays.

FEATURES & BENEFITS

- Pre-Loaded with LC/UPC Duplex Singlemode Adapters with zirconia sleeves
- Smooth Telescopic Ball-Bearing Sliding Drawer for easy front access without removing unit
- Complete Splice Kit Included (Splice trays, heatshrink holders, and protective sleeves)
- 4 Rear Cable Entry Ports equipped with cable clamps and rubber protection glands
- Constructed from 1.2mm electro-galvanized cold-rolled steel with black powder finish
- Available in 1U (6, 12, 24 Port) and 2U (48 Port) configurations

TYPICAL APPLICATIONS

- Data Center Fiber Density Patching & Main Cross-Connect (MC)
- Telecom Central Offices, FTTx Core Nodes, and Enterprise Racks
- High-Speed 10G/40G/100G Optical Backbone Distribution



COMPLIANCE & STANDARDS

- ✓ EIA/ECA-310-E Standard 19" Specifications
- ✓ TIA/EIA-568.3-D & ISO/IEC 11801
- ✓ Telcordia GR-326-CORE Compliant Adapters
- ✓ RoHS & REACH Compliant

SPECIFICATIONS & TECHNICAL PARAMETERS

Product Standard	LOGX 19" Sliding Rail Fiber Patch Panel	Adapter Type	Loaded with LC/UPC Duplex Singlemode Adapters (Blue)
Capacities Available	6 Port (1U) / 12 Port (1U) / 24 Port (1U) / 48 Port (2U)	Chassis Material	1.2mm High-Strength Cold-Rolled Steel (SPCC)
Sliding Mechanism	Smooth Telescopic Ball-Bearing Drawer Rails	Splice Management	Includes Splice Trays, Heatshrink Sleeves & Cable Glands
Cable Entry Ports	4 Rear Cable Entry Ports with Rubber Grommets	Surface Finish	Electrostatic Matte Black Powder Coating

MECHANICAL CHARACTERISTICS

Drawer Extension	Full 100% Extension Sliding Drawer
Adapter Ceramic Sleeve	Zirconia Ceramic Alignment Sleeve (≤ 0.2dB Loss)
Mounting Dimensions	Standard 19-Inch EIA Rack Width

SPLICE CAPACITY & ACCESSORIES

Splice Trays	Stackable ABS Trays (24 Fibers per tray)
Accessories Included	Splice Sleeves, PG Glands, Cable Ties, M6 Screws
Operating Temp.	-40°C to +80°C

ORDERING INFORMATION

PART NUMBER	DESCRIPTION	RACK SIZE
LXFPRDLC12	12 Port LC Duplex Fiber Patch Panel, 1U	12 Port (1U)
LXFPRDLC24	24 Port LC Duplex Fiber Patch Panel, 1U	24 Port (1U)
LXFPRDLC48	48 Port LC Duplex Fiber Patch Panel, 2U	48 Port (2U)