

LOGX FIBER OPTIC PIGTAIL LC/UPC SIMPLEX

LC/UPC Single-Mode Pigtail, 2 m

LOGX 1.5M & 2M 0.9MM LC/UPC SM & OM3 FIBER PIGTAIL

PART NUMBER

LXFTLCSUS22

DESCRIPTION

LOGX LC/UPC 0.9mm Fiber Optic Pigtails are precision factory-terminated fiber ends designed for fusion splicing inside fiber patch panels, wall-mount enclosures, and splice trays. Features high-purity zirconia ferrules, low insertion loss, and easy-strip 0.9mm tight buffer coating.

FEATURES & BENEFITS

- 0.9mm Easy-Strip Tight Buffer for fast and clean fusion splicing
- Precision Factory Polished LC/UPC Ferrule with  $\leq 0.2\text{dB}$  Insertion Loss
- Available in Single Mode (OS2) and 10G Multimode (OM3) in 1.5M and 2.0M lengths
- 100% Optically Tested for IL, RL, and end-face geometry
- High mechanical durability and environmental stability
- Individually packaged with protective connector dust cap

TYPICAL APPLICATIONS

- Fusion Splicing inside 19-Inch Fiber Patch Panels and Optical Distribution Frames (ODF)
- FTTH Terminal Boxes and Wall-Mount Optical Enclosures
- Industrial Automation & Telecommunication Network Splicing



COMPLIANCE & STANDARDS

- ✓ TIA/EIA-568.3-D & ISO/IEC 11801
- ✓ Telcordia GR-326-CORE / IEC 61754-20
- ✓ RoHS & REACH Compliant

SPECIFICATIONS & TECHNICAL PARAMETERS

|                   |                               |                  |                                                                              |
|-------------------|-------------------------------|------------------|------------------------------------------------------------------------------|
| Connector Type    | LC/UPC Simplex (0.9mm Buffer) | Fiber Types      | Single Mode 9/125 $\mu\text{m}$ (OS2) / Multimode 50/125 $\mu\text{m}$ (OM3) |
| Buffer Diameter   | 0.9 mm Tight Buffer           | Jacket Material  | PVC (OFNR)                                                                   |
| Lengths Available | 1.5 Meters / 2.0 Meters       | Ferrule Material | Precision Zirconia Ceramic                                                   |
| Insertion Loss    | $\leq 0.3\text{ dB}$          | Return Loss      | $\geq 50\text{ dB}$ (Single Mode UPC)   $\geq 30\text{ dB}$ (OM3)            |

OPTICAL CHARACTERISTICS

|                      |                                                          |
|----------------------|----------------------------------------------------------|
| Insertion Loss       | $\leq 0.3\text{ dB}$                                     |
| Return Loss          | $\geq 50\text{ dB}$ (SM UPC)   $\geq 30\text{ dB}$ (OM3) |
| Operating Wavelength | 1310 / 1550 nm (SM)   850 / 1300 nm (OM3)                |

ENVIRONMENTAL SPECIFICATIONS

|                     |                                     |
|---------------------|-------------------------------------|
| Operating Temp.     | -20°C to +70°C                      |
| Jacket Material     | PVC (OFNR)                          |
| Standard Compliance | Telcordia GR-326-CORE, IEC 61754-20 |

ORDERING INFORMATION

| PART NUMBER   | DESCRIPTION                       | LENGTH                 |
|---------------|-----------------------------------|------------------------|
| LXFTLCSUS21.5 | LC/UPC Single-Mode Pigtail, 1.5 m | 1.5M · Single Mode OS2 |
| LXFTLCSUS22   | LC/UPC Single-Mode Pigtail, 2 m   | 2.0M · Single Mode OS2 |
| LXFTLCSUM31.5 | LC/UPC OM3 Pigtail, 1.5 m         | 1.5M · Multimode OM3   |
| LXFTLCSUM32   | LC/UPC OM3 Pigtail, 2 m           | 2.0M · Multimode OM3   |