



Copper Interface	1 × RJ45 Port (Auto-MDI/MDI-X, Auto-Negotiation)	Fiber Interface	1 × Open SFP / SFP+ Slot (Universal Compatibility)
Chassis Material	Durable Metal Casing for Heat Dissipation	LED Indicators	PWR, 1000M/10G, Link/Act, FX Link/Act, TP Link/Act
Power Input	DC 5V / 1A (1G) DC 12V / 1A (10G), Adapter Included	Dimensions (W×D×H)	70 × 94 × 26 mm (1G) 94 × 70 × 26 mm (10G)

TECHNICAL SPECIFICATIONS

Forwarding Mode Store-and-Forward Switching Architecture
Transmission Dist. 1G: 550m MMF / 120km SMF | 10G: 300m MMF / 80km SMF
Power Consumption < 3 Watts (1G) | < 6 Watts (10G)

ENVIRONMENTAL SPECIFICATIONS

Operating Temp. 0°C to +50°C | Storage: -20°C to +70°C
Operating Humidity 5% to 90% Non-condensing
Certifications CE, FCC Class A, RoHS

Ordering information

Part number	Description	Speed
LGX-MC1000GSFP	1G SFP Media Converter	1G SFP
LGX-MC10GSFP+	10G SFP+ Media Converter	10G SFP+

© LOGX NETWORK · Specifications subject to change without notice.logxnetwork.com/en/products/1g-sfp-media-converter-lgx-mc1000gsfp · sales@logxnetwork.com

LOGXNETWORK

Structured cabling, fiber optic distribution and rack infrastructure — supplied as one connected range.

Products

- [Copper cabling](#)
- [Fiber optic](#)
- [Racks & accessories](#)
- [Datasheets](#)

Contact

- [Request a quotation](#)
- sales@logxnetwork.com
- [About](#)
- [Company profile](#)

Offices

Head office LOGX NETWORKS LTD. 71-75 Shelton Street, Covent Garden, London, United Kingdom
Middle East distributor Networks Sea Company Olaya, Riyadh, Saudi Arabia

