

LOGXNETWORK

Technical datasheet Rev. 2026-09

LOGX GIGABIT & 10G SFP MEDIA CONVERTER

10G SFP+ Media Converter

LOGX 1G & 10G SFP PORT FIBER TO ETHERNET MEDIA CONVERTER

Part number **LGX-MC10GSFP+**

Description

LOGX SFP Media Converters transparently convert copper Ethernet signals (RJ45) to fiber optic signals via standard SFP/SFP+ slots. Designed in a rugged metal enclosure with low power consumption, auto-negotiation, and Link Fault Pass-Through (LFP) for reliable enterprise network extension.

Features & benefits

- **Converts 10/100/1000M or 10G Copper** to High-Speed Optical Fiber
- **Open Standard SFP / SFP+ Slot** compatible with all MSA-compliant transceivers
- **Auto-Negotiation & Auto-MDI/MDIX** on RJ45 port eliminates crossover cables
- **Link Fault Pass-Through (LFP)** enables instant fault alerting on remote connections
- Rugged, compact metal chassis engineered for optimal heat dissipation and long MTBF
- Comprehensive LED status indicators for power, fiber link, copper activity, and speed

Typical applications

- Extending Local Area Networks (LAN) over Long-Distance Fiber Optic Backbones
- Connecting Remote IP CCTV Cameras and Wi-Fi Access Points to Central Core Switches
- Data Center Server Interconnections (10GBASE-T to 10G SFP+)

Compliance & standards

- IEEE 802.3ab (1000BASE-T), IEEE 802.3z (1000BASE-X)
- IEEE 802.3an (10GBASE-T), IEEE 802.3ae (10GBASE-SR/LR)
- CE, FCC Class A, RoHS Compliant

SPECIFICATIONS & TECHNICAL PARAMETERS

Product	LOGX Industrial/Enterprise Media	Models	1G SFP (10/100/1000M) / 10G SFP+
Standard	Converter	Available	(10GBASE-T to 10G SFP+)

Copper Interface	1 × RJ45 Port (Auto-MDI/MDI-X, Auto-Negotiation)	Fiber Interface	1 × Open SFP / SFP+ Slot (Universal Compatibility)
Chassis Material	Durable Metal Casing for Heat Dissipation	LED Indicators	PWR, 1000M/10G, Link/Act, FX Link/Act, TP Link/Act
Power Input	DC 5V / 1A (1G) DC 12V / 1A (10G), Adapter Included	Dimensions (W×D×H)	70 × 94 × 26 mm (1G) 94 × 70 × 26 mm (10G)

TECHNICAL SPECIFICATIONS

Forwarding Mode Store-and-Forward Switching Architecture
Transmission Dist. 1G: 550m MMF / 120km SMF | 10G: 300m MMF / 80km SMF
Power Consumption < 3 Watts (1G) | < 6 Watts (10G)

ENVIRONMENTAL SPECIFICATIONS

Operating Temp. 0°C to +50°C | Storage: -20°C to +70°C
Operating Humidity 5% to 90% Non-condensing
Certifications CE, FCC Class A, RoHS

Ordering information

Part number	Description	Speed
LGX-MC1000GSFP	1G SFP Media Converter	1G SFP
LGX-MC10GSFP+	10G SFP+ Media Converter	10G SFP+

© LOGX NETWORK · Specifications subject to change without notice.logxnetwork.com/en/products/10g-sfp-media-converter-lgx-mc10gsfp · sales@logxnetwork.com

LOGXNETWORK

Structured cabling, fiber optic distribution and rack infrastructure — supplied as one connected range.

Products

- [Copper cabling](#)
- [Fiber optic](#)
- [Racks & accessories](#)
- [Datasheets](#)

Contact

- [Request a quotation](#)
- sales@logxnetwork.com
- [About](#)
- [Company profile](#)

Offices

Head office LOGX NETWORKS LTD. 71-75 Shelton Street, Covent Garden, London, United Kingdom
Middle East distributor Networks Sea Company Olaya, Riyadh, Saudi Arabia

