



Input Plug Type	UK BS 1363 13A Fused Plug (3-Pin)	Power Cable	3 × 1.5mm ² Heavy-Duty Power Cord (2.0 Meters)
Chassis Material	Heavy-Duty Extruded Aluminum Alloy (Black)	Control & Protection	Master ON/OFF Switch with Protective Cover
Electrical Rating	250V AC, 50/60Hz, 13A Max (3250W Max Capacity)	Mounting Format	1U 19-Inch Horizontal Rack Mount

ELECTRICAL SPECIFICATIONS

Nominal Voltage	250V AC 50/60Hz
Max. Current / Load	13 Amps 3250 Watts Maximum Load
Safety Switch	Illuminated Master Switch with Safety Guard

SAFETY & STANDARDS

Socket Compliance	BS 1363 / British 3-Pin Standard Sockets
Grounding	External M5 Earthing Lug for Rack Grounding
Certifications	CE, RoHS, BS 5733 Safety Certified

Ordering information

Part number	Description	Format
LGX-PDU6-UK	6-Way UK Socket PDU 1U / 6 Way UK	
© LOGX NETWORK · Specifications subject to change without notice. logxnetwork.com/en/products/6-way-uk-socket-pdu-lgx-pdu6-uk · sales@logxnetwork.com		

LOGXNETWORK

Structured cabling, fiber optic distribution and rack infrastructure — supplied as one connected range.

Products

- [Copper cabling](#)
- [Fiber optic](#)
- [Racks & accessories](#)
- [Datasheets](#)

Contact

- [Request a quotation](#)
- sales@logxnetwork.com
- [About](#)
- [Company profile](#)

Offices

Head office*LOGX NETWORKS LTD.71-75 Shelton Street, Covent Garden, London, United Kingdom*
Middle East distributor*Networks Sea CompanyOlaya, Riyadh, Saudi Arabia*
 © 2026 LOGX NETWORK · Specifications subject to change without notice.

[PrivacyTerms](#)