

LOGX 86 TYPE GLOSSY FACEPLATE

86 Type Faceplate, 1 Port

LOGX F1007 1 PORT & 2 PORTS GLOSSY FACEPLATE (86×86MM)

PART NUMBER
LXA10

DESCRIPTION

LOGX F1007 86 Type British Standard Faceplates are designed for flush-mount and surface-mount telecom outlet termination. Manufactured in standard 86×86mm dimensions with high-gloss white ABS plastic, integrated spring dust shutters, transparent labeling windows, and strictly available in 1 Port (LXA10) and 2 Ports (LXA20) configurations.

FEATURES & BENEFITS

- Standard 86×86mm British Format with 60.3mm mounting pitch
- Configurations: Strictly 1 Port (LXA10) and 2 Ports (LXA20)
- Spring-Loaded Dust Shutter prevents dust ingress and contact damage
- High-Gloss ABS Flame-Retardant Material (UL 94V-0 compliant)
- Clear Labeling Window with interchangeable icon inserts
- Compatible with all standard CAT6 & CAT6A RJ45 Keystone Jacks
- Includes standard M3.5 mounting screws and screw-hole caps

TYPICAL APPLICATIONS

- Work Area Outlet Wall Termination in Commercial & Residential Projects
- Single-Port and Dual-Port High-Speed Data / Voice Outlets
- Compatible with Standard 86-Type Wall Mounting Back Boxes



COMPLIANCE & STANDARDS

- ✓ BS 5733 / British Standard 86 Format
- ✓ ANSI/TIA-568.2-D & ISO/IEC 11801
- ✓ UL 94V-0 Fire Safety Standard
- ✓ RoHS & REACH Compliant

SPECIFICATIONS & TECHNICAL PARAMETERS

Product Series	LOGX F1007 British Standard Faceplate	Dimensions	86 mm × 86 mm (Standard 86 Type)
Material	High-Impact Flame-Retardant ABS (UL 94V-0)	Mounting Pitch	60.3 mm (Standard British Wall Box)
Surface Finish	Glossy White with Protective Dust Shutter	Available Ports	1 Port (LXA10) & 2 Ports (LXA20) Only
Port Compatibility	Standard CAT6 & CAT6A Keystone Jacks	Accessories	Mounting Screws (M3.5) & Icon Inserts Included

PHYSICAL CHARACTERISTICS

Flame Resistance	UL 94V-0 Fire-Retardant ABS Plastic
Dust Protection	Spring-Loaded Auto-Close Dust Shutter
Durability	≥ 500 Insertions & Removals

ENVIRONMENTAL SPECIFICATIONS

Storage Temp.	-40°C to +70°C
Operating Temp.	-10°C to +60°C
Relative Humidity	≤ 93% (Non-condensing)

ORDERING INFORMATION

PART NUMBER	DESCRIPTION	PORT COUNT
LXA10	86 Type Faceplate, 1 Port	1 Port
LXA20	86 Type Faceplate, 2 Port	2 Ports