

LOGX CAT 6A U/UTP SOLID LAN CABLE

CAT6A U/UTP LAN Cable, 305 m Box

LOGX CAT6A UTP LAN CABLE (305M) COPPER 0.54MM, 4 PAIR U/UTP, 23 AWG SOLID

PART NUMBER

LXC6AUUPVG305

DESCRIPTION

LOGX CAT 6A U/UTP Solid Cable is designed for enterprise data centers and next-generation 10-Gigabit Ethernet networks. Utilizing 23AWG (0.54mm) solid bare copper conductors with high-frequency skin-foam insulation and enhanced internal cross-separator to minimize alien crosstalk up to 500MHz bandwidth.

FEATURES & BENEFITS

Solid 23AWG Bare Copper Conductors (0.54mm)

Supports 10GBASE-T 10-Gigabit Ethernet transmission up to 100 meters

Extended 500MHz Bandwidth with high signal-to-noise ratio**Enhanced Central Cross Spline** for maximum Alien Crosstalk (ANEXT) protection

100% Pass Fluke Channel / Permanent Link Test certified

305 Meter (1000 ft) Easy-Pull Dispenser Box

TYPICAL APPLICATIONS

10GBASE-T 10-Gigabit Ethernet Applications

Data Center Backbone & Server Room Structured Horizontal Cabling

High-Power PoE / PoE+ / PoE++ (IEEE 802.3af/at/bt up to 90W)

Ultra-HD 4K/8K Video Streaming and Cloud Computing

COMPLIANCE & STANDARDS

- ✓ ANSI/TIA-568.2-D Category 6A
- ✓ ISO/IEC 11801 Class EA | IEC 61156-5
- ✓ EN 50173-1 & EN 50288-10-1
- ✓ 100% Pass Fluke Test Certified
- ✓ RoHS & REACH Compliant

COLOR CODING

Pair 1	White-Blue / Blue
Pair 2	White-Orange / Orange
Pair 3	White-Green / Green
Pair 4	White-Brown / Brown

SPECIFICATIONS & TECHNICAL PARAMETERS

Product Standard	LOGX CAT6A U/UTP Solid Cable	Conductor Material	Solid Bare Copper 0.54mm (23 AWG)
Insulation	Skin-Foam-Skin PE Insulation	Central Cross Member	Enhanced PE Cross Separator (Spline)
Outer Jacket	Durable PVC (Grey Color)	Overall Diameter	7.2 ± 0.4 mm
Packaging	305M (1000ft) Easy-Pull Box	Test Performance	100% Pass Fluke Test (500 MHz)

MECHANICAL CHARACTERISTICS

Bending Radius	4 × Cable Diameter (Installed)
Max. Pulling Force	110 N Elongation ≥ 100%
Temperature Range	-20°C to +60°C (Operating)

ELECTRICAL CHARACTERISTICS

Frequency Bandwidth	Up to 500 MHz (10GBASE-T High Speed)
DC Resistance Unbal.	≤ 2.0% Delay Skew ≤ 45 ns/100m
Alien Crosstalk	Optimized suppression of ANEXT & AFEXT

ORDERING INFORMATION

PART NUMBER	DESCRIPTION	PACKAGING
LXC6AUUPVG305	CAT6A U/UTP LAN Cable, 305 m Box	305M Box