

LOGX CAT 6 U/UTP SOLID LAN CABLE

CAT6 U/UTP LAN Cable, 305 m Box

LOGX CAT6 UTP LAN CABLE (305M) 24AWG, BARE COPPER 0.52MM, PASS FLUKE TEST, GREY

PART NUMBER

LXC6UUPVG305

DESCRIPTION

LOGX CAT 6 U/UTP Solid LAN Cable is engineered for high-performance Gigabit network cabling. Built with 24AWG solid bare copper conductors (0.52mm), HDPE insulation, internal PE cross separator, and flame-retardant PVC sheath. Exceeds Category 6 transmission standards and guaranteed 100% Pass Fluke Test.

FEATURES & BENEFITS

- Solid 24AWG Bare Copper (0.52mm) for maximum signal conductivity
- Integrated PE Central Cross Separator to minimize internal crosstalk (NEXT)
- 250MHz Performance Bandwidth tested and certified
- 100% Pass Fluke Test guaranteed quality standard
- Durable, easy-strip PVC outer sheath (Grey)
- 305 Meter (1000 ft) Easy-Pull Reel in Box packaging

TYPICAL APPLICATIONS

- 1000BASE-T Gigabit Ethernet & 100BASE-TX Fast Ethernet
- Horizontal Cabling in Structured Telecommunications Networks
- High-Speed VoIP, IP CCTV Surveillance, and Smart Building Systems
- Power over Ethernet (PoE / PoE+ IEEE 802.3af/at)



COMPLIANCE & STANDARDS

- ✓ ANSI/TIA-568.2-D Category 6
- ✓ ISO/IEC 11801 Class E | IEC 61156-5
- ✓ EN 50173-1 & EN 50288-6-1
- ✓ 100% Pass Fluke Test Certified
- ✓ RoHS & REACH Compliant

COLOR CODING

|        |                       |
|--------|-----------------------|
| Pair 1 | White-Blue / Blue     |
| Pair 2 | White-Orange / Orange |
| Pair 3 | White-Green / Green   |
| Pair 4 | White-Brown / Brown   |

SPECIFICATIONS & TECHNICAL PARAMETERS

|                  |                                  |                      |                                      |
|------------------|----------------------------------|----------------------|--------------------------------------|
| Product Standard | LOGX CAT6 U/UTP Solid Cable      | Conductor Material   | Solid Bare Copper 0.52mm (24 AWG)    |
| Insulation       | High-Density Polyethylene (HDPE) | Central Cross Member | PE Cross Separator (Internal Spline) |
| Outer Jacket     | Durable PVC (Grey Color)         | Overall Diameter     | 5.8 ± 0.3 mm                         |
| Packaging        | 305M (1000ft) Easy-Pull Box      | Test Performance     | 100% Pass Fluke Test (250 MHz)       |

MECHANICAL CHARACTERISTICS

|                    |                                |
|--------------------|--------------------------------|
| Bending Radius     | 4 × Cable Diameter (Installed) |
| Max. Pulling Force | 100 N   Elongation ≥ 100%      |
| Temperature Range  | -20°C to +60°C (Operating)     |

ELECTRICAL CHARACTERISTICS

|                      |                                          |
|----------------------|------------------------------------------|
| Frequency Bandwidth  | Up to 250 MHz (Exceeds ANSI/TIA-568.2-D) |
| DC Resistance Unbal. | ≤ 2.5%   Velocity of Prop. 68%           |
| Quality Test         | 100% Pass Fluke Channel / Link Test      |

ORDERING INFORMATION

| PART NUMBER  | DESCRIPTION                     | PACKAGING |
|--------------|---------------------------------|-----------|
| LXC6UUPVG305 | CAT6 U/UTP LAN Cable, 305 m Box | 305M Box  |