

LOGX KEYSTONE JACK 180° TOOLLESS

CAT6 UTP Keystone Jack, Toolless

LOGX K1014 UTP CAT6 & CAT6A KEYSTONE JACK 180 DEGREE TOOLLESS

PART NUMBER  
LXCJ6UFT

DESCRIPTION

LOGX K1014 Toolless Keystone Jacks deliver fast, punch-free, and high-performance termination for Category 6 (250MHz) and Category 6A (500MHz) unshielded structured cabling. Engineered with a 180-degree toolless butterfly closing mechanism, phosphor bronze contacts plated with 50-microinch gold, and full compliance with PoE++ IEEE 802.3bt (up to 90W).

FEATURES & BENEFITS

- 180-Degree Toolless Termination without requiring a 110 punchdown tool
- 50µ" Gold-Plated Contacts for maximum signal integrity & anti-corrosion
- Dual T568A & T568B Color Coding with clear wire guide cap
- Compact Slim Profile fits high-density 24-port / 48-port panels & faceplates
- Supports Power over Ethernet (PoE / PoE+ / PoE++ IEEE 802.3bt up to 90W)
- High-impact flame-retardant UL 94V-0 white polycarbonate housing

TYPICAL APPLICATIONS

- Horizontal Cabling Termination in 19" Patch Panels and 86-Type Faceplates
- CAT6 (Gigabit) and CAT6A (10-Gigabit) Enterprise Data Center Networks
- High-Density Server Racks and Workstation Outlets



COMPLIANCE & STANDARDS

- ✓ ANSI/TIA-568.2-D Category 6 & Category 6A
- ✓ ISO/IEC 11801 Class E & Class EA
- ✓ IEC 60603-7-4 & IEC 60603-7-41
- ✓ IEEE 802.3bt (Type 4 PoE 90W)
- ✓ UL 94V-0 Fire Safety Standard
- ✓ RoHS & REACH Compliant

SPECIFICATIONS & TECHNICAL PARAMETERS

|                      |                                                |                 |                                                 |
|----------------------|------------------------------------------------|-----------------|-------------------------------------------------|
| Product Standard     | LOGX K1014 180° Toolless Keystone Jack         | Shielding Type  | UTP (Unshielded)                                |
| Housing Material     | Flame-Retardant Polycarbonate (UL 94V-0)       | RJ45 Contacts   | Phosphor Bronze with 50µ" Gold Plating          |
| Termination Type     | 180-Degree Toolless Butterfly Latch & Wire Cap | Wiring Standard | Dual T568A & T568B Color Coded                  |
| Supported Conductors | Solid & Stranded 22-26 AWG Copper              | Durability      | ≥ 750 Insertions (RJ45)   ≥ 250 Re-terminations |

MECHANICAL CHARACTERISTICS

|                     |                                      |
|---------------------|--------------------------------------|
| Plug Insertion Life | 750 Mating Cycles                    |
| IDC Re-terminations | 250 Cycles (22-26 AWG)               |
| Holding Force       | 30 lbs (133 N) between plug and jack |

ELECTRICAL CHARACTERISTICS

|                     |                                             |
|---------------------|---------------------------------------------|
| Contact Resistance  | ≤ 20 mΩ   Insulation Res. ≥ 500 MΩ          |
| Dielectric Strength | 1000V AC RMS 60Hz 1 Min                     |
| Current Rating      | 1.5 Amps   PoE/PoE++ Compatible (up to 90W) |

ORDERING INFORMATION

| PART NUMBER | DESCRIPTION                       | CATEGORY |
|-------------|-----------------------------------|----------|
| LXCJ6UFT    | CAT6 UTP Keystone Jack, Toolless  | CAT 6    |
| LXCJ6AUFT   | CAT6A UTP Keystone Jack, Toolless | CAT 6A   |