

LOGX RJ45 MODULAR PLUGS

8P8C UTP RJ45 Modular Plug

LOGX S0088 & S0288 8P8C RJ45 MODULAR PLUGS, UTP & FTP SHIELDED

PART NUMBER

LXCPUTC6

DESCRIPTION

LOGX S0088 and S0288 RJ45 Modular Plugs are precision engineered for reliable field termination of Category 6 (UTP) and Category 6A (FTP) patch cords and device links. Built with high-transparency flame-retardant polycarbonate housing, 3-prong gold-plated contacts, and an independent wire load bar / insert guide for rapid, error-free conductor alignment.

FEATURES & BENEFITS

- Precision 3-Prong Gold-Plated Contacts** for solid and stranded conductors
- Separate Wire Load Bar / Insert Guide** for optimal pair separation and fast wiring
- Crystal-Clear Flame-Retardant Polycarbonate Housing** (UL 94V-0 rated)
- Available in UTP (Unshielded) and FTP (Shielded Metal Shell) versions
- Supports Power over Ethernet (PoE / PoE+ IEEE 802.3af/at)
- Supplied in convenient 100 pcs/bag packaging

TYPICAL APPLICATIONS

- Fabrication of Custom High-Performance CAT6 / CAT6A Patch Cords
- Direct Device Termination (IP CCTV Cameras, Wi-Fi Access Points, VoIP Phones)
- Modular Plug Terminated Link (MPTL) Field Connections



COMPLIANCE & STANDARDS

- ✓ ANSI/TIA-568.2-D Category 6 & 6A
- ✓ ISO/IEC 11801 Class E & Class EA
- ✓ IEC 60603-7 (8P8C Connector Standard)
- ✓ UL 94V-0 Flame Safety Standard
- ✓ RoHS & REACH Compliant

SPECIFICATIONS & TECHNICAL PARAMETERS

Plug Series	LOGX S0088 / S0288 8P8C Modular Plug	Housing Material	Crystal Clear Polycarbonate (UL 94V-0 Rated)
Shielding / Rating	UTP (CAT6) / FTP Metal Shield (CAT6A)	Contact Pins	Phosphor Bronze with Gold Plated 3-Prong Contacts
Supported Conductors	24-28 AWG Stranded & Solid Copper Wires	Wire Alignment	Includes Dedicated Wire Load Bar / Insert Guide
Durability	≥ 1000 Mating / Insertion Cycles	Quality Standard	100% Pass Fluke Component Test

MECHANICAL CHARACTERISTICS

Cable-to-Plug Tension	89 N (20 lbs) retention strength
Mating Durability	1000 Insertion Cycles
Operating Temp.	-20°C to +60°C

ELECTRICAL CHARACTERISTICS

Current / Voltage	1.5A Max. at 25°C 150V AC
Contact Resistance	≤ 20 mΩ Insulation Res. ≥ 500 MΩ
Dielectric Strength	1000V AC RMS 1 Min (Contact to Contact)

ORDERING INFORMATION

PART NUMBER	DESCRIPTION	PACKAGING
LXCPUTC6	8P8C UTP RJ45 Modular Plug	UTP CAT6 Plug
LXCPSTC6A	8P8C FTP Shielded RJ45 Plug	FTP CAT6A Plug