

LOGX FTTH SM DROP FIBER OPTIC CABLE

Armoured Single-Mode Drop Cable, 12 Core — 1000 m

LOGX 4, 8 & 12 CORE SM FTTH DROP CABLE (1000M)

PART NUMBER
LXFHS127ALS

DESCRIPTION

LOGX FTTH Single Mode Drop Fiber Cables are designed for Fiber-to-the-Home (FTTH) subscriber drops and indoor/outdoor distribution. Built with ITU-T G.657.A1 bend-insensitive fibers, dual dielectric FRP strength members, corrugated light steel tape armoring (for 8 & 12 cores), and flame-retardant LSZH outer jacket.

- FEATURES & BENEFITS
- ITU-T G.657.A1 Bend-Insensitive Optical Fiber for tight radius routing

Dual Dielectric FRP Strength Members for superior anti-electromagnetic performance

Corrugated Light Steel Tape Armoring (8C & 12C) for rodent and crush protection

Low Smoke Zero Halogen (LSZH) Jacket for enhanced fire safety compliance

Compact, lightweight, and flexible structure for easy stripping and splicing

Standard 1000 Meter (1KM) wooden drum packaging
- COMPLIANCE & STANDARDS

✓ ITU-T G.657.A1 & ITU-T G.652.D

✓ IEC 60793 / IEC 60794

✓ IEC 60332-1 (Flame Retardant) & IEC 60754 (Halogen Free)

✓ RoHS & REACH Compliant



TYPICAL APPLICATIONS

FTTH Access Networks and Last-Mile Subscriber Drop Links
Indoor Riser and Horizontal Optical Distribution in Multi-Dwelling Units (MDU)
Direct Underground Conduit or Indoor Duct Installations

SPECIFICATIONS & TECHNICAL PARAMETERS			
Fiber Type	G.657.A1 Single Mode Optical Fiber (Bend-Insensitive)	Core Options	4 Core / 8 Core / 12 Core
Strength Member	Dual Non-Metallic FRP (Fiber Reinforced Plastic)	Armoring (8 & 12 Core)	Corrugated Light Steel Tape Armored (Rodent-Proof)
Outer Sheath	Low Smoke Zero Halogen (LSZH) / UV Resistant	Cable Diameter	3.0mm ± 0.2mm (4C) / 6.0mm ± 0.4mm (8C/12C)
Attenuation	≤ 0.36 dB/km (1310nm) ≤ 0.22 dB/km (1550nm)	Packaging	1000 Meters (1KM) Wooden Drum Reel

MECHANICAL CHARACTERISTICS		ENVIRONMENTAL SPECIFICATIONS	
Tensile Strength	Long Term ≥ 300N Short Term ≥ 600N	Operating Temp.	-40°C to +70°C
Crush Resistance	Long Term ≥ 1000N/100mm Short Term ≥ 2200N	Installation Temp.	-20°C to +60°C
Min. Bend Radius	15 mm (Dynamic) 10 mm (Static - G.657.A1)	Fire Rating	LSZH (IEC 60332-1, IEC 60754, IEC 61034)

ORDERING INFORMATION		
PART NUMBER	DESCRIPTION	PACKAGING
LXFHN047ALS	Single-Mode Drop Cable, 4 Core — 1000 m	4 Core
LXFHS087ALS	Armoured Single-Mode Drop Cable, 8 Core — 1000 m	8 Core Armoured
LXFHS127ALS	Armoured Single-Mode Drop Cable, 12 Core — 1000 m	12 Core Armoured