

LOGX 19 INCH SLIDING FIBER PATCH PANEL

48 Port LC Duplex Fiber Patch Panel, 2U

LOGX 6, 12, 24 & 48 PORT LC DUPLEX LOADED FIBER PATCH PANEL

PART NUMBER

LXFPRDLC48

DESCRIPTION

LOGX Sliding Rail Fiber Optic Patch Panels provide high-density fiber patching and splicing in standard 19-inch equipment racks. Pre-loaded with high-precision LC/UPC duplex adapters, smooth telescopic ball-bearing sliding rails for easy front maintenance, and complete internal splice management trays.

COMPLIANCE & STANDARDS

✓ EIA/ECA-310-E Standard 19" Specifications

✓ TIA/EIA-568.3-D & ISO/IEC 11801

✓ Telcordia GR-326-CORE Compliant Adapters

✓ RoHS & REACH Compliant

- FEATURES & BENEFITS
- Pre-Loaded with LC/UPC Duplex Singlemode Adapters with zirconia sleeves

Smooth Telescopic Ball-Bearing Sliding Drawer for easy front access without removing unit

Complete Splice Kit Included (Splice trays, heatshrink holders, and protective sleeves)

4 Rear Cable Entry Ports equipped with cable clamps and rubber protection glands

Constructed from 1.2mm electro-galvanized cold-rolled steel with black powder finish

Available in 1U (6, 12, 24 Port) and 2U (48 Port) configurations

TYPICAL APPLICATIONS

Data Center Fiber Density Patching & Main Cross-Connect (MC)

Telecom Central Offices, FTTx Core Nodes, and Enterprise Racks

High-Speed 10G/40G/100G Optical Backbone Distribution

SPECIFICATIONS & TECHNICAL PARAMETERS

Product Standard	LOGX 19" Sliding Rail Fiber Patch Panel	Adapter Type	Loaded with LC/UPC Duplex Singlemode Adapters (Blue)
Capacities Available	6 Port (1U) / 12 Port (1U) / 24 Port (1U) / 48 Port (2U)	Chassis Material	1.2mm High-Strength Cold-Rolled Steel (SPCC)
Sliding Mechanism	Smooth Telescopic Ball-Bearing Drawer Rails	Splice Management	Includes Splice Trays, Heatshrink Sleeves & Cable Glands
Cable Entry Ports	4 Rear Cable Entry Ports with Rubber Grommets	Surface Finish	Electrostatic Matte Black Powder Coating

MECHANICAL CHARACTERISTICS

SPLICE CAPACITY & ACCESSORIES

Drawer Extension	Full 100% Extension Sliding Drawer	Splice Trays	Stackable ABS Trays (24 Fibers per tray)
Adapter Ceramic Sleeve	Zirconia Ceramic Alignment Sleeve (≤ 0.2dB Loss)	Accessories Included	Splice Sleeves, PG Glands, Cable Ties, M6 Screws
Mounting Dimensions	Standard 19-Inch EIA Rack Width	Operating Temp.	-40°C to +80°C

ORDERING INFORMATION

PART NUMBER	DESCRIPTION	RACK SIZE
LXFPRDLC12	12 Port LC Duplex Fiber Patch Panel, 1U	12 Port (1U)
LXFPRDLC24	24 Port LC Duplex Fiber Patch Panel, 1U	24 Port (1U)
LXFPRDLC48	48 Port LC Duplex Fiber Patch Panel, 2U	48 Port (2U)