



Loaded Adapters	Pre-loaded with LC/UPC Duplex SM Adapters	Adapter Polish	UPC
Material	Cold Rolled Steel	Surface Finish	Black Powder Coating
Mounting Type	Wall Mount	Splice Tray Capacity	4 Fibers (4 Port) / 8 Fibers (8 Port), Heat Shrink
Dimensions (W×D×H)	160 × 100 × 30 mm (4 Port)		

MECHANICAL CHARACTERISTICS

Chassis Material	Cold Rolled Steel, Black Powder Coated
Cable Entry	4 × Ø 3 mm Inlets
Cover	Snap-On Lock Cover with Anti-Tamper Screw

OPTICAL & ADAPTER SPECIFICATIONS

Adapter Type	LC Duplex, Single Mode
Port Capacity	4 Ports / 8 Ports LC Duplex
Sleeve Material	Zirconia Ceramic Alignment Sleeve

Ordering information

Part number	Description	Capacity
LXFTBLC04	4 Port LC Fiber Terminal Box	4 Port (8 Fibers)
LXFTBLC08	8 Port LC Fiber Terminal Box	8 Port (16 Fibers)

© LOGX NETWORK · Specifications subject to change without notice.logxnetwork.com/en/products/8-port-lc-fiber-terminal-box-lxftblc08 · sales@logxnetwork.com

LOGXNETWORK

Structured cabling, fiber optic distribution and rack infrastructure — supplied as one connected range.

Products

- [Copper cabling](#)
- [Fiber optic](#)
- [Racks & accessories](#)
- [Datasheets](#)

Contact

- [Request a quotation](#)
- sales@logxnetwork.com
- [About](#)
- [Company profile](#)

Offices

Head officeLOGX NETWORKS LTD.71-75 Shelton Street, Covent Garden, London, United Kingdom

Middle East distributorNetworks Sea CompanyOlaya, Riyadh, Saudi Arabia

© 2026 LOGX NETWORK · Specifications subject to change without notice.

[Privacy](#)[Terms](#)