



Buffer Diameter	0.9 mm Tight Buffer	Jacket Material	PVC (OFNR)
Lengths Available	1.5 Meters / 2.0 Meters	Ferrule Material	Precision Zirconia Ceramic
Insertion Loss	≤ 0.3 dB	Return Loss	≥ 50 dB (Single Mode UPC) ≥ 30 dB (OM3)

OPTICAL CHARACTERISTICS

Insertion Loss	≤ 0.3 dB
Return Loss	≥ 50 dB (SM UPC) ≥ 30 dB (OM3)
Operating Wavelength	1310 / 1550 nm (SM) 850 / 1300 nm (OM3)

ENVIRONMENTAL SPECIFICATIONS

Operating Temp.	-20°C to +70°C
Jacket Material	PVC (OFNR)
Standard Compliance	Telcordia GR-326-CORE, IEC 61754-20

Ordering information

Part number	Description	Length
LXFTLCSUS21.5	LC/UPC Single-Mode Pigtail, 1.5 m	1.5M · Single Mode OS2
LXFTLCSUS22	LC/UPC Single-Mode Pigtail, 2 m	2.0M · Single Mode OS2
LXFTLCSUM31.5	LC/UPC OM3 Pigtail, 1.5 m	1.5M · Multimode OM3
LXFTLCSUM32	LC/UPC OM3 Pigtail, 2 m	2.0M · Multimode OM3

© LOGX NETWORK · Specifications subject to change without notice.logxnetwork.com/en/products/lc-upc-om3-pigtail-1-5-m-lxftlcsus21-5 · sales@logxnetwork.com

LOGXNETWORK

Structured cabling, fiber optic distribution and rack infrastructure — supplied as one connected range.

Products

- [Copper cabling](#)
- [Fiber optic](#)
- [Racks & accessories](#)
- [Datasheets](#)

Contact

- [Request a quotation](#)
- sales@logxnetwork.com
- [About](#)
- [Company profile](#)

Offices

Head officeLOGX NETWORKS LTD.71-75 Shelton Street, Covent Garden, London, United Kingdom

Middle East distributorNetworks Sea CompanyOlaya, Riyadh, Saudi Arabia

© 2026 LOGX NETWORK · Specifications subject to change without notice.

[Privacy](#)[Terms](#)