



LOGIX LIFTLOCKED 100ft

100ft (30.5m) Patch Cord, Cat 5e, RJ45 to RJ45

MADE IN CHINA



LOGIX
NETWORK

Buffer Diameter	0.9 mm Tight Buffer	Jacket Material	PVC (OFNR)
Lengths Available	1.5 Meters / 2.0 Meters	Ferrule Material	Precision Zirconia Ceramic
Insertion Loss	≤ 0.3 dB	Return Loss	≥ 50 dB (Single Mode UPC) ≥ 30 dB (OM3)

OPTICAL CHARACTERISTICS

Insertion Loss	≤ 0.3 dB
Return Loss	≥ 50 dB (SM UPC) ≥ 30 dB (OM3)
Operating Wavelength	1310 / 1550 nm (SM) 850 / 1300 nm (OM3)

ENVIRONMENTAL SPECIFICATIONS

Operating Temp.	-20°C to +70°C
Jacket Material	PVC (OFNR)
Standard Compliance	Telcordia GR-326-CORE, IEC 61754-20

Ordering information

Part number	Description	Length
LXFTLCSUS21.5	LC/UPC Single-Mode Pigtail, 1.5 m	1.5M · Single Mode OS2
LXFTLCSUS22	LC/UPC Single-Mode Pigtail, 2 m	2.0M · Single Mode OS2
LXFTLCSUM31.5	LC/UPC OM3 Pigtail, 1.5 m	1.5M · Multimode OM3
LXFTLCSUM32	LC/UPC OM3 Pigtail, 2 m	2.0M · Multimode OM3

© LOGX NETWORK · Specifications subject to change without notice.logxnetwork.com/en/products/lc-upc-single-mode-pigtail-2-m-lxftlcsus22 · sales@logxnetwork.com

LOGXNETWORK

Structured cabling, fiber optic distribution and rack infrastructure — supplied as one connected range.

Products

- [Copper cabling](#)
- [Fiber optic](#)
- [Racks & accessories](#)
- [Datasheets](#)

Contact

- [Request a quotation](#)
- sales@logxnetwork.com
- [About](#)
- [Company profile](#)

Offices

Head officeLOGX NETWORKS LTD.71-75 Shelton Street, Covent Garden, London, United Kingdom

Middle East distributorNetworks Sea CompanyOlaya, Riyadh, Saudi Arabia

© 2026 LOGX NETWORK · Specifications subject to change without notice.

[Privacy](#)[Terms](#)