

Prosthetic Hand

Dylan Duunk

Discipulus-Ex

March 15, 2019

Abstract

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Contents

1	Introduction	1
2	Materials	1
2.1	Plastic	1
2.2	Silicone	1
2.3	Carbon Fiber	2
2.4	Metal	2
3	Morphological chart	2

1 Introduction

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

2 Materials

2.1 Plastic

PLA and ABS are 2 of the most common FDM (Fused deposition modeling) desktop printing materials. Both materials are thermoplastics, meaning they become pliable or moldable at a certain elevated temperature and solidifies upon cooling. Via the FDM process, both materials are melted and then extruded through a nozzle to build up the layers that create a final part.

Table 1 below compares the main properties between PLA & ABS:

Properties ¹	PLA	ABS
Density	1.3g/cm ³	1.0 – 1.4g/cm ³
Elongation	6%	3.5-50%
Flexural Modulus	4GPa	2.1-7.6 GPa
Melting Point	160 °C	N/A (amorphous)
Biodegradable	Yes, under the correct conditions	No
Glass Transition Temperature	60 °C	105 °C

Table 1: Comparing PLA with ABS

¹ Sourced from *MakeItFrom* [1]

2.2 Silicone

Silicone is a dynamic material that moves with the body while simultaneously offering an enhanced grip on the residual limb and improved suspension of the prosthesis. Silicone is mostly used in realistic looking prosthetics and for mold making.

Table 2 below gives the main properties of silicone:

Properties ¹	Silicone plastic
Density	1.9g/cm ³
Elastic Modulus	9.0 GPa
Max. Temperature: Decomposition	480 °C
Biodegradable	No
Glass Transition Temperature	200 °C

Table 2: Properties silicone plastic

¹ Sourced from *MakeItFrom* [1]

2.3 Carbon Fiber

Carbon fiber reinforced plastic (CFRP), is an extremely strong and light fiber-reinforced plastic which contains carbon fibers. Carbon fiber is often used in prosthetics, sports equipment, aerospace and wherever the high strength-to-weight ratio and stiffness from carbon fiber are required. CFRPs are composite materials. In this case the composite consists of two parts: a matrix and a reinforcement. In this case the reinforcement is carbon fiber, which provides the strength. The matrix is usually a polymer resin, such as epoxy, to bind the reinforcements together. This makes the material properties depend on those distinct elements.

2.4 Metal

Alloys containing titanium are known for their high strength, lightweight, and exceptional corrosion resistance. Despite being as strong as steel, titanium is about 40% lighter in weight. Titanium is also formidable in its resistance to corrosion by both water and chemical media.

Because titanium has a low modulus of elasticity that means titanium is not also very flexible, but returns to its original shape after bending.

Aluminium is a very light metal with a specific weight of 2.7g/cm³, about a third that of steel. Its strength can be adapted to the application required by modifying the composition of its alloys. Aluminium naturally generates a protective oxide coating and is highly corrosion resistant which can be further improved by different types of surface treatments. This is particularly useful for applications where protection and conservation are required.

3 Morphological chart

	PLA	ABS	Silicone	Carbon	Titanium ¹	Aluminium ¹
Easy of use	★★★★★	★★★★☆	★★★☆☆	★★★☆☆	★★☆☆☆	★★★☆☆
Strength	★★☆☆☆	★★★★☆	★★★★☆	★★★★★	★★★★★	★★★★★
Weight ²	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★
Elastic Modulus	★★☆☆☆	★★★★☆	★★★★★	★★★☆☆	★★★★★	★★★☆☆
Price	★★★★★	★★★★★	★★★★☆	★★★☆☆	★★☆☆☆	★★★☆☆
Usability ³	★★★★★	★★★★☆	★★★☆☆	★★☆☆☆	☆☆☆☆☆	★★☆☆☆

Table 3: Materials Morphological Chart

These values in this Morphological Chart are based on eachother.

¹ The material properties of these materials can vary based on the alloys used.

² Weight is based on how lightweight the material is.

³ Usability in this case is based on how usefull this material will be for our prototype.

References

- [1] MakeItFrom. Material properties database. Available at <https://www.makeitfrom.com/>, 2009.