

## Alternating quantifiers strategies rna examples

### Alternating nested quantifiers

$$\forall s \in S \exists b \in B ( \text{basecount}(s, b) = 3 )$$

In English: For each RNA strand there is a base that occurs 3 times in this strand.

Write the negation and use De Morgan's law to find a logically equivalent version where the negation is applied only to the  $BC$  predicate (not next to a quantifier).

Is the original statement **True** or **False**?

$$\exists s \in S \forall b \in B \exists n \in \mathbb{N} ( \text{basecount}(s, b) = n )$$

In English: There is an RNA strand so that for each base there is some nonnegative integer that counts the number of occurrences of that base in this strand.

Write the negation and use De Morgan's law to find a logically equivalent version where the negation is applied only to the  $BC$  predicate (not next to a quantifier).

Is the original statement **True** or **False**?

## Defining functions more examples

Let's practice with functions related to some of our applications so far.

Recall: We model the collection of user ratings of the four movies Superman, Wicked, KPop Demon Hunters, A Minecraft Movie as the set  $\{-1, 0, 1\}^4$ . One function that compares pairs of ratings is

$$d_0 : \{-1, 0, 1\}^4 \times \{-1, 0, 1\}^4 \rightarrow \mathbb{R}$$

given by

$$d_0((x_1, x_2, x_3, x_4), (y_1, y_2, y_3, y_4)) = \sqrt{(x_1 - y_1)^2 + (x_2 - y_2)^2 + (x_3 - y_3)^2 + (x_4 - y_4)^2}$$

Notice: any ordered pair of ratings is an okay input to  $d_0$ .

Notice: there are (at most)

$$(3 \cdot 3 \cdot 3 \cdot 3) \cdot (3 \cdot 3 \cdot 3 \cdot 3) = 3^8 = 6561$$

many pairs of ratings. There are therefore lots and lots of real numbers that are not the output of  $d_0$ .

Recall: RNA is made up of strands of four different bases that encode genomic information in specific ways. The bases are elements of the set  $B = \{\mathbf{A}, \mathbf{C}, \mathbf{U}, \mathbf{G}\}$ . The set of RNA strands  $S$  is defined (recursively) by:

$$\begin{array}{ll} \text{Basis Step:} & \mathbf{A} \in S, \mathbf{C} \in S, \mathbf{U} \in S, \mathbf{G} \in S \\ \text{Recursive Step:} & \text{If } s \in S \text{ and } b \in B, \text{ then } sb \in S \end{array}$$

where  $sb$  is string concatenation.

**Pro-tip:** informal definitions sometime use  $\dots$  to indicate “continue the pattern”. Often, to make this pattern precise we use recursive definitions.

| Name                        | Domain                           | Codomain       | Rule                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Example                                                                                                                |
|-----------------------------|----------------------------------|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <i>rnalen</i>               | $S$                              | $\mathbb{Z}^+$ | <p>Basis Step:<br/>           If <math>b \in B</math> then <math>rnalen(b) = 1</math><br/>           Recursive Step:<br/>           If <math>s \in S</math> and <math>b \in B</math>, then<br/> <math>rnalen(sb) = 1 + rnalen(s)</math></p>                                                                                                                                                                                                                                                                                                                   | $rnalen(\mathbf{AC}) \stackrel{\text{rec step}}{=} 1 + rnalen(\mathbf{A})$ $\stackrel{\text{basis step}}{=} 1 + 1 = 2$ |
| <i>basecount</i>            | $S \times B$                     | $\mathbb{N}$   | <p>Basis Step:<br/>           If <math>b_1 \in B, b_2 \in B</math> then<br/> <math>basecount( (b_1, b_2) ) =</math> <math display="block">\begin{cases} 1 &amp; \text{when } b_1 = b_2 \\ 0 &amp; \text{when } b_1 \neq b_2 \end{cases}</math>           Recursive Step:<br/>           If <math>s \in S, b_1 \in B, b_2 \in B</math><br/> <math>basecount( (sb_1, b_2) ) =</math> <math display="block">\begin{cases} 1 + basecount( (s, b_2) ) &amp; \text{when } b_1 = b_2 \\ basecount( (s, b_2) ) &amp; \text{when } b_1 \neq b_2 \end{cases}</math></p> | $basecount( (\mathbf{ACU}, \mathbf{C}) ) =$                                                                            |
| “2 to the power of”         | $\mathbb{N}$                     | $\mathbb{N}$   | <p>Basis Step:<br/> <math>2^0 = 1</math><br/>           Recursive Step:<br/>           If <math>n \in \mathbb{N}, 2^{n+1} =</math></p>                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                        |
| “ $b$ to the power of $i$ ” | $\mathbb{Z}^+ \times \mathbb{N}$ | $\mathbb{N}$   | <p>Basis Step:<br/> <math>b^0 = 1</math><br/>           Recursive Step:<br/>           If <math>i \in \mathbb{N}, b^{i+1} = b \cdot b^i</math></p>                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                        |

$2^0 = 1$ 
 $2^1 = 2$ 
 $2^2 = 4$ 
 $2^3 = 8$ 
 $2^4 = 16$ 
 $2^5 = 32$ 
 $2^6 = 64$ 
 $2^7 = 128$ 
 $2^8 = 256$ 
 $2^9 = 512$ 
 $2^{10} = 1024$

# Defining sets

*To define sets:*

To define a set using **roster method**, explicitly list its elements. That is, start with  $\{$  then list elements of the set separated by commas and close with  $\}$ .

To define a set using **set builder definition**, either form “The set of all  $x$  from the universe  $U$  such that  $x$  is ...” by writing

$$\{x \in U \mid ...x...\}$$

or form “the collection of all outputs of some operation when the input ranges over the universe  $U$ ” by writing

$$\{...x... \mid x \in U\}$$

We use the symbol  $\in$  as “is an element of” to indicate membership in a set.

**Example sets:** For each of the following, identify whether it's defined using the roster method or set builder notation and give an example element.

Can we infer the data type of the example element from the notation?

$$\{-1, 1\}$$

$$\{0, 0\}$$

$$\{-1, 0, 1\}$$

$$\{(x, x, x) \mid x \in \{-1, 0, 1\}\}$$

$$\{\}$$

$$\{x \in \mathbb{Z} \mid x \geq 0\}$$

$$\{x \in \mathbb{Z} \mid x > 0\}$$

$$\{\cup, \otimes\}$$

$$\{\text{A}, \text{C}, \text{U}, \text{G}\}$$

$$\{\text{AUG}, \text{UAG}, \text{UGA}, \text{UAA}\}$$

## Rna motivation

RNA is made up of strands of four different bases that encode genomic information in specific ways. The bases are elements of the set  $B = \{\text{A}, \text{C}, \text{U}, \text{G}\}$ . Strands are ordered nonempty finite sequences of bases.

Formally, to define the set of all RNA strands, we need more than roster method or set builder descriptions.

## Set recursive examples

**Definition** The set of nonnegative integers  $\mathbb{N}$  is defined (recursively) by:

Basis Step:

Recursive Step:

Examples:

**Definition** The set of all integers  $\mathbb{Z}$  is defined (recursively) by:

Basis Step:

Recursive Step:

Examples:

**Definition** The set of RNA strands  $S$  is defined (recursively) by:

Basis Step:  $\mathbf{A} \in S, \mathbf{C} \in S, \mathbf{U} \in S, \mathbf{G} \in S$

Recursive Step: If  $s \in S$  and  $b \in B$ , then  $sb \in S$

where  $sb$  is string concatenation.

Examples:

**Definition** The set of bitstrings (strings of 0s and 1s) is defined (recursively) by:

Basis Step:

Recursive Step:

*Notation:* We call the set of bitstrings  $\{0, 1\}^*$  and we say this is the set of all strings over  $\{0, 1\}$ .

Examples: