# Algorithm definition

**New!** An algorithm is a finite sequence of precise instructions for solving a problem.

Algorithms can be expressed in English or in more formalized descriptions like pseudocode or fully executable programs.

Sometimes, we can define algorithms whose output matches the rule for a function we already care about. Consider the (integer) logarithm function

$$logb : \{b \in \mathbb{Z} \mid b > 1\} \times \mathbb{Z}^+ \quad \rightarrow \quad \mathbb{N}$$

defined by

$$logb(\ (b, n)\ ) = \text{greatest integer } y \text{ so that } b^y \text{ is less than or equal to } n$$

Calculating integer part of base $b$ logarithm

```
1   procedure logb(b,n: positive integers with b>1)
2   i := 0
3   while n > b-1
4     i := i+1
5     n := n div b
6   return i {i holds the integer part of the base b logarithm of n}
```

Trace this algorithm with inputs $b = 3$ and $n = 17$

| | $b$ | $n$ | $i$ | $n > b - 1$? |
|---|---|---|---|---|
| Initial value | 3 | 17 | | |
| After 1 iteration | | | | |
| After 2 iterations | | | | |
| After 3 iterations | | | | |
| | | | | |

Compare: does the output match the rule for the (integer) logarithm function?

CC BY-NC-SA 2.0 Version October 19, 2026 (1)

# Base expansion algorithms

### Two algorithms for constructing base $b$ expansion from decimal representation

**Most significant first**: Start with left-most coefficient of expansion (highest value)

*Informally*: Build up to the value we need to represent in "greedy" approach, using units determined by base.

Calculating base $b$ expansion, from left

```
1  procedure basebmost(n,b: positive integers with b>1)
2  v := n
3  k := 1+ output of logb algorithm with inputs b and n
4  for i := 1 to k
5     a_{k-i} := 0
6     while v ≥ b^{k-i}
7        a_{k-i} := a_{k-i} + 1
8        v := v - b^{k-i}
9  return (a_{k-1},...,a_0){(a_{k-1}...a_0)_b is the base b expansion of n}
```

CC BY-NC-SA 2.0 Version October 19, 2026 (2)

**Least significant first**: Start with right-most coefficient of expansion (lowest value)

Idea: (when $k > 1$)

$$\begin{aligned} n &= a_{k-1}b^{k-1} + \cdots + a_1 b + a_0 \\ &= b(a_{k-1}b^{k-2} + \cdots + a_1) + a_0 \end{aligned}$$

so $a_0 = n$ **mod** $b$ and $a_{k-1}b^{k-2} + \cdots + a_1 = n$ **div** $b$.

Calculating base $b$ expansion, from right

```
1  procedure basebleast(n,b: positive integers with b>1)
2  k := 0
3  q := n
4  while q ≠ 0
5     a_k := q mod b
6     k := k+1
7     q := q div b
8  return (a_{k-1},...,a_0){(a_{k-1}...a_0)_b is the base b expansion of n}
```

CC BY-NC-SA 2.0 Version October 19, 2026 (3)

# Base conversion algorithm

Practice: write an algorithm for converting from base $b_1$ expansion to base $b_2$ expansion:

CC BY-NC-SA 2.0 Version October 19, 2026 (4)