

Problem Set 3 Exercise #08: Rotate Right K

Reference: Lecture 7 notes

Learning objective: One-dimensional array

Estimated completion time: 30 minutes

Problem statement:

[CS1010 AY2012/13 Semester 1 Midterm Test, Q9]

Write a program **rotate_right.c** that contain a function

```
void rotate_right_k(int arr[], int size, int k)
```

that takes an array **arr** of **size** ($1 \leq \text{size} \leq 100$) elements, rotate it **k** positions to the right, where **k** is a positive integer. For example, given an array **arr** {1, 2, 3, 4, 5, 6},

- Calling **rotate_right_k(arr, 6, 1)** would result in **arr** becoming {6, 1, 2, 3, 4, 5}.
- Calling **rotate_right_k(arr, 6, 3)** would result in **arr** becoming {4, 5, 6, 1, 2, 3}.
- Calling **rotate_right_k(arr, 6, 60002)** would result in **arr** becoming {5, 6, 1, 2, 3, 4}.

A tip is given at the beginning of next page.

Sample run #1:

```
Enter the number of elements: 6
Enter 6 elements: 1 2 3 4 5 6
Enter k: 1
[6, 1, 2, 3, 4, 5]
```

Sample run #2:

```
Enter the number of elements: 6
Enter 6 elements: 1 2 3 4 5 6
Enter k: 3
[4, 5, 6, 1, 2, 3]
```

Sample run #3:

```
Enter the number of elements: 6
Enter 6 elements: 1 2 3 4 5 6
Enter k: 60002
5 6 1 2 3 4
```

Useful tip:

It might be useful to write another function

```
void rotate_right_1(int arr[], int size)
```

that rotates the array **arr** to the right by 1 position.

It may be called by the **rotate_right_k()** function.