

```
SELECT EMP_CITY,COUNT(*) AS CNT FROM EMPLOYEES GROUP BY  
EMP_CITY
```

	emp_city character varying (100)	cnt bigint
1	Mumbai	2
2	Delhi	2
3	Bangalore	2
4	Kolkata	1

```
SELECT EMP_CITY, COUNT(EMP_ID) AS CNT FROM EMPLOYEES  
GROUP BY EMP_CITY
```

	emp_city character varying (100)	cnt bigint
1	Mumbai	2
2	Delhi	2
3	Bangalore	2
4	Kolkata	1

```
SELECT EMP_CITY, SUM (CASE WHEN EMP_SALARY>=90000 THEN 1 ELSE 0 END) AS CNT FROM  
EMPLOYEES  
GROUP BY EMP_CITY
```

	emp_city character varying (100)	cnt bigint
1	Mumbai	1
2	Delhi	0
3	Bangalore	2
4	Kolkata	0

```
SELECT EMP_CITY,SUM(CASE WHEN EMP_SALARY>=90000 THEN 1 ELSE 0 END) AS CNT FROM  
EMPLOYEES  
GROUP BY EMP_CITY  
ORDER BY EMP_CITY DESC
```

	emp_city character varying (100)	cnt bigint
1	Mumbai	1
2	Kolkata	0
3	Delhi	0
4	Bangalore	2

SELECT EMP_CITY,SUM(CASE WHEN EMP_SALARY>=90000 THEN 1 ELSE 0 END) AS CNT FROM
EMPLOYEES

GROUP BY EMP_CITY

ORDER BY CNT DESC,EMP_CITY DESC

	emp_city character varying (100)	cnt bigint
1	Bangalore	2
2	Mumbai	1
3	Kolkata	0
4	Delhi	0

SELECT EMP_CITY AS CNT FROM EMPLOYEES

GROUP BY EMP_CITY

HAVING COUNT(EMP_ID)>=2

	cnt character varying (100)
1	Mumbai
2	Delhi
3	Bangalore

SELECT DISTINCT EMP_CITY

FROM EMPLOYEES

	emp_city character varying (100)
1	Mumbai
2	Delhi
3	Bangalore
4	Kolkata